

Attachment #1

Introduction:

- The objectives of this acquisition is to award a contract for the purchase of walk behind floor scrubbers for CMNT activities.
- The outcomes desired by WMATA is to purchase new walk behind floor scrubbers or replace uneconomical repairable walk behind floor scrubbers.
- Benefits of this acquisition to WMATA are to improve work areas safety and environmental conditions.

Background:

Many floor scrubbers used by CMNT personnel have exceeded their life expectancy, are in need of repair or are uneconomical to repair. Overhaul work areas constantly require the use of floors scrubbed to remove oil, grease or chemicals. As these scrubbers become aged and fail or become uneconomical to repair, they must be replaced to keep the work area environmentally safe and environmentally friendly. The average life expectancy of floor scrubbers is 8 years. Some of CMNT's scrubbers have exceeded this life expectancy or are approaching it. A two year contract will permit CMNT to replace these aging floor scrubbers.

Current Scope of Work:

- The successful vendor is expected to deliver an Advance SC900 Floor Scrubber or equivalent floor scrubbers that comply with or exceed the specifications listed below.

Deliverables:

- The successful vendor shall deliver floor scrubbers ordered by the ordering officers listed below.
- Vendor must deliver floor scrubbers within 8 weeks after receipt of an order from the ordering officer.
- Vendor will deliver floor scrubbers to the ordering officer location listed below.
- Vendor will provide familiarization training on each scrubber delivered.

Performance and Acceptance Criteria:

- Vendor must ship scrubbers to the ordering officer's location within 8 weeks.
- Floor scrubbers must be fully operational upon delivery to the ordering officer's location.

Technical Specifications:

- Minimum 24 volt AGM battery
- Minimum 360 242 ah WET battery
- Minimum runtime 5 hours
- Battery charger input 120 volts AC, 60 Hz, output 24 volts DC/ 30 amp
- Minimum solution tank 30 gallons

- Minimum recovery tank 32 gallons
- Minimum squeegee 39" & quick release latch
- ~~Minimum disk cleaning width 30" and 34"~~
- Maximum cleaning width between 29" and 34"
- ~~Minimum edge cleaning width 28"~~
- Auto brush pressure setting
- Maximum decibels 62 dB
- ~~Minimum 2 disks 15" diameter~~
- Minimum cylindrical dimensions 2 (6" X 27")
- ~~Minimum edge dimensions 28" X 14"~~
- Five years parts warranty
- Two years labor warranty

Performance Schedules:

- Vendor will deliver floor scrubbers within 8 weeks after receipt of an order.

Location of work and any constraints:

- Floor scrubbers will be manufactured at the manufacturer's location.

Ordering Officers:

Alexandria S & I
3201 Eisenhower Avenue
Alexandria, VA 22314
John Coon
(703) 667-2860

Branch Avenue S & I
5700 Capital Gateway Dr.
Suitland, MD 20747
David Krueger
(301) 955-2225

Brentwood S & I/MRO
601 T St NE
Washington, DC 20018
Justin Nunez
(202) 962-5908