

# WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY



## DESIGN OF NEW STAIR FOR BETHESDA STATION

7450 WISCONSIN AVENUE

BETHESDA, MD 20814

CONTRACT NO. 13-FQ10060-MCAP-19

FINAL SUBMISSION  
NOVEMBER 28, 2012



# GENERAL NOTES

- NOT ALL SYMBOL DEPICTED ON THIS DRAWING ARE USED IN THE ARCHITECTURAL DRAWINGS.
- VERIFY ALL DIMENSIONS IN THE FIELD.
- VERIFY ALL FIELD CONDITIONS.
- ALL DIMENSIONS ARE NOMINAL UNLESS NOTED OTHERWISE.
- ALL WORK WILL BE COMPLETED IN ACCORDANCE WITH THE LATEST VERSIONS OF I.B.C. AND LIFE SAFETY CODES. SEE THIS SHEET FOR LIST OF CODES. ALL WORK IS DESIGNED AND SHALL BE CONSTRUCTED IN ACCORDANCE WITH WMATA DESIGN CRITERIA, VERSION 9.
- DO NOT SCALE DRAWINGS FOR PURPOSES OF CONSTRUCTION.
- ANY DEVIATION FROM, OR IN FIELD ALTERATION TO THESE DRAWINGS, AND SPECIFICATIONS IS STRICTLY PROHIBITED WITHOUT PRIOR APPROVAL OF A.R. ANY SUCH ALTERATIONS SHALL BE CORRECTED AT ONCE, WITH NO EXPENSE TO THE OWNER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE WORK OF ALL TRADES REGARDLESS OF DISCREPANCIES IN THE CONTRACT DOCUMENTS. NO ADDITIONAL COSTS WILL BE PAID BY THE OWNER TO RECTIFY WORK TO BE RELOCATED DUE TO LACK OF JOBSITE COORDINATION.
- DEMOLITION, CUTTING, AND PATCHING OF ANY MATERIALS OR FIXTURES REQUIRED TO CONSTRUCT THE PROJECT IS HEREIN MADE A PART OF THESE DOCUMENTS.
- THE CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS.
- THE IMAGES ON THE CONSTRUCTION DOCUMENT FLOOR PLANS REFLECT THE INFORMATION FROM THE ORIGINAL CONSTRUCTION DOCUMENTS FOR THE PROJECT, IT IS NOT AN INDICATION OF NEW WORK, IT IS SHOWN IN GRAY LINE COLOR. THE NEW WORK AND REQUIRED DEMOLITION OR REMOVALS ARE SHOWN IN BLACK LINE COLOR. IF THE DIFFERENCE IS NOT OBVIOUS, REPORT TO THE A.R. IMMEDIATELY.
- ALL WORK INDICATED OR SHOWN GRAPHICALLY AS "EXISTING TO REMAIN" WILL BE THE CONTRACTOR'S RESPONSIBILITY TO PROTECT AND WORK AROUND WITHOUT DISTURBING. IF DAMAGED, THE CONTRACTOR WILL REPLACE AT NO ADDITIONAL COST TO THE OWNER.
- FIREPROOF ALL NEW STRUCTURAL STEEL, INCLUDING, BUT NOT LIMITED TO COLUMNS, BEAMS, METAL DECK, AND MISCELLANEOUS METALS - SEE SPECIFICATION SECTION 07.81.00.
- CUTTING AND PATCHING OF QUARRY TILE PAVERS WILL BE UNDERTAKEN CAREFULLY, NEW TILE WILL BE "TOOTHED" INTO EXISTING IN AREAS OF STRUCTURAL DEMOLITION.
- THE DOOR AND FRAME BELOW THE STAIR ARE HOLLOW METAL. THE DOOR SIZE IS 9'-0" HIGH BY 4'-4" WIDE. THE ACTIVE LEAF IS 3'-0" WIDE. THE DOORS AND FRAME ARE PAINTED. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.

# INDEX OF DRAWINGS

- G-001 COVER
  - G-002 INDEX OF DRAWINGS, VICINITY MAPS, AND CODE INFORMATION
- ARCHITECTURAL DRAWINGS**
- A-001 ABBREVIATIONS AND LEGENDS
  - A-002 WORK ZONE PLAN
  - A-100 DEMOLITION AND NEW WORK PLAN
  - A-200 STAIR SECTIONS, ELEVATIONS & REFLECTED CEILING PLAN
  - A-300 STAIR SECTIONS AND ENLARGED DETAILS
  - A-301 STAIR SECTIONS AND ENLARGED DETAILS
- STRUCTURAL DRAWINGS**
- S-001 GENERAL NOTES
  - S-100 DEMOLITION - EXISTING MEZZANINE STEEL
  - S-101 DEMOLITION - EXISTING MEZZANINE CONCRETE
  - S-102 DEMOLITION - EXISTING PLATFORM CONCRETE
  - S-200 DEMOLITION - CONCRETE REMOVAL DETAILS
  - S-201 NEW WORK - PLATFORM STAIR ELEVATION AND SECTIONS
  - S-202 NEW WORK - STAIR FRAMING ELEVATION AND SECTIONS
  - S-203 NEW WORK - CONCRETE REPAIR DETAILS
  - S-300 NEW WORK - STEEL DETAILS
  - S-301 NEW WORK - PRECAST STRINGER DETAILS
- ELECTRICAL DRAWINGS**
- E-001 SYMBOLS, ABBREVIATIONS, AND GENERAL NOTES
  - E-100 STAIR LIGHTING-MEZZANINE DEMOLITION PLAN
  - E-101 STAIR LIGHTING - PLATFORM
  - E-102 STAIR LIGHTING - MEZZANINE
  - E-600 PANEL AND LIGHTING FIXTURE SCHEDULE
  - E-601 LIGHTING CALCULATIONS



ADC MAP - 3RD EDITION, 2000 Alexandria Drafting Company

VICINITY MAP  
SCALE: NONE

# CODE INFORMATION:

**APPLICABLE CODES:**

- BUILDING CODE: 2012 INTERNATIONAL BUILDING CODE
  - ELECTRICAL CODE: 2008 NFPA 70 NATIONAL ELECTRICAL CODE
  - LIFE SAFETY CODE: 2009 NFPA 101 LIFE SAFETY CODE
  - ACCESSIBILITY CODES: MARYLAND ACCESSIBILITY CODE GUIDELINES FOR BUILDINGS AND FACILITIES - CONMAR 05.02.02, ADAAG, & FFHAG
- NOTE: ALL APPLICABLE CODES TO INCLUDE MONTGOMERY COUNTY AMENDMENTS

**BUILDING INFORMATION:**


- USE GROUP: A-3 ASSEMBLY
- CONSTRUCTION TYPE: 1B NON-COMBUSTIBLE

**SPRINKLER SYSTEM:**

- EXISTING BUILDING: NONE-NOT REQUIRED
- PROPOSED CONSTRUCTION: NOT REQUIRED



SYSTEM MAP  
SCALE: NONE



KEY PLAN  
SCALE: NONE

CONTRACT NO.  
**13-FQ10060-MCAP-19**

DESIGNED	J. SCHNEIDER	08/12	REFERENCE DRAWINGS		REVISIONS			
			NUMBER	DESCRIPTION	DATE	BY	DESCRIPTION	
DRAWN	C. RICHARDSON	11/12						
CHECKED	J. SCHNEIDER	11/12						
APPROVED	R. ST. JOHN	11/12						

## WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY

DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM



APPROVED \_\_\_\_\_

SUBMITTED \_\_\_\_\_  
PROJECT MANAGER

## DESIGN OF NEW STAIR FOR BETHESDA STATION

GENERAL  
INDEX OF DRAWINGS, VICINITY MAP, & LOCATION MAP

SCALE  
NONE

DRAWING NO.  
G-002

SHEET NO.  
-002

# ARCHITECTURAL ABBREVIATIONS

# LEGEND

ABV	ABOVE	DIM	DIMENSION	HTR	HEATER	PNT	PAINT
AC	AIR CONDITIONER	DIV	DIVISION	HVAC	HEATING, VENTILATING, & AIR CONDITIONING	PORC	PORCELAIN
ACST	ACOUSTIC	DL	DEAD LOAD	ID	INSIDE DIAMETER	PR	PAIR
ADDL	ADDITIONAL	DMPF	DAMPPOOFING	IE	THAT IS	PREFAB	PREFABRICATED
ADJ	ADJACENT	DN	DOWN	IH	INTAKE HOOD	PROJ	PROJECT
AFF	ABOVE FINISH FLOOR	DPN	DEMOUNTABLE PARTITION MANUFACTURER	INSUL	INSULATION	PSF	POUNDS PER SQUARE FOOT
AGGR	AGGREGATE	DR	DOOR	INTR	INTERIOR	PSI	POUNDS PER SQUARE INCH
AL	ALUMINUM	DS	DOWNSPOUT	JST	JOIST	PT	POINT
ALT	ALTERNATE	DW	DISHWASHER	JT	JOINT	PTD	PAINTED
A.R.	AUTHORITY REPRESENTATIVE	DWG	DRAWING	LAB	LABORATORY	PTN	PARTITION
ARCH	ARCHITECTURAL	E	EAST	LAM	LAMINATE	PVC	POLYVINYL CHLORIDE
ASB	ASBESTOS	EA	EACH	LAV	LAVATORY	QTF	QUARRY-TILE FLOOR
ASPHRS	ASPHALT ROOF SHINGLES	EGEN	EMERGENCY GENERATOR	LG	LENGTH	R	RADIUS
ASSN	ASSOCIATION	EF	EXHAUST FAN	LH	LEFT HAND	R	RISER
ASST	ASSISTANT	EIFS	EXTERIOR INSULATION & FINISH SYSTEM	LIB	LIBRARY	RD	ROOF DRAIN
ASSY	ASSEMBLY	EL	ELEVATION	LIN	LINEAR	REF	REFRIGERANT/REFRIGERATION
AVE	AVENUE	ELEC	ELECTRICAL	LL	LIVE LOAD	REFR	REFRIGERATOR
AVG	AVERAGE	ELEV	ELEVATOR	LLH	LONG LEG HORIZONTAL	REINF	REINFORCE
BALC	BALCONY	ENTR	ENTRANCE	LLV	LONG LEG VERTICAL	REQD	REQUIRED
BD	BOARD	EQ	EQUAL	LPT	LOW POINT	RET	RETURN
BETW	BETWEEN	EQUIP	EQUIPMENT	LT	LIGHT	REV	REVISION
BLDG	BUILDING	ETR	EXISTING TO REMAIN	LWC	LIGHTWEIGHT CONCRETE	REG	REGISTER
BLKG	BLOCKING	EWC	ELECTRIC WATER COOLER	MAINT	MAINTENANCE	RFG	ROOFING
BLR	BOILER	EXH	EXHAUST	MAS	MASONRY	RH	RIGHT HAND
BM	BEAM	EX	EXISTING	MATL	MATERIAL	RM	ROOM
BM	BENCHMARK	EXP	EXPANSION	MAX	MAXIMUM	RWC	RAIN WATER CONDUCTOR
BOT	BOTTOM	EXP JT	EXPANSION JOINT	MECH	MECHANICAL	S	SOUTH
BP	BASE PLATE	EXT	EXTERIOR	MEMB	MEMBRANE	SAPC	SUSPENDED ACOUSTICAL PANEL CEILING
BRDG	BRIDGING	FAB	FABRICATE	MEZZ	MEZZANINE	SCHED	SCHEDULE
BRG	BEARING	FBD	FIBERBOARD	MFR	MANUFACTURER	SDG	SIDING
BS	BOTH SIDES	FD	FLOOR DRAIN	MGR	MANAGER	SEC	SECTION
BSMT	BASEMENT	FDN	FOUNDATION	MH	MANHOLE	SF	SQUARE FOOT
CAB	CABINET	FDR	FIRE DOOR	MIL	MILITARY	SGFT	STRUCTURAL GLAZED FACING TILE
CAP	CAPACITY	FE	FIRE EXTINGUISHER	MIN	MINIMUM	SH	SHOWER
CARP	CARPET	FEC	FIRE EXTINGUISHER & CABINET	MISC	MISCELLANEOUS	SHM	SECURITY HOLLOW METAL SHEET
CDR	COILING DOOR	FHY	FIRE HYDRANT	MET	METAL	SHT	SHEET
CER	CERAMIC	FIN	FINISH	ML	METAL LATH	SI	INTERNATIONAL SYSTEM OF UNITS
CER TILE	CERAMIC TILE	FIX	FIXTURE	MLDG	MOLDING	SIM	SIMILAR
CI	CAST IRON	FL	FLASHING	MO	MASONRY OPENING	SKY	SKYLIGHT
CIP	CAST-IRON PIPE	FLEX	FLEXIBLE	MOD	MOTOR OPERATED DAMPER	SLDR	SLIDING DOOR
CJ	CONTROL JOINT	FLG	FLANGE	MTG	MOUNTING	SMLS	SEAMLESS SPECIFICATION
CL	CENTERLINE	FLR	FLOOR	MTL	METAL	SPKLR	SPRINKLER
CLG	CEILING	FLRG	FLOORING	NA	NOT APPLICABLE	SPKR	SPEAKER
CLO	CLOSET	FP	FIREPROOF	NIC	NOT IN CONTRACT	SQ	SQUARE
CLR	CLEAR	FRP	FIBERGLASS-REINFORCED PLASTICS	NO	NUMBER	SS	STAINLESS STEEL
CMIU	CONCRETE MASONRY INSULATED UNIT	FT	FOOT	NRC	NOISE-REDUCTION COEFFICIENT	ST	STAINED
CMU	CONCRETE MASONRY UNIT	FTG	FOOTING	NTS	NOT TO SCALE	STD	STANDARD
CNCL	CONCEALED	FURN	FURNITURE	OA	OVERALL	STL	STEEL
CO	CLEANOUT	GALV	GALVANIZED	OC	ON CENTER	STOR	STORAGE
CO	COMPANY	GAR	GARAGE	OD	OUTSIDE DIAMETER	STRUCT	STRUCTURE/STRUCTURAL
COL	COLUMN	GEN	GENERATOR	OFF	OFFICE	STWY	STAIRWAY
COMP	COMPOSITION	GL	GLASS	OH	OPPOSITE HAND	SUPT	SUPERINTENDENT
CONC	CONCRETE	GLU-LAM	GLUE-LAMINATED	OHDR	OVERHEAD DOOR	SUPVR	SUPERVISOR
CONSTR	CONSTRUCTION	GOVT	GOVERNMENT	OPNG	OPENING	SURF	SURFACE
CONT	CONTINUOUS	GR	GRADE	OPP	OPPOSITE	SUSP	SUSPENDED/SUSPENSION
CONTR	CONTRACTOR	GRD	GROUND	OSB	ORIENTED STRAND BOARD	SYS	SYSTEM
CRV	CURVED	GVL	GRAVEL	P/L	PROPERTY LINE	TB	TACK BOARD
CSK	COUNTERSINK	GWB	GYPSTUM WALLBOARD	PASS	PASSENGER	T/	TOP OF
CTD	COATED	GYP	GYPSTUM	PEB	PRE-ENGINEERED BUILDING	T&B	TOP AND BOTTOM
CTR	CENTER	H	HIGH	PERF	PERFORATED	T&G	TONGUE AND GROOVE
CUH	CABINET UNIT HEATER	HDWE	HARDWARE	PL	PLATE	TAN	TANGENT
D	DEPTH	HM	HOLLOW METAL	PLAS	PLASTER	TDD	TELECOMMUNICATION DISPLAY DEVICE
DBL	DOUBLE	HMD	HOLLOW METAL DOOR	PLBG	PLUMBING		
DEG	DEGREE	HORIZ	HORIZONTAL	PLYWD	PLYWOOD		
DEPT	DEPARTMENT	HPT	HIGH POINT	PNL	PANEL		
DET	DETAIL	HT	HEIGHT				
DGL	DIAGONAL						
DIA	DIAMETER						

TEL	TELEPHONE	TEMP	TEMPERED
TER	TERRAZZO	TRTD	TREATED
THRU	THROUGH	TYP	TYPICAL
TLT	TOILET	UNO	UNLESS NOTED OTHERWISE
VAT	VINYL ASBESTOS TILE	VCT	VINYL COMPOSITION TILE
VERT	VERTICAL	VIF	VERIFY IN FIELD
VTR	VENT THRU ROOF	W	WEST
W	WIDE	W	WITH
W/O	WITHOUT	WBD	WALLBOARD
WDB	WATER CLOSET	WDR	WOOD DOOR
WD	WOOD	WH	WATER HEATER
WDR	WOOD DOOR	WTRPRF	WATERPROOFING
WH	WATER HEATER	WWF	WELDED WIRE FABRIC
WTRPRF	WATERPROOFING	XFMR	TRANSFORMER
WWF	WELDED WIRE FABRIC	WB	WHITE BOARD
XFMR	TRANSFORMER		
WB	WHITE BOARD		

## BUILDING MATERIALS

	BRICK
	CMU
	ACOUSTICAL CMU
	CMU
	SGFT / GLAZED CMU
	CONCRETE
	GYP BD / GROUT
	BATT INSULATION
	RIGID INSULATION
	COARSE AGGREGATE /BALLAST
	STEEL
	ALUMINUM
	FINISH LUMBER
	DIMENSIONAL LUMBER
	SHIM
	PLYWOOD
	ACOUSTICAL PANEL
	TILE
	EARTH

### SYMBOLS

100A			DOOR NUMBER REFERENCE
100			ROOM NUMBER REFERENCE
			WINDOW TYPE REFERENCE
L-2			LINTEL TYPE REFERENCE
			LOUVER TYPE REFERENCE
			TOILET ACCESSORY REFERENCE
			COLUMN REFERENCE
			MULTIPLE INTERIOR ELEVATION REFERENCE DRAWING ON WHICH ELEVATION APPEARS
			SINGLE INTERIOR ELEVATION REFERENCE DRAWING ON WHICH ELEVATION APPEARS
			PARTITION TYPE REFERENCE
			LARGE SCALE PLAN REFERENCE

\*Professional Certification. I hereby certify that these documents were prepared or approved by me, and that I am a duly licensed professional architect under the laws of the State of Maryland, License No. 5231--A, Expiration Date: 05-18-2013.\*

CONTRACT NO.  
**13-FQ10060-MCAP-19**

DESIGNED	J. SCHNEIDER	08/12	DATE
DRAWN	C. RICHARDSON	11/12	DATE
CHECKED	J. SCHNEIDER	11/12	DATE
APPROVED	R. ST. JOHN	11/12	DATE

REFERENCE DRAWINGS	
NUMBER	DESCRIPTION

REVISIONS		
DATE	BY	DESCRIPTION

## WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY

DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM


APPROVED \_\_\_\_\_ SUBMITTED \_\_\_\_\_ PROJECT MANAGER

A Gannett Fleming/Parsons  
JOINT VENTURE


## DESIGN OF NEW STAIR FOR BETHESDA STATION

ARCHITECTURAL ABBREVIATIONS AND LEGENDS

SCALE NONE	DRAWING NO. A-001	SHEET NO. -003
---------------	----------------------	-------------------




1 PLATFORM LEVEL-WORK ZONE  
SCALE: 1/8"=1'-0"



2 MEZZANINE LEVEL-WORK ZONE  
SCALE: 1/8"=1'-0"

**WORK ZONE NOTES:**

1. CONSTRUCT TEMPORARY PARTITIONS OF 2x4s @ 24" O.C. AND 5/8" PLYWOOD. ALL LUMBER IS TO BE FIRE-RATED.
2. EXTEND TO UNDERSIDE OF CEILING ON PLATFORM LEVEL. BRACE PARTITIONS TO FLOORS WITH ANGLED 2x4s-ANCHOR TO FLOOR SECURELY. REPLACE QUARRY TILES DAMAGED BY ATTACHMENT AFTER CONSTRUCTION IS COMPLETE.
3. CONSTRUCT PARTITIONS 8'-0" HIGH ON MEZZANINE LEVEL. ANCHOR TO FLOOR AS INDICATED IN NOTE 2.
4. LOCATE ACCESS DOORS WHERE NEEDED FOR CONSTRUCTION ACTIVITIES. CONTRACTOR TO DETERMINE LOCATIONS. A.R. TO APPROVE.
5. THE CONTRACTOR MAY EXTEND THE LENGTH OF THE WORK ZONE WITH WMATA'S APPROVAL, BUT MUST MAINTAIN MIN. 6'-0" FROM EDGE OF PLATFORM AND CONCRETE PARAPET.
6. PROVIDE TEMPORARY WARNING SIGNAGE IN ACCORDANCE WITH WMATA REQUIREMENTS.
7. PROVIDE TEMPORARY LIGHTING IN WORK ZONES INCLUDING STORAGE AREAS IN ACCORDANCE WITH WMATA DESIGN CRITERIA, VERSION 9.
8. CONSTRUCTION WORK AND STORAGE AREAS MUST BE APPROVED BY WMATA.



DESIGNED	J. SCHNEIDER	08/12	REFERENCE DRAWINGS		REVISIONS	
			NUMBER	DESCRIPTION	DATE	BY
DRAWN	C. RICHARDSON	11/12				
CHECKED	J. SCHNEIDER	11/12				
APPROVED	R. ST. JOHN	11/12				

WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY

DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM



APPROVED \_\_\_\_\_

SUBMITTED \_\_\_\_\_  
PROJECT MANAGER

DESIGN OF NEW STAIR FOR BETHESDA STATION  
ARCHITECTURAL WORK ZONE PLAN


SCALE AS SHOWN

DRAWING NO. A-002


SHEET NO. -004

**GENERAL DEMOLITION NOTES**


1. VERIFY EXISTING FIELD CONDITIONS.
2. PRIOR TO DEMOLITION, VERIFY MATERIALS AND EQUIPMENT TO BE SALVAGED. STORE WHERE DIRECTED BY WMATA (OWNER).
3. VERIFY AND MARK ALL UNDER SLAB UTILITIES PRIOR TO THE START OF WORK.
4. REMOVE ALL RUBBISH AND DEMOLITION DEBRIS FROM THE SITE AND DISPOSE OF IN A LAWFUL MANNER.
5. COORDINATE GENERAL CONSTRUCTION DEMOLITION WITH THE STRUCTURAL AND ELECTRICAL DEMOLITION WORK.
6. REPAIR ALL EXISTING STRUCTURES, UTILITIES, AND EQUIPMENT, SCHEDULED TO REMAIN, WHICH ARE DAMAGED DURING DEMOLITION OPERATIONS. ALL WORK SCHEDULED TO BE DEMOLISHED, WILL BE REMOVED COMPLETELY INCLUDING ALL FASTENERS, ATTACHMENTS, ACCESSORIES, OR ANY RELATED WORK.
7. DEMOLITION OF CONCRETE SLABS IS NOT SHOWN ON THE DEMOLITION PLAN AS IT RELATES TO DEMOLITION FOR OTHER TRADES SUCH AS STRUCTURAL FOUNDATIONS. SEE ELECTRICAL AND STRUCTURAL DRAWINGS FOR RELATED DEMOLITION WORK.
8. DEMOLITION INCLUDES ALL ITEMS WHETHER OR NOT SHOWN ON THE DRAWINGS, THAT ARE REQUIRED TO BE REMOVED IN ORDER TO INSTALL THE NEW WORK SHOWN ON DRAWING A-100 AND OTHER PORTIONS OF THE CONTRACT DOCUMENTS.
9. ALL SURFACES TO REMAIN SHALL BE REFINISHED TO REPAIR ALL HOLES, SCRATCHES, DENTS, MARS, PITTING, ADHESIVE, BAD JOINTS, DEFECTIVE CMU, ETC. TO BE ACCEPTABLE IN EVERY WAY TO RECEIVE NEW FINISHES.
10. GC WILL COORDINATE LOCATIONS OF ALL UTILITIES IN PLENUM AREA BELOW PLATFORM AND VERIFY THAT ALL WORK IS COORDINATED.
11. PAINT DOORS AND FRAME WMATA "METRO BROWN", FEDERAL STANDARD, 595C PAINT COLOR.
12. FINISH FOR PRECAST WALL PANELS IS WMATA STANDARD BOARD FORM PATTERN.




**1 PLATFORM LEVEL-DEMOLITION PLAN**  
SCALE: 1/8"=1'-0"




**2 MEZZANINE LEVEL-DEMOLITION PLAN**  
SCALE: 1/8"=1'-0"



**3 PLATFORM LEVEL-NEW WORK**  
SCALE: 1/4"=1'-0"



**4 MEZZANINE LEVEL-NEW WORK**  
SCALE: 1/4"=1'-0"



DESIGNED	J. SCHNEIDER	08/12
		DATE
DRAWN	C. RICHARDSON	11/12
		DATE
CHECKED	J. SCHNEIDER	11/12
		DATE
APPROVED	R. ST. JOHN	11/12
		DATE

REFERENCE DRAWINGS		REVISIONS	
NUMBER	DESCRIPTION	DATE	BY

**WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY**

DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM

APPROVED \_\_\_\_\_

**GFP** A Gannett Fleming/Parsons JOINT VENTURE


SUBMITTED \_\_\_\_\_  
PROJECT MANAGER

**DESIGN OF NEW STAIR FOR BETHESDA STATION**


ARCHITECTURAL DEMOLITION & NEW WORK PLAN

SCALE: AS SHOWN      DRAWING NO. A-100      SHEET NO. -005


CONTRACT NO. 13-FQ10060-MCAP-19




**1 WEST ELEVATION/SECTION**  
SCALE: 1/4"=1'-0"




**4 PARTIAL REFLECTED CEILING PLAN**  
SCALE: 1/4"=1'-0"




**2 NORTH ELEVATION/SECTION**  
SCALE: 1/4"=1'-0"




**3 SOUTH ELEVATION/SECTION**  
SCALE: 1/4"=1'-0"




**7 CONCRETE PANEL DETAIL**  
SCALE: 1/2"=1'-0"




**5 SECTION-TOP OF STAIR**  
SCALE: 1/2"=1'-0"



**8 DETAIL**  
SCALE: 3"=1'-0"



**9 DETAIL**  
SCALE: 3"=1'-0"



**6 SECTION-BOTTOM OF STAIR**  
SCALE: 1/2"=1'-0"



**KEY PLAN**  
SCALE: NONE


CONTRACT NO.  
**13-FQ10060-MCAP-19**

DESIGNED	DATE	REFERENCE DRAWINGS		REVISIONS	
		NUMBER	DESCRIPTION	DATE	DESCRIPTION
J. SCHNEIDER	08/12				
C. RICHARDSON	11/12				
J. SCHNEIDER	11/12				
R. ST. JOHN	11/12				

**WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY**  
DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM  
APPROVED \_\_\_\_\_

**GFP** A Gannett Fleming/Parsons JOINT VENTURE  
SUBMITTED \_\_\_\_\_ PROJECT MANAGER

**DESIGN OF NEW STAIR FOR BETHESDA STATION**  
ARCHITECTURAL  
STAIR SECTIONS, ELEVATIONS & REFLECTED CEILING PLAN  
SCALE AS SHOWN  
DRAWING NO. A-200  
SHEET NO. -006



NOTE: CEILING AND TRIM WORK WILL BE A PART OF A FUTURE CONTRACT.

NOTE: FIREPROOF NEW STRUCTURAL STEEL TO MATCH EXISTING. SEE SPECIFICATION SECTION 07 81 00.

DESIGNED J. SCHNEIDER 08/12  
 DRAWN C. RICHARDSON 11/12  
 CHECKED J. SCHNEIDER 11/12  
 APPROVED R. ST. JOHN 11/12


REFERENCE DRAWINGS		REVISIONS	
NUMBER	DESCRIPTION	DATE	DESCRIPTION

WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY  
 DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
 OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM  
 APPROVED \_\_\_\_\_


GFP A Gannett Fleming/Parsons JOINT VENTURE  
 SUBMITTED \_\_\_\_\_ PROJECT MANAGER

DESIGN OF NEW STAIR FOR BETHESDA STATION  
 ARCHITECTURAL STAIR SECTIONS AND ENLARGED DETAILS

CONTRACT NO. 13-FQ10060-MCAP-19  
 SCALE AS SHOWN DRAWING NO. A-300 SHEET NO. -007



1 TYPICAL SECTION @ HANDRAIL  
 A-301 SCALE: 1-1/2"=1'-0"



1 PLAN DETAIL @ GLASS SUPPORT FITTING  
 A-301 SCALE: 3"=1'-0"

CONTRACT NO.  
 13-FQ10060-MCAP-19

DESIGNED	J. SCHNEIDER	08/12	REFERENCE DRAWINGS		REVISIONS	
			NUMBER	DESCRIPTION	DATE	BY
DRAWN	C. RICHARDSON	11/12				
CHECKED	J. SCHNEIDER	11/12				
APPROVED	R. ST. JOHN	11/12				

WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY  
 DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES  
 OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM  
 APPROVED \_\_\_\_\_

**GFP** A Gannett Fleming/Parsons JOINT VENTURE  
 SUBMITTED \_\_\_\_\_  
 PROJECT MANAGER

DESIGN OF NEW STAIR FOR BETHESDA STATION  
 ARCHITECTURAL  
 STAIR SECTIONS AND ENLARGED DETAILS

SCALE AS SHOWN  
 DRAWING NO. A-301  
 SHEET NO. -008



I. GENERAL:

1. WORK SHALL BE COORDINATED WITH ALL TRADES TO AVOID CONFLICT OR INTERFERENCE WITH PLACEMENT OF STRUCTURAL MEMBERS. IF THERE IS A DISCREPANCY BETWEEN DRAWINGS, IT IS THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE ENGINEER PRIOR TO PERFORMING THE WORK.
2. PIPES, CONDUITS, AND DUCT WORK PRESENT IN PLENUM (UNDER PLATFORM) ARE NOT SHOWN IN THE STRUCTURAL DRAWINGS. IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY WHAT UTILITIES ARE PRESENT AND RELOCATE AS REQUIRED FOR STRUCTURAL MEMBER PLACEMENT, AS PART OF THE WORK. RELOCATIONS SHALL BE PERFORMED PRIOR TO CONSTRUCTION SHOWN ON THESE DOCUMENTS.
3. DO NOT CUT OR ALTER ANY EXISTING STRUCTURAL MEMBERS, BEYOND THOSE SHOWN FOR REMOVAL IN PLANS.
4. CONTRACTOR SHALL VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO STARTING WORK, AND NOTIFY THE ENGINEER OF ANY DISCREPANCIES.
5. PRIOR TO PREPARATION OF SHOP DRAWINGS THE CONTRACTOR SHALL VERIFY AND/OR DETERMINE THE SIZE, LOCATION, CONFIGURATION, ETC. OF EXISTING STRUCTURE AT EVERY LOCATION WHERE NEW WORK IS TO ABUT, ATTACH, OR CLEAR. THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF ANY AND ALL CONDITIONS WHICH DIFFER FROM THOSE SHOWN ON PLANS.

II. DESIGN:

1. DESIGN IN ACCORDANCE WITH THE FOLLOWING CODES:

- A. INTERNATIONAL BUILDING CODE (IBC) 2012
- B. ACI 318 & ACI 301, CURRENT VERSIONS
- C. WMATA MANUAL OF DESIGN CRITERIA, RELEASE 9

2. DESIGN LOADS:

- A. STAIRS: 150 PSF & 300 LB CONCENTRATED LOAD (OUTSIDE D.C. ONLY)
- B. MEZZANINE: 150 PSF
- C. PLATFORM: 150 PSF
- D. PRECAST WALL UNITS: 40 PSF WIND LOAD

III. MATERIALS:

1. STRUCTURAL STEEL:

ALL ROLLED SHAPES: ASTM A992, GRADE 50  
 ALL PLATES AND CONNECTION MATERIAL: ASTM A36  
 ANCHOR RODS: ASTM F1554, GRADE 55, GALV. AS PER ASTM A123  
 BOLTING MATERIALS: ASTM A325, U.N.O

2. SHEAR CONNECTORS:

1/2" DIAMETER HEADED STUDS, U.N.O.  
 (LENGTHS SHOWN ON PLANS)

3. CAST-IN-PLACE CONCRETE:

FLOOR SLABS 4,000 PSI, NORMAL WEIGHT

4. PRECAST CONCRETE:

ARCHITECTURAL PANELS: 5,000 PSI, NORMAL WEIGHT  
 CONCRETE STAIR STRINGERS: 5,000 PSI, NORMAL WEIGHT

5. REINFORCEMENT:

DEFORMED BARS: ASTM A615, GRADE 60, BLACK

IV. STRUCTURAL STEEL:

1. ALL WELDING SHALL COMPLY WITH A.W.S., D1.1, LATEST VERSION.
2. USE NON-SHRINK, NON-METALLIC GROUT UNDER BASE PLATES WITH A MINIMUM STRENGTH OF 7,000 PSI AT 28 DAYS.
3. ADEQUATE TEMPORARY BRACING SHALL BE PROVIDED DURING CONSTRUCTION, AS REQUIRED. THE CONTRACTOR SHALL PROVIDE ALL ADDITIONAL STEEL, TEMPORARY CONNECTIONS, EQUIPMENT, GUYING, ETC., REQUIRED FOR STEEL ERECTION.
4. MINIMUM THICKNESS OF STRUCTURAL STEEL PLATES AND MISCELLANEOUS MATERIAL SHALL BE 1/4".
5. ALL COLUMN BASE PLATES SHALL BE AS PER SECTION III, MATERIALS. MILL ENDS OF COLUMNS AT BASE PLATES.
6. ALL PROPOSED STEEL, AND EXISTING STEEL WHICH HAD FIREPROOFING REMOVED FOR PROPOSED STEEL INSTALLATION, SHALL BE PROTECTED WITH SPRAYED FIREPROOFING. FIREPROOFING SHALL HAVE A MINIMUM TWO HOUR FIRE RESISTANCE RATING.
7. ALL STEEL SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM A123.

V. PRECAST CONCRETE:

1. PRECAST CONCRETE UNITS SHALL BE DESIGNED, PRODUCED, AND ERECTED IN ACCORDANCE WITH METHODS AND SPECIFICATIONS CONTAINED IN THE LATEST VERSIONS OF THE PCI DESIGN HANDBOOK AND ACI 318.
2. CONTRACTOR/PRECAST MANUFACTURER SHALL VERIFY ALL DIMENSIONS FOR STAIR STRINGERS AND WALL PANELS, PRIOR TO SHOP DRAWINGS AND FABRICATION.
3. PRECAST MANUFACTURER SHALL SUBMIT SHOP DRAWINGS, SIGNED AND SEALED DESIGN BY A REGISTERED PROFESSIONAL ENGINEER IN THE STATE OF MARYLAND FOR APPROVAL. SHOP DRAWINGS MUST INCLUDE ALL REINFORCEMENT DETAILS, EMBEDMENTS AND ANCHORAGES.
4. ALL CONCRETE EMBEDMENTS SHALL BE HOT DIPPED GALVANIZED.

VI. MASONRY:

1. INTERIOR CMU WALL SHALL BE 4", AND REINFORCED VERTICALLY WITH #5 BARS @ 24". DOWEL BARS SHALL BE DRILLED INTO STRUCTURAL FLOOR SLAB AND GROUTED WITH EPOXY GROUT TO AN EMBEDMENT DEPTH NOT LESS THAN 4"
2. CMU WALL SHALL HAVE HORIZONTAL TRUSS REINFORCING EVERY 16".

VII. METAL DECK

1. COMPOSITE METAL DECK SHALL BE USED TO REPAIR THE KNOCKOUT SLAB AT THE PLATFORM LEVEL OF BETHESDA STATION. THE DECK SHALL BE FABRICATED FROM ASTM A611 OR ASTM A653 STEEL WITH ASTM A653 GALVANIZING. PROPOSED DECK SHALL BE 2 INCH, 18 GA. WITH 2 1/2" CONCRETE TOPPING.
2. ALL METAL DECKING HAS BEEN DESIGNED FOR UNSHORED CONSTRUCTION.
3. DECK SUPPLIER SHALL FURNISH ANY AND ALL SCREEDS, CLOSURES, POUR STOPS, COLUMN CLOSURES AND CANTILEVER STRIPS AS REQUIRED FOR COMPLETE INSTALLATION OF DECK.
4. THE CONTRACTOR SHALL FASTEN STEEL DECK TO STEEL FRAMING WITH THE FOLLOWING:
  - A. AT ENDS AND SUPPORT: 3/8" DIAMETER PUDDLE WELDS WITH A 36/4 PATTERN.
  - B. SIDE LAPS: #10 TEK SCREWS AT 12" SPACING, OR EQUIVALENT.
  - C. DECK EDGES: 3/8" DIAMETER PUDDLE WELDS AT 18" SPACING

VIII. DEMOLITION:

1. CONTRACTOR IS RESPONSIBLE FOR ALL TEMPORARY SHORING, SHIELDING, TEMPORARY WALLS, ETC., AS REQUIRED TO PREVENT THE PROPAGATION OF CONSTRUCTION DEBRIS BEYOND THE WORK AREA.
2. CONTRACTOR IS RESPONSIBLE FOR THE SAFETY OF ALL WORKMEN, AUTHORITY EMPLOYEES AND THE PUBLIC EXPECTED TO BE IN THE PROXIMITY DURING THIS WORK.
3. NOTIFY OWNER AND ENGINEER IMMEDIATELY IF ANY PORTION OF THE EXISTING STRUCTURE WHICH IS NOT TO BE DEMOLISHED, IS DAMAGED. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL REPAIR COSTS, INCLUDING DESIGN AND INSPECTION EXPENSES.
4. CONTRACTOR SHALL SAW CUT IN LOCATIONS SPECIFIED AS PER PLANS. CUTTING SHALL BE PERFORMED IN A NEAT AND WORKMANLIKE MANNER. CONTRACTOR TO DRILL CORNERS AND SAW CUT STRAIGHT LINES. CUT AND/OR DAMAGED PAVER TILES SHALL BE REMOVED IN THE PROXIMITY OF THE SAW CUTS TO THE NEXT UNDAMAGED TILE AND REPLACED.
5. CONTRACTOR'S WORK ZONE IS SHOWN ON DRAWING NO. A-004. ALL CLEARANCES SHOWN MUST BE MAINTAINED AT ALL TIMES.
6. THE CONTRACTOR WILL BE REQUIRED INSTALL BRACING OR SHORING TO MINIMIZE CORNER CRACKS AND TRANSFERRING LOAD TO ADJACENT SLAB FOR THE DEMOLITION OPENINGS IN THE PLATFORM SLAB (1'-10" X 1'-1"). TEMPORARY STEEL ANGLES BOLTED THROUGH THE SLAB ALIGNED DIAGONALLY WITH EACH OF THE PROPOSED SLAB CUT CORNERS IS RECOMMENDED. THE CONTRACTOR MAY ALSO SHORE THE SLAB FROM THE UNDERSIDE AS AN OPTION. THE BRACING/SHORING METHOD SHALL BE SUBMITTED FOR APPROVAL TO THE ENGINEER AND THE AUTHORITY BEFORE PLATFORM SLAB DEMOLITION BEGINS.

IX. CONSTRUCTION/ERECTION:

1. THE CONTRACTOR SHALL BE AWARE THAT THE PLATFORM OF THE BETHESDA METRO RAIL STATION IS NOT ON GRADE, AND THAT VOIDS EXIST UNDER THE 8" THICK CONCRETE PLATFORM SLAB. THE CONTRACTOR IS PROHIBITED FROM USING ANY CONSTRUCTION EQUIPMENT, SUCH AS A FORK LIFT OR OTHER MECHANIZED RUBBER Tired VEHICLE, TO RAISE AND POSITION THE PRECAST CONCRETE STRINGERS, OR FOR ANY OTHER CONSTRUCTION RELATED ACTIVITIES. SUCH EQUIPMENT WILL ONLY BE PERMITTED IF THE CONTRACTOR CAN PROVIDE CALCULATIONS TO THE AUTHORITY THAT THE EXISTING FLOOR SLAB IS CAPABLE OF SUPPORTING SUCH LOADS SAFELY, WITH OR WITHOUT TEMPORARY UNDER-PLATFORM SHORING. REQUIRED CALCULATIONS MUST BE SIGNED AND SEALED BY A REGISTERED PROFESSIONAL ENGINEER IN THE STATE OF MARYLAND AND SUBMITTED TO THE AUTHORITY FOR REVIEW AND APPROVAL.


2. SUGGESTED SEQUENCE OF CONSTRUCTION FOR STRUCTURAL ELEMENTS: (CONTRACTOR SHALL SUBMIT SEQUENCE OF CONSTRUCTION FOR APPROVAL):


- A. REMOVE MEZZANINE AND PLATFORM CONCRETE, AND PRECAST PARAPET AS SHOWN.
- B. INSTALL ANCHOR RODS FOR EACH STEEL FRAME. INSTALL STEEL FRAMES FOR CENTER AND BOTTOM LANDINGS. BOTH FRAMES SHALL BE TEMPORARILY BRACED IN TRANSVERSE AND LONGITUDINAL DIRECTIONS.
- C. INSTALL PROPOSED MEZZANINE FRAMING, WITH THE EXCEPTION OF THE W6X12 BEAM BETWEEN STRINGERS.
- D. INSTALL BOTTOM PRECAST STRINGERS TO BOTTOM LANDING FRAME AND CENTER LANDING FRAME. SHIM AS REQUIRED. TEMPORARY WELDS MAY BE USED. DO NOT INSTALL ANY GRANITE RISERS.
- E. WELD THE W6X12 BEAM BETWEEN THE TWO TOP STRINGERS TO TOP EMBEDDED PLATES. RAISE AND SET THE TWO PRECAST STRINGERS AND STEEL BEAM INTO POSITION ON THE CENTER LANDING FRAME.
- F. WELD THE W6X12 BEAM BETWEEN THE TWO TOP STRINGERS TO TOP EMBEDDED PLATES. RAISE AND SET THE TWO PRECAST STRINGERS AND STEEL BEAM INTO POSITION ON THE CENTER LANDING FRAME. SHORE THE W6X12 BEAM SUCH THAT IT LINES UP WITH PROPOSED MEZZANINE FRAMING. ADJUST POSITION OF THE C7X9.8 ON THE W6X12 CONNECTION PLATES UNTIL STRINGERS ARE EVEN WITH ONE ANOTHER AND AT THE CORRECT ELEVATION. INSTALL FINAL WELDS BETWEEN THE ENDS OF THE C7X9.8 AND THE W6X12.
- G. INSTALL PERMANENT WELDS AT ALL STRINGER BASE PLATES.
- H. REPAIR PLATFORM CONCRETE AROUND CENTER LANDING SLAB COLUMNS.
- I. REPLACE THE KNOCKOUT SLAB WITH A NEW CONCRETE SLAB AND METAL DECKING.
- J. INSTALL GRANITE RISERS, BEGINNING AT THE BASE OF THE STAIRS AND ENDING AT THE TOP GRANITE LANDING.
- K. ADJUST POSITION OF BOLTS IN SLOTTED HOLES AS REQUIRED BETWEEN C7X9.8 AND THE CONNECTION PLATES OF THE W24X68 TO ACCOUNT FOR DL DEFLECTION OF THE NEW STEEL SUPPORTS. INSTALL FINAL FIELD WELD BETWEEN C7X9.8 AND THE W6X12 CONNECTION PLATES, AFTER STAIRS FULLY LOADED.
- L. INSTALL NEW PAVER TILES AT PLATFORM AND GRANITE BOTTOM LANDING SLAB.
- M. INSTALL 4" CMU WALL, ARCHITECTURAL PRECAST PANELS, AND DOOR UNDER STAIRS.

ABBREVIATIONS

ADD'L.	ADDITIONAL	JT.	JOINT
ARCH.	ARCHITECTURAL	MEZZ.	MEZZANINE
BM.	BEAM	MIN.	MINIMUM
B.O.G.S.	BOTTOM OF CONCRETE STRINGER	MTL.	METAL
BOTT.	BOTTOM	OPP.	OPPOSITE
BRG.	BEARING	OPNG.	OPENING
⊕	CENTERLINE	PL	PLATE
CMU	CONCRETE MASONRY UNIT	PROP.	PROPOSED
COL.	COLUMN	RECONSTR.	RECONSTRUCTION
CONC.	CONCRETE	REINF.	REINFORCEMENT
CONN.	CONNECTION	REQ'D	REQUIRED
DEMO.	DEMOLISH/DEMOLITION	SHT.	SHEET
DIA.	DIAMETER	SIM.	SIMILAR
DWG.	DRAWING	SS.	STAINLESS STEEL
EA.	EACH	STIFF.	STIFFENER
EMBED.	EMBEDMENT	STL.	STEEL
EXIST.	EXISTING	THK.	THICK
FIN.	FINISHED	T.O.C.	TOP OF CONCRETE
FLR.	FLOOR	T.O.F.F.	TOP OF FINISHED FLOOR
GA.	GAUGE	T.O.S.	TOP OF SLAB
GALV.	GALVANIZED	TYP.	TYPICAL
GR.	GRADE	TYP.	VERTICAL
HORIZ.	HORIZONTAL	W/	WITH

CONTRACT NO.  
 13-FQ10060-MCAP-19

DESIGNED <u>W. ROBIN</u> 08/12 DATE DRAWN <u>C. RICHARDSON</u> 08/12 DATE CHECKED <u>D. MOSTOLLER</u> 11/12 DATE APPROVED <u>M. AKLAN</u> 11/12 DATE	REFERENCE DRAWINGS		REVISIONS			WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM APPROVED _____	 A Gannett Fleming/Parsons JOINT VENTURE SUBMITTED _____ PROJECT MANAGER	DESIGN OF NEW STAIR FOR BETHESDA STATION STRUCTURAL GENERAL NOTES		
	NUMBER	DESCRIPTION	DATE	BY	DESCRIPTION			SCALE AS SHOWN	DRAWING NO. S-001	SHEET NO. -009



**DEMOLITION PLAN – EXISTING MEZZANINE FRAMING**


SCALE: 3/16"=1'-0"

**NOTES:**

1. PRIMARY EXISTING FRAMING MEMBERS SHOWN. FOR FRAMING NOT LABELED, OR FOR DETAILS RELATED TO MEZZANINE GIRDERS #1 THRU #3, REFER TO ORIGINAL CONSTRUCTION DOCUMENTS BY DE LEUW, CATHER & COMPANY, DATED MAY, 12, 1977, CONTRACT NO. 1A0112.
2. THE CONTRACTOR SHALL LIMIT THE LIVE LOAD IN THE IMMEDIATE AREA OF THE DEMOLITION (AS DEFINED AS SOUTH OF GRID LINE B, AND BETWEEN 1 & 2,) TO THE 150 PSF DESIGN LOAD. NO TEMPORARY SHORING IS REQUIRED, UNLESS CONTRACTOR IS EXPECTED TO EXCEED 150 PSF LIVE LOAD. IF SHORING IS REQUIRED, IT SHALL BE PLACED CENTERED, UNDER EACH W24x68 BEAM AT THE INTERSECTION OF GRID LINE B.1. AS AN ADDED PRECAUTION, THE CONTRACTOR SHALL INSTALL A TEMPORARY HARDWOOD STIFFENER AT THE SHORING LOCATION, ONE ON EACH SIDE OF THE BEAM WEB. STIFFENERS SHALL FIT SNUG BETWEEN TOP AND BOTTOM FLANGES WITHOUT MECHANICAL CONNECTIONS OF ANY KIND.
3. CONTRACTOR'S WORK ZONE IS SHOWN ON DRAWING NO. A-004. ALL CLEARANCES SHOWN MUST BE MAINTAINED AT ALL TIMES.

**LEGEND:**

- EXISTING STEEL TO BE REMOVED
- REMOVAL OF EXISTING PRECAST CONCRETE PARAPET



KEY PLAN  
SCALE: NONE

CONTRACT NO.  
**13-FQ10060-MCAP-19**

DESIGNED		DATE		REFERENCE DRAWINGS		REVISIONS	
NUMBER	DESCRIPTION	DATE	BY	NUMBER	DESCRIPTION	DATE	BY
DESIGNED	W. ROBIN	08/12					
DRAWN	C. RICHARDSON	08/12					
CHECKED	D. MOSTOLLER	11/12					
APPROVED	M. AKLAN	11/12					

**WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY**

DEPARTMENT OF TRANSIT INFRASTRUCTURE  
AND ENGINEERING SERVICES  
OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM

APPROVED \_\_\_\_\_

SUBMITTED \_\_\_\_\_  
PROJECT MANAGER



**DESIGN OF NEW STAIR FOR  
BETHESDA STATION**

STRUCTURAL  
DEMOLITION – EXISTING MEZZANINE STEEL

SCALE AS SHOWN	DRAWING NO. S-100	SHEET NO. -010
-------------------	----------------------	-------------------