WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY



CONTRACT NO. FQ16078 VOLUME 3

STRUCTURAL RETROFIT OF B9 BEAM FARRAGUT NORTH METRORAIL STATION


CONTRACT DRAWINGS

AUGUST 2015



ABBREVIATIONS

| BRG./BRGS. | BEARINGS | LF | LINEAR FEET |
|------------|---|--------|-------------------------------|
| BOT. | BOTTOM | LLV | LONG LEG VERTICAL |
| CFRP | CARBON FIBER-REINFORCED POLYMER | L.P. | LOW POINT |
| C.I.P. | CAST-IN-PLACE | LS | LUMP SUM |
| ç | CENTER LINE | MAT'L | MATERIAL |
| | CLEARANCE | MAX. | MAXIMUM |
| CL. | | MIN. | MINIMUM |
| CLR | CLEAR | MH | MANHOLE |
| COL./COLS. | COLUMN/COLUMNS | MNFR | MANUFACTURER |
| CONC. | CONCRETE | N/A | NOT APPLICABLE |
| CONST. | CONSTRUCTION | NO. | NUMBER |
| COTR | CONTRACTING OFFICER TECHNICAL REPRESENTATIVE | N.T.S. | NOT TO SCALE |
| C.O.R. | CONTRACTING OFFICER | 0.B. | OUTBOUND |
| | REPRESENTATIVE | OH | OVERHEAD |
| CY | CUBIC YARD | OPNG | OPENING |
| DB | REINFORCING BAR DIAMETER | Æ | PLATE |
| DIA. | DIAMETER | PT. | POINT |
| DWG. | DRAWING | RA | RETURN AIR |
| EXP. | EXPANSION | R.S.A. | REVENUE SERVICE ADJUSTMENT |
| E.B. | EASTBOUND | SA | SUPPLY AIR |
| E.F. | EACH FACE | SAN. | SANITARY |
| EL | ELEVATION | | SQUARE FEET |
| EXIST. | EXISTING | S.F. | SPACING |
| Ŧ.S. | FAR SIDE | SPA. | STAINLESS STEEL |
| T. | FEET | SS | |
| GALV. | GALVANIZED | SSWP | SITE SPECIFIC WORK PLAN |
| GFRP | GLASS FIBER-REINFORCED | ST. | STORM |
| | POLYMER | STIFF. | STIFFENER |
| GOTRS | GENERAL ORDER TRACK RIGHTS | T.C. | TENSION CONTROL |
| H.P. | HIGH POINT | TYP. | TYPICAL |
| H.S. | HIGH STRENGTH | VERT. | VERTICAL |
| I.B. | INBOUND | V.I.F. | VERIFY IN FIELD |
| IN | INCHES | U.O.N. | UNLESS OTHERWISE NOTED |
| JT | JOINT | | |




SYSTEM MAP N.T.S.

INDEX OF DRAWINGS

| | | | <u>···· ·····</u> | | |
|-----------|-----------|---|-------------------|------------|--------------------------------------|
| SHEET NO. | DWG. NO. | TITLE OF DRAWING | SHEET NO. | DWG. NO. | TITLE OF DRAWING |
| M1275-01 | A02-S-001 | VICINITY MAP & ABBREVIATIONS | M10-147 | A03-S-002 | STRUCTURAL KEY PLAN - STA. 37+62 TO |
| M1275-02 | A02-S-002 | GENERAL NOTES | M10-207 | A03-S-163 | VAULT ROOF PLAN BELOW "L" STREET ST |
| M1275-03 | A02-S-100 | BEAM 9 LEVEL PLAN | M10-208 | A03-S-153 | BEAM DETAILS FOR VAULT BELOW "L" STR |
| M1275-04 | A02-S-101 | PLATFORM LEVEL PLAN | M10-210 | A03-S-154 | VAULT ROOF PLAN BELOW "L" STREET – |
| M1275-05 | A02-S-300 | SECTIONS - 1 | M10-211 | A03-S-141 | STRUCTURE UNIT A441 |
| M1275-06 | A02-S-301 | SECTIONS - 2 | M10-212 | A03-S-127 | VAULT & PLATFORM PLAN – STRUCTURE |
| M1275-07 | A02-S-500 | STRUCTURAL DETAILS | M10-213 | A03-S-155 | PART ROOF SLAB BELOW "L" STREET – S |
| M1275-08 | A02-S-501 | SUPPORT COLUMN DETAILS - 1 | M10-214 | A03-S-142 | STRUCTURE UNIT A436 |
| M1275-09 | A02-S-502 | SUPPORT COLUMN DETAILS - 2 | M10-302 | A03-A-005 | PLATFORM PLAN & STATION SECTION STA. |
| M1275-10 | A02-S-503 | JACKING DETAILS | M80-026 | FA3-A-021 | STATION SECTIONS & DETAILS |
| M1275-11 | A02-S-504 | PLATFORM REINFORCEMENT DETAILS | M80-067 | FA3-AC-002 | FARRAGUT NORTH STATION AIR CONDITION |
| M1275-12 | A02-M-001 | SYMBOLS, ABBREVIATIONS, AND NOTES | | | STA. 43+00 TO STA. 45+40.83 |
| M1275-13 | A02-M-002 | MECHANICAL DEMOLITION AND NEW WORK PLAN | M80-074 | FA3-AC-13 | FARRAGUT NORTH STATION AIR CONDITION |
| | | | | A02-M-102 | A02 FARRAGUT NORTH STATION, MECHANIC |

| | REFERENCE DRAWINGS | | REVISIONS | Staterer 9. Men | WASHINGTON METROPOLITA | AREA TRANSIT AUTHORITY |
|------------------------------|--------------------|---------|-------------|------------------|--|------------------------|
| DESIGNED CTV 7-30-15 DATE | NUMBER DESCRIPTION | DATE BY | DESCRIPTION | | | |
| DRAWN 7 7 | | | | STRUCT OF COLLER | DEPARTMENT OF TRANSIT INFRASTRUCTURE | A Gannett Fleming/Par |
| DATE CHECKED CTV 7-30-15 | | | | | AND ENGINEERING SERVICES | JOINT VENTU |
| DATE APPROVED DAB 7-30-15 | | | | HA CONSTOL | OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM | |
| APPROVED DAB 7-30-15 DATE | | | | TOSONAL ENGR | | |
| | | | | | APPROVED | PROJECT MANAGER |



STRUCTURAL GENERAL NOTES

- REPAIR/RETROFIT THE EXISTING WMATA STRUCTURES AS SHOWN ON THE DRAWINGS. FOR DESCRIPTION OF WORK, APPLICABLE REFERENCES, REQUIRED SUBMITTALS, QUALITY ASSURANCE, MATERIALS, EXECUTION, SEE PROJECT SPECIFICATIONS IN ADDITION TO THESE NOTES.
- FOR DETAILS OF EXISTING STRUCTURE, SEE REFERENCE DRAWINGS; WMATA, SECTION A-3, CONNECTICUT AVENUE ROUTE, JUNE 1970 APPROVED FOR CONSTRUCTION JUNE 17. 1970.
- ALL APPLICABLE DIMENSIONS, LOCATIONS, CLEARANCES AND ELEVATIONS OF 3. EXISTING STRUCTURES SHOWN ON THE DRAWINGS AND IN THE REFERENCE DRAWINGS SHALL BE VERIFIED BY THE CONTRACTOR IN THE FIELD PRIOR TO PREPARATION OF SHOP DRAWINGS AND COMMENCEMENT OF ANY WORK. IF DISCREPANCIES ARE DISCOVERED BETWEEN EXISTING CONDITIONS AND TH CONTRACT WORK, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE C.O.R.
- ALL WORK WITHIN WMATA FARRAGUT NORTH STATION WILL BE SUBJECT TO 4. WORK HOUR RESTRICTIONS AS SPECIFIED IN THE CONTRACT DOCUMENTS.
- THE CONTRACTOR SHALL KEEP DEBRIS FROM FALLING ON THE TRACKS BY 5. PROVIDING A DEBRIS CONTAINMENT SYSTEM WHERE APPLICABLE OR AS DIRECTED BY C.O.R.
- 6. THE CONTRACTOR SHALL MAINTAIN AND MONITOR EXISTING UTILITIES DURING THE EXECUTION OF WORK IN THE VICINITY OF THE PLATFORM.
- CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL IN ACCORDANCE WITH THE SPECIFICATIONS.
- 8. UPON COMPLETION OF WORK, CONTRACTOR SHALL RESTORE SITE TO THE CONDITION THAT EXISTED PRIOR TO THE START OF THE CONTRACT.
- FALSEWORK SHORING SHALL BE DESIGNED IN ACCORDANCE WITH THE AASHTO "GUIDE SPECIFICATIONS FOR BRIDGE TEMPORARY WORKS," 1995. FALSEWORK SYSTEMS ARE TO BE CONFIGURED SUCH THAT THE EXISTING PLATFORM IS NOT DAMAGED OR OVER STRESSED BY TEMPORARY LOADS
- 10. ALL DIMENSIONS SHOWN ON THE PLANS ARE MEASURED HORIZONTALLY OR VERTICALLY UNLESS OTHERWISE NOTED, DIMENSIONS SHALL NOT BE MEASURED FROM THE PLANS.
- A. SPECIFICATIONS
- A1. CONSTRUCTION: WMATA MANUAL OF DESIGN CRITERIA FOR MAINTAINING & CONTINUED OPERATION OF FACILITIES & SYSTEMS, RELEASE 9, REVISION 2, AUGUST 2014
- A2. DESIGN: WMATA MANUAL OF DESIGN CRITERIA, FACILITIES, SECTION 15, 2014.
- A3. DESIGN: AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS AASHTO "STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES," 17TH EDITION, 2002.
- A4. DESIGN: BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE, ACI 318-99

B. LOADINGS

- B1. ALL LOADINGS SHALL BE IN ACCORDANCE WITH WMATA MANUAL OF DESIGN CRITERIA FOR MAINTAINING & CONTINUED OPERATION OF FACILITIES & SYSTEMS, RELEASE 9, REVISION 2, AUGUST 2014.
- B2. TEMPORARY CONSTRUCTION LOADING ON THE PLATFORM SHALL NOT EXCEED 150 PSF AND THE WEIGHT OF MATERIAL TRANSPORTED ACROSS THE PLATFORM SHALL NOT EXCEED 5000 LBS AT A TIME.
- B3. THE MAXIMUM WEIGHT OF MATERIAL TRANSPORTED VIA ESCALATOR AND ELEVATORS DURING CONSTRUCTION, SHALL NOT EXCEED 200 PSF.

C. MATERIALS

- C1. CONCRETE (MIN. 28-DAY STRENGTHS): CONCRETE NON-SHRINK GROUT ..f'c = 7.500 psi CAST IN PLACE SUPPORT PEDESTALS / PLATFORMfc = 5,000 psi LEAN CONCRETE FILL . .f'c = 1.000 psi
- C2. ALL EXPOSED CORNERS SHALL BE CHAMFERED $\frac{3}{4}$, UNLESS SHOWN OTHERWISE.
- C3. CONSTRUCTION JOINTS SHALL BE MADE WHERE SHOWN IN THE PLANS. ADDITIONAL JOINTS SHALL BE MADE ONLY WITH THE APPROVAL OF THE COR

- C4. REINFORCING STEEL: ALL REINFORCING STEEL SHALL BE ASTM A615, GRADE 60, EPOXY COATED
- C5. ALL REINFORCING STEEL SHALL HAVE 2" CLEAR COVER FOR PRIMARY REINFORCEMENT AND 1 1/2 " FOR STIRRUPS, UNLESS OTHERWISE NOTED.
- C6. ALL BEND DIMENSIONS FOR REINFORCING STEEL SHALL BE OUT-TO-OUT OF BARS, ALL PLACEMENT DIMENSIONS SHALL BE TO THE CENTER OF BARS, UNLESS OTHERWISE NOTED.
- C7. FIELD ADJUSTMENTS OF REINFORCING STEEL SHALL BE MADE ONLY WITH APPROVAL OF THE C.O.R. CUT BARS MUST HAVE ACCOMPANYING BARS OF THE SAME SIZE WITH APPROPRIATE LAP ACROSS THE CUT LOCATION. THE SHOP DRAWINGS SHALL INCLUDE ADDITIONS OR REARRANGEMENT OF REINFORCING STEEL FROM THAT SHOWN ON THE PLANS.
- C8. BAR LAPS, HOOKS AND BENDS SHALL HAVE A MINIMUM LENGTH IN ACCORDANCE WITH AASHTO, OR AS SHOWN ON THE PLANS.
- C9. WELDING OF REINFORCING BARS IS NOT PERMITTED UNLESS APPROVED IN WRITING BY THE COTR.
- C10. FIELD BENDING OF REINFORCING BARS PARTIALLY EMBEDDED IN CONCRETE IS NOT PERMITTED. REBAR SHALL NOT BE HEATED WITH A TORCH IN THE FIFI D
- C11. FABRICATED STRUCTURAL STEEL SHALL BE AASHTO M270, GRADE 50. UNLESS NOTED OTHERWISE. ALL FABRICATED STRUCTURAL STEEL AND HARDWARE SHALL BE GALVANIZED EXCEPT A490 T.C. BOLTS.
- C12. ALL FASTENERS ARE TO BE 1" DIA. A490 T.C. BOLTS, UNLESS OTHERWISE NOTED.
- C13. ANCHOR BOLTS ARE TO BE ASTM F1554, GRADE 55. SET ANCHOR BOLTS BY TEMPLATE OR PREFORMED HOLES. FILL PREFORMED HOLES WITH NON-SHRINK GROUT.
- C14. PROVIDE SPRAYED CEMENTITOUS FIREPROOFING MATERIAL ON ALL STRUCTURAL INTERMEDIATE SUPPORT ELEMENTS (MINIMUM 1" THICKNESS). FIREPROOFING MATERIAL IS TO HAVE A MINIMUM 3 HOUR FIREPROOFING RATING, SEE CONTRACT SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- C15. PROVIDE CFRP PRECURED STRIPS TO TEMPORARILY STRENGTHEN THE EXISTING PLATFORM SLAB AS INDICATED. SEE CONTRACT SPECIFICATIONS FOR ADDITIONAL INFORMATION.

BEAM 9 RETROFIT CONSTRUCTION SEQUENCE


- 1. REMOVE, STORE AND PROTECT THE EXISTING GRANITE BENCH AND EXISTING PYLON WITHIN THE VICINITY OF THE RETROFIT. STORE ON THE SOUTH END OF THE PLATFORM (SEE SCHEMATIC).
- 2. SET BARRICADES AS APPLICABLE FOR CONSTRUCTION. (SEE SCHEMATIC)
- 3. REMOVE EXISTING FLOOR TILES AS INDICATED.
- 4. INSTALL CFRP REINFORCING STRIPS AND TEMPORARY WOOD SUPPORTS AS SHOWN PRIOR TO PLATFORM REMOVAL
- 5. SAWCUT AND REMOVE EXISTING PLATFORM TO THE LIMITS SHOWN FOR COLUMN INSTALLATION AND BENCH RELOCATION.
- 6. REMOVE AND STORE EXISTING CEILING PANELS AND SUPPORTING ELEMENTS TO FACILITATE BEAM 9 RETROFIT.
- 7. RELOCATE MECHANICAL AND HVAC ELEMENTS AS APPLICABLE (SEE MECHANICAL PLANS)
- 8. CLEAN AND PREPARE INVERT SLAB FOR PEDESTALS, INSTALL DOWELS AND CONSTRUCT CIP CONCRETE SUPPORT PEDESTALS. DO NOT INSTALL STEEL COLUMNS UNTIL PEDESTALS HAVE REACHED A MINIMUM COMPRESSIVE STRENGTH OF 2500 PSI.
- 9. INSTALL STEEL COLUMN ANCHOR BOLTS BY USE OF A TEMPLATE OR PRE-FORMED HOLES.
- 10.INSTALL TOP PLATE ANCHOR RODS INTO THE EXISTING BEAM 9 AS NOTED. USE A TEMPLATE FOR POSITIONING THE ANCHOR RODS
- 11.INSTALL TOP PLATES AND LOCK INTO POSITION WITH HEX NUTS AS INDICATED. OPTIONALLY USE ANCHOR RODS TO SUPPORT BOTTOM PLATES PRIOR TO COLUMN ERECTION (SEE DETAIL ON SHEET S-503).
- 12 FRECT STEEL COLUMN SYSTEMS INCLUDING COLUMNS, BATTEN PLATES, BOTTOM PLATES AND STIFFENING ASSEMBLIES. INSTALL WELDED CONNECTIONS WHERE APPLICABLE. DO NOT EXCEED LOADS NOTED IN GENERAL NOTES, ITEM B.
- 13. INSTALL HYDRAULIC JACKS. VERTICALLY JACK THE CYLINDERS IN UNISON TO 145 TONS/JACK AND LOCK-OFF. SEE JACKING NOTES ON SHEET S-503 FOR ADDITIONAL INFORMATION.
- 14.INSTALL REINFORCEMENT AROUND THE HYDRAULIC JACKS AS SHOWN AND PLACE NON-SHRINK GROUT TO THE LIMITS IDENTIFIED.
- 15. INSTALL FIREPROOFING ON ALL EXPOSED STRUCTURAL STEEL.
- 16.INSTALL PLATFORM DOWELS AND REINFORCEMENT, RECONSTRUCT PLATFORM AND CONSTRUCT NEW BENCH PEDESTAL

17. INSTALL LEAN CONCRETE AT THE BASE OF THE COLUMNS AS SHOWN.

18. INSTALL CLADDING.

- 19. RE-INSTALL CEILING PANELS AND MODIFY PANELS & SUPPORT ELEMENTS AS REQUIRED TO FIT AROUND CLADDING.
- 20.RE-INSTALL BENCH AND PYLONS TO THE LOCATIONS INDICATED.
- 21.INSTALL PLATFORM TILES TO THE OUTSIDE LIMITS OF THE CLADDING & RELOCATED BENCH.

22.REMOVE BARRICADES.




| | | REFERENCE DRAWINGS | | | REVISIONS | Statener ?. Wern | WASHINGTON METROPOLITA | N AREA TRANSIT ALITHORITY |
|------------------------------------|--------|--------------------|------|----|-------------|---|--|---------------------------|
| DESIGNED CTV 7-30-15 DATE | NUMBER | DESCRIPTION | DATE | BY | DESCRIPTION | | | |
| DRAWN 7-30-15 | | | | | | STRCT OF COLLER | DEPARTMENT OF TRANSIT INFRASTRUCTURE | A Gannett Fleming/Parsons |
| DATE CHECKED <u>CTV</u> 7–30–15 | | | | | | A (2 (2) (2) (2) (2) (2) (2) (2) | AND ENGINEERING SERVICES | JOINT VENTURE |
| DATE | | | | | | /R | OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM | |
| APPROVED DAB 7-30-15 DATE | | | | | | CA LICENSED | APPROVED | SUBMITTED DAVID BURROWS |
| | | | | | | | AFFROVED | PROJECT MANAGER |


| APPROXIMATE QUANTITIES - BEAM 9 RETROFIT | | | | | | |
|---|------|-------|--|--|--|--|
| | | | | | | |
| ITEM | UNIT | TOTAL | | | | |
| CAST-IN-PLACE CONCRETE | СҮ | 6 | | | | |
| REINFORCEMENT | LBS | 1490 | | | | |
| FIRE PROOFING | SF | 500 | | | | |
| FABRICATED STRUCTURAL STEEL (1) | LB | 21900 | | | | |
| ANCHOR BOLTS | EA | 16 | | | | |
| ANCHOR RODS | EA | 8 | | | | |
| GFRP CLADDING (2) | SF | 300 | | | | |
| CFRP STRIPS | SF | 60 | | | | |

⁽¹⁾ INCLUDES NON-SHRINK GROUT, BASE PLATES, H.S. BOLTS, NUTS, WASHERS & LEAN CONCRETE.


⁽²⁾ INCLUDES ANCHORAGE DEVICES AND BRACING ELEMENTS.




| | MOTES | - | | | | | |
|---|----------------------|--------------------|-------------------------|--------------|---------|--|--|
| LAYOUT € OF COLUMN SUPPORTS AT THE € OF THE BEAM 9 WEBS. VERIFY 32'-10" DIMENSION AND REVISE AS APPLICABLE BASED ON ACTUAL BEAM DIMENSIONS. | | | | | | | |
| | В | ID DOCU | MENTS | CONTRACT NO. | 6078 | | |
| n s | STRUC FARRAG | TURAL F UT NORT | | | | | |
| E | | BEAM S | 9 LEVEL P | LAN | | | |
| | SCALE 3/16"=1'−0" | 1 3 5 7 | drawing no. A02—S—10 | O N | 1275-03 | | |













| | | REFERENCE DRAWINGS | | | REVISIONS |
|---|--------|--------------------|------|----|-----------|
| DESIGNED <u>S. GROVER</u> 06/15 DATE | NUMBER | DESCRIPTION | DATE | BY | DESCRIPTI |
| DRAWN <u>S. GROVER</u> 06/15 DATE | | | | | |
| CHECKED J. MEAGHER 06/15 DATE | | | | | |
| APPROVED H. THOMAS 06/15 | | | | | |
| DATE | | | | | |










CONCRETE PEDESTAL SECTION $(5-500) \quad 3/4" = 1'-0"$



PRECAST CLADDING LAYOUT $(5-500) \quad 3/4" = 1'-0"$

WASHINGTON METROPOLITAN AREA TRANSIT AUTHORITY


DEPARTMENT OF TRANSIT INFRASTRUCTURE AND ENGINEERING SERVICES OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM





APPROVED

SUBMITTED

DAVID BURROWS PROJECT MANAGER








M1275-08

A02-S-50



7-30-1

DATE

APPROVED DAB

OFFICE OF INFRASTRUCTURE RENEWAL PROGRAM


APPROVED

SUBMITTED DAVID BURROWS PROJECT MANAGER

NOTES:

- 1. MARK TOP AND BOTTOM PLATES TO IDENTIFY THE LOCATION OF 9.65" DIAMETER HYDRAULIC JACKS.
- 2. ENSURE 100% CONTACT BETWEEN BOTTOM OF EXISTING BEAM & TOP PLATE BY MEANS OF GRINDING THE BEAM OR BY GROUTING THE VOIDS BETWEEN THE TWO SURFACES WITH NON-SHRINK GROUT.
- 3. WELD ALL AROUND STIFFENERS & COLUMNS TO BOTTOM PLATE.
- 4. COLUMN SYSTEM INCLUDING COLUMNS, BATTEN PLATES, STIFFENER ASSEMBLIES AND BOTTOM PLATE CAN BE ASSEMBLED IN THE SHOP TO THE EXTENT THAT THE CONTRACTOR CAN DELIVER AND ERECT WITHIN THE PLATFORM, BASED ON THE SITE LIMITATIONS AND CONTRACTOR MEANS AND METHODS. DO NOT EXCEED THE WEIGHT LIMITS SHOWN ON SHEET S-002, ITEM B, LOADINGS.

| | | FQ16078 |
|---------|--|---------------------------|
| | STRUCTURAL RETROFIT C FARRAGUT NORTH METROR | OF B9 BEAM AIL STATION |
| ns E | SUPPORT COLUMN DETAI | LS-2 |
| _ | SCALE 1/2"=1'-0" 1 6" 0 1 2 A02-S-502 | M1275-09 |
| | | |




APPROVED

DATE

1. VERIFY THE LOCATION OF THE EXISTING POST-TENSIONING DUCTS IN THE VICINITY OF THE PROPOSED HILTI RODS WITH A PACHOMETER. ADJUST HILTI ROD LOCATIONS AS REQUIRED TO MISS POST-TENTIONING DUCTS PRIOR TO DRILLING HOLES IN THE TOP PLATE.


- JACK ALL FOUR CYLINDERS TO A UNIFORM LOAD. THE JACKING OPERATION IS TO BE MONITORED AS INDICATED IN ORDER TO VERIFY THAT EXCESSIVE MOVEMENTS AND/OR UNBALANCED LOADING DOES NOT OCCUR IN THE BEAM.
- 2. IN ORDER TO CONTROL THE UNIFORM LOADING, USE A ENERPAC SLCG-8 SERIES LIFT SYSTEM (OR EQUIVALENT). THE ACCURACY TOLERANCE BETWEEN LEADING AND LAGGING CYLINDERS IS NOT TO EXCEED 0.04".
- JACK EACH CYLINDER TO 145 TONS AT INCREMENTS OF 25 TONS/JACK VERIFY THAT ALL FOUR JACKS ARE LOADED EQUALLY BEFORE ADDING ADDITIONAL LOAD. CONTINUE THIS PROCESS UNTIL 145 TON/JACK IN REACHED. LOCK-OFF CYLINDERS (TO PERMANENTLY REMAIN).
- 4. DURING THE JACKING OPERATION, MONITOR THE VERTICAL MOVEMENT OF BEAM 9. IF THE BEAM MOVES 3" VERTICALLY PRIOR TO REACHING 145 TONS/JACK, STOP THE OPERATION AND NOTIFY THE C.O.R.
- 5. DURING THE JACKING OPERATION, VISUALLY MONITOR THE ADJACENT CEILING SLABS SUPPORTED FROM BEAM 9. IF CRACKING OF THE SLABS OCCUR DURING THIS OPERATION, STOP WORK AND NOTIFY THE C.O.R.
- 6. AFTER JACKS ARE LOCKED, INSTALL REINFORCEMENT & PLACE NON-SHRINK

| | | ACT NO. FQ16078 |
|----|---|--------------------------|
| ns | STRUCTURAL RETROFIT OF FARRAGUT NORTH METROR | F B9 BEAM AIL STATION |
| E | JACKING DETAILS | |
| _ | SCALE 6" 3" 0 6" DRAWING NO. A02-S-503 | M1275-10 |



SYMBOLS AND ABBREVIATIONS

POINT OF CONNECTION POINT OF DISCONNECT DUCT



| CONTRACTING OFFICER REPRESENTATIVE | C.O.R. |
|------------------------------------|--------|
| EXISTING | (E) |
| TYPICAL | TYP. |
| STAINLESS STEEL | SS |
| FEET | FT |
| INCHES | IN |
| MANHOLE | MH |
| RETURN AIR | RA |
| SUPPLY AIR | SA |
| CENTER LINE | Ę |
| DEMOLISH | DEMO |


| | | | REFERENCE DRAWINGS | | | REVISIONS |
|---------------------------|---------------|--------|--------------------|------|----|------------|
| DESIGNED P. SANFORD | 06/15 | NUMBER | DESCRIPTION | DATE | BY | DESCRIPTIO |
| DRAWN <u>A. PINKOWSKI</u> | 06/15 DATE | | | | | |
| CHECKED <u>C. ROSS</u> | 06/15 DATE | | | | | |
| APPROVED D. BURROWS | 06/15 DATE | | | | | |
| | DATE | | | | | |

MECHANICAL GENERAL NOTES DEMOLITION

- 1. THE CONTRACTOR SHALL INSPECT THE SITE AND BECOME INFORMED AS TO THE CONDITION OF THE PREMISES AND THE EXTENT AND CHARACTER OF WORK REQUIRED.
- 2. ALL DEMOLITION SHALL BE ACCOMPLISHED IN PHASES AS REQUIRED TO MEET THE OWNER'S OPERATIONAL NEEDS. SUBMIT DETAILS OF PROPOSED TEMPORARY WORK TO C.O.R. FOR APPROVAL.
- 3. ALL WORK IN RETURN AIR TUNNEL SHALL CONFORM TO "CONFINED SPACE ENTRY" REQUIREMENTS.
- 4. IN REMOVING DESIGNATED COMPONENTS CONTRACTOR SHALL PRESERVE AND PROTECT ADJACENT OR ADJOINING COMPONENTS SUCH AS DUCT TRANSITION PIECES FOR REUSE WITH NEW COMPONENTS.
- 5. REMOVE OR RELOCATE ANY EXISTING PIPING, DUCTWORK OR ELECTRICAL CONDUITS THAT INTERFERE WITH THE DEMOLITION OR INSTALLATION OF NEW WORK. PROVIDE TEMPORARY SERVICE TO EQUIPMENT FOR ITEMS REMOVED. SUBMIT DETAILS OF PROPOSED TEMPORARY WORK TO C.O.R. FOR APPROVAL.
- 6. THE LOCATIONS OF THE VARIOUS DUCTS AND EQUIPMENT AS SHOWN ON THE DRAWINGS ARE INTENDED TO BE DIAGRAMMATIC ONLY. THE CONTRACTOR SHALL CONFORM TO THE CONDITIONS IN THE AREA AND ALL NECESSARY CHANGES IN THE RUN OF THE DUCT FROM THOSE SHOWN IN THE DRAWING SHALL BE MADE AS PART OF THE WORK UNDER THIS CONTRACT SUBJECT TO THE APPROVAL OF THE C.O.R.

GENERAL NOTES:

- EXISTING.
- CONTRACT.
- THE REQUIREMENTS OF THE SPECIFICATIONS.
- DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE.
- FOR SALVAGE.
- ALL EXPOSED METALLIC STRUCTURES.



1. THE PLANS SHOWS THE TYPICAL ARRANGEMENT OF THE NEW EQUIPMENT AND ACCESSORIES IN THE STATION. THE EXISTING RETURN AIR BENCH AND DUCTWORK IS SHOWN IN IT'S APPROXIMATE LOCATION. CONTRACTOR SHALL PROVIDE THE REQUIRED FITTINGS TO CONNECT THE NEW DUCTWORK TO THE

2. THE CONTRACTOR SHALL INSPECT THE ENTIRE SITE AND BECOME INFORMED AS TO THE CONDITION OF THE PREMISES AND THE EXTENT AND CHARACTER OF WORK REQUIRED PARTICULARLY GAINING ACCESS TO THE WORK AREA. NOTE THAT THE ACTUAL CONDITION IN THE FIELD MAY VARY FROM THE EXISTING CONDITIONS SHOWN ON THE DRAWINGS. CONTRACTOR SHALL MAKE MODIFICATIONS IN THE FIELD TO COMPLY WITH THE GENERAL INTENT OF THE

3. COORDINATE ALL MECHANICAL WORK WITH ALL OTHER TRADES TO AVOID CONFLICTS. PROVIDE NECESSARY FITTINGS FOR OFFSETS, RISES AND DROPS TO AVOID CONFLICTS. PROVIDE COORDINATION DRAWINGS IN ACCORDANCE WITH

4. PROVIDE ALL MATERIALS AND EQUIPMENT AND PERFORM ALL LABOR REQUIRED TO INSTALL COMPLETE AND OPERABLE DUCT SYSTEMS AS INDICATED ON THE


5. CONTRACTOR TO COORDINATE WITH THE C.O.R. FOR ANY REMOVED EQUIPMENT

6. GROUNDING OF EXPOSED MATALLIC STRUCTURES SHALL BE PROVIDED. THE GROUNDING SYSTEM SHALL PROVIDE A LOW IMPEDANCE PATH TO GROUND FOR

7. ANY HARDWARE OR STRUCTURAL METAL USED SHALL BE OF TYPE 316 SS.

8. REFER TO REFERENCE DRAWING FA3-AC-21 FOR ADDITIONAL INFORMATION.


| | BID DOCUI | | FQ16078 |
|---------------|-------------------------------|--------------------------|-----------|
| arsons URE | STRUCTURAL R FARRAGUT NORT | | |
| OKL | SYMBOLS, ABBR | - | AND NOTES |
| | SCALE NONE | DRAWING NO. A02-M-001 | M1275-12 |




NEW WORK NOTES

- 1 RECONSTRUCT THE PEDESTAL IN THE NEW BENCH LOCATION WITH TWO NEW 11"X96" WIRE MESH SCREENS AND RE-INSTALL THE GRANITE TOP. USE DETAILS FROM THE AS-BUILT DRAWINGS FOR THE RECONSTRUCTION OF THE RA BENCH PEDESTAL.
- (2) PROVIDE AND INSTALL NEW RETURN AIR DUCTWORK AS NECESSARY. CONNECT RETURN AIR BENCH INTO EXISTING RETURN AIR TUNNEL.
- (3) SEE STRUCTURAL DRAWINGS FOR DETAILS ON PLATFORM WORK.
- (4) CONTRACTOR TO RETURN/REINSTALL SUPPLY AIR PYLON AT ORIGINAL LOCATION AND IN WORKING CONDITION. CONTRACTOR TO REBALANCE SUPPLY AIR PYLON TO ORIGINAL AIR FLOW.
- 5 CONTRACTOR SHALL FIELD FABRICATE RA DUCT CONNECTION BETWEEN RA OPENING IN UNDER PLATFORM WALL AND POINT OF CONNECTION TO RA BENCH PLENUM BOX.

| | 1 | |
|---|----------------|-------------------------------|
| | | |
| | | |
| | | |
| | <u> €</u> ou | TBOUND TRACK |
| | 2 | |
| JRAL _ EXISTING COLUMN _ (TYP.) | r | URN AIR TUNNEL OW PLATFORM |
| | —€ STA | TION |
| EXISTING PYLON - (TYP.) | | |
| | | |
| | | |
| | € INE | BOUND TRACK |
| | | |
| | | |
| | | |
| | | |
| | | |
| | CONTRA | ACT NO. |
| BID DOCUMENTS | F | Q16078 |
| STRUCTURAL RETROFI FARRAGUT NORTH METR | T OF | B9 BEAM |
| URE MECHANICAL DEMOLITION AND | NEW | WORK PLANS |
| SCALE 1/8"=1'-0" 210246810 DRAWING NO. A02-M-C | 02 | M1275-13 |





• • •

··· ·· · · ·· ·


• • • • • •


നുള്ളങ്ങള്ളും കേപ്പാം അംഗ്രം നേട്ട് നേട്ട് പ്രതിക്കുന്നു. പ്രതിക്കുന്നത് പ്രതിക്കുന്നത് പ്രതിക്കുന്നത്. പ്രതിക്

.


-

· · · ·







SEILING LIN SEE DETAIL F DWG. A3-5-14 2 3 5 @ LONGITUDINAL RIDS 2°CE EACH R BENEDNITE PANEL # 7 OPPOSITE EACH IN INSIDE FACE-BONDED CONSTRUCTION T FTOP OF SLAB 1-6 0/13-1 THE SEE VAULT SECTION 214-214 DEG A3-5-141 VAULT WALL "A" SCALE 1/2" = 1=0" TYPICAL WALL DETAIL BELOW L STREET AND GELIERAL NOTES SEE DWG. A3-5-163 FOR REFERENCE ONLY LOCATION OF STRUCTURE AS BUILT UNIT SEE KEY PLAN 4/12/76 CONNECTICUT AVENUE ROUTE VANET ROOF PLAN BELOW "L" STREET STRUCTURE UNIT A 441 **A** 144-1-0- 1-2-3-4-8 A3-8-154 MIO-210



| | | • |
|------|---|---|
| SLAB | 3 NOTE: PCO +107 AS BUILT - WATER PROOFING DESCRIPTION | |
| | SUBSTITUTE BITUTHENE MEMBRANE WATERPROOFING MATERIAL FOR THE FIVE-PLY MEMBRANE SYSTEM SPECIFIED IN THE CONTRACT AND SUBSTITUT PROTECTIVE BOARD FOR CONCRETE OVER THE MEMBRANE IN ALL LOCATION MORE THAN TEN FEET BELOW THE GROUND SURFACE. | |







| NAL REINF. NO POST-TEN- PRE-LOADING 3-5-163 | TE: FOR GENERAL MOTES / LOCATION DF STRUCTURE UNIT SEE KEY PLAN DWG. A 3-5-2 HUGWH 4/12/16 |
|--|--|
| TRANSIT AUTHORITY | CONNECTICUT AVENUE ROUTE |
| | PART ROOF SLAB BELOW "L" STREET STRUCTURE UNIT A 436 |
| | SCALE = 1'-0" - 2 3 4 5 DRAWING NO. A3-S-155 MIO-213 |
| | |

FOR REFERENCE ONLY









.

