



MEMORANDUM


WI #17-009

19 January 2018

Addressed to: Kyle Pepin, GFP

Prepared by: James T. Nelson, Ph.D., P.E. License DC #: PE920122

Subject: Building damage potential – Final Draft
WMATA Green Line
Task Order NO. 17-FQ15191-TSFA-005



Peak particle velocities (PPV) produced by WMATA revenue service trains, road traffic, and internal residential sources were measured at various homes along the WMATA Green Line. The maximum observed peak particle velocities are summarized below in Table 1, which has been extracted from the report “Ground-Borne Noise and Vibration Evaluation.” This table lists the maximum peak particle velocities observed during extended measurement periods over several hours, and thus includes data for several passbys by various types of trains, vibration caused by road traffic, and vibration caused by internal sources such as door closures and footfalls.

The highest events were observed at Site 1 (0.0801 ips PPV Longitudinal), and Site 2 (0.034 ips PPV Transverse). The highest vertical components were generally less than either the longitudinal or transverse. These magnitudes are anomalous relative to maximum particle velocities listed for Sites 3 through 15. Inspection of the logged data for Site 1 and 2 indicate that these events occurred either at the very beginning of the test period or at the very end of the test period. Review of these data indicate that the typical maximum peak particle velocities observed during periods involving numerous train passbys and other sources were of the order of 0.001 to perhaps 0.01 ips PPV. This is typical of ground vibration produced by rapid trains operating in tunnels.

Criteria for cosmetic and structural damage to buildings are generally much higher than the peak particle velocities observed at these homes. A peak particle velocity of 0.5 ips is considered the threshold of cosmetic cracking damage for transient vibration such as blasting, for which some modest cracking of plaster might occur. Further, the strains associated with incident ground vibration with peak magnitude 0.5 ips are comparable with the seasonal and diurnal strains due to temperature changes, and are also comparable with the strains induced by door slams.¹ Cosmetic cracking is a naturally occurring process in buildings. Whiffin² identifies a limit of 0.2 ips PPV for residences with plastered walls and ceiling, above which there is a risk of architectural damage but no structural damage. Whiffin further identifies a magnitude of 0.1 ips PPV below which there is

¹ Dowding, C. H., ., **Construction Vibrations**, Prentice Hall, Upper Saddle River, NJ., 1996, Pg. 186

² Whiffin, A. C. 1971. **A survey of traffic-induced vibrations**. (Report LR419.) Crowthorne, Berkshire, England: United Kingdom Department of Environment, Road Research Laboratory.

“virtually” no risk of architectural damage to normal buildings, and a limit of 0.08 ips PPV below which there is no risk to ruins or ancient monuments. These criteria given by Whiffin are the most conservative of building damage criteria that have been recently listed, for example, by the California Department of Transportation.³ The damage criterion employed by WMATA for new construction is 0.12 ips PPV. The WMATA damage criterion is thus conservative with respect to accepted damage criteria for threshold cracking. Vibration velocities in excess of these limits do not necessarily induce cracking, as pointed out by Dowding.⁴

Table 1: PPV Vibration Data for Residential Survey Sites

| Potential for Building Vibration Damage Assessment | | | | | | | |
|--|-------------------------------------|----------------------|--------|---------------------|----------------------|--------|--------|
| Site # ¹ | > 0.12 in/sec PPV in any direction? | Average PPV (in/sec) | | | Highest PPV (in/sec) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| 1 | NO | 0.0012 | 0.0008 | 0.0005 | 0.0236 | 0.0062 | 0.0801 |
| 2 | NO | 0.0034 | 0.0034 | 0.0021 | 0.0340 | 0.0250 | 0.0120 |
| 3 | NO | 0.0012 | 0.0005 | 0.0004 | 0.0016 | 0.0071 | 0.0016 |
| 6 | NO | 0.0031 | 0.0032 | 0.0021 | 0.0050 | 0.0130 | 0.0070 |
| 7 | NO | 0.0006 | 0.0005 | 0.0003 ² | 0.0012 | 0.0118 | 0.0016 |
| 9 | NO | 0.0029 | 0.0029 | 0.0020 | 0.0030 | 0.0070 | 0.0040 |
| 10 | NO | 0.0031 | 0.0032 | 0.0027 | 0.0110 | 0.0230 | 0.0170 |
| 12 | NO | 0.0032 | 0.0030 | 0.0021 | 0.0180 | 0.0080 | 0.0270 |
| 13 | NO | 0.0005 | 0.0006 | 0.0003 ² | 0.0022 | 0.0115 | 0.0102 |
| 15 | NO | 0.0030 | 0.0029 | 0.0020 | 0.0080 | 0.0140 | 0.0070 |

¹ PPV vibration was only measured at residential measurement sites.

² Resolution of monitoring equipment is 0.00031 inches per second.

PPV = peak particle velocity, inches per second

None of the data collected along the WMATA Green Line for operating trains approach or exceed even the most conservative of threshold damage criteria. Thus, the probability of cosmetic damage, or, for that matter, structural or foundation damage, to buildings along the WMATA Green Line, caused by vibration from rail transit trains is virtually nil.

³ **Transportation- and Construction-Induced Vibration Guidance Manual**, California Department of Transportation, September 2013

⁴ Dowding, C. H., **Construction Vibrations**, Prentice Hall, Upper Saddle River, NJ., 1996, Pg. 168



WMATA

Task Order No. 17-FQ15191-TSFA-005

Ground-Borne Noise and Vibration Evaluation

Final Draft

January 22, 2018

**Prepared for:
Washington Metropolitan Area Transit Authority (WMATA)**



A Gannett Fleming/Parsons
JOINT VENTURE

**800 I ST, NW - 6th Floor
Washington, DC 20001**

Questions about this report should be directed to WMATA's office of External Relations

WI Project 17-009



Table of Contents

| | | |
|-------|--|----|
| 1 | Executive Summary | 5 |
| 2 | Introduction | 7 |
| 2.1 | Purpose..... | 7 |
| 2.2 | Background..... | 7 |
| 3 | Introduction to Decibel Scales..... | 7 |
| 4 | Ground-Borne Noise and Vibration Assessment Criteria..... | 8 |
| 4.1 | WMATA Design Criteria..... | 8 |
| 4.2 | FTA Criteria | 9 |
| 5 | Building Vibration Damage Thresholds..... | 11 |
| 6 | Measurement and Analysis Methodology | 13 |
| 6.1 | Instrumentation and Calibration | 13 |
| 6.2 | Residential Measurements..... | 13 |
| 6.3 | Outdoor-Only Vibration Measurements | 14 |
| 6.4 | Data Analysis..... | 14 |
| 6.4.1 | Train Speeds..... | 14 |
| 6.4.2 | Train Vehicles | 16 |
| 6.4.3 | Ground-Borne Noise and Vibration Levels | 17 |
| 6.5 | PPV Vibration Data Analysis | 18 |
| 6.6 | Rail Roughness Measurements..... | 18 |
| 7 | Site-Specific Field Studies..... | 20 |
| 7.1 | Sample Residential Survey Site – Site 1, 1300 block of Park Road NW..... | 30 |
| 7.1.1 | Site 1 - Building and Tunnel Notes | 30 |
| 7.1.2 | Site 1 - Measurement Positions | 31 |
| 7.1.3 | Site 1 - Vibration and Ground-Borne Noise Assessment Summary..... | 34 |
| 7.1.4 | Site 1 - PPV Results | 35 |
| 7.1.5 | Site 1 - Passby Vibration Spectra and Overall Levels..... | 35 |
| 7.2 | Sample Outdoor Survey Site – Site 8, New Hampshire Avenue NW & Webster Street NW | 45 |
| 7.2.1 | Tunnel Notes..... | 45 |
| 7.2.2 | Measurement Positions..... | 45 |
| 7.2.3 | Overall Level vs Distance Plot | 46 |
| 8 | Discussion of Findings..... | 48 |

| | | |
|-------|--|----|
| 8.1 | Passby Ground-Borne Noise and Vibration Assessment..... | 48 |
| 8.1.1 | Ground-Borne Noise..... | 48 |
| 8.1.2 | Vibration | 50 |
| 8.2 | Potential for Building Damage Assessment..... | 54 |
| 8.3 | WMATA Rail Roughness Measurement Results | 54 |
| 8.4 | 7000 Series Fleet Compared to Other Fleets..... | 56 |
| 8.4.1 | Comparison of Single-Number Decibel Metrics..... | 56 |
| 8.4.2 | Comparison of 1/3-Octave Band Spectra | 57 |
| 9 | Vehicle Characteristics..... | 63 |
| 9.1 | Primary Resonance Frequency | 63 |
| 9.2 | Un-Sprung Mass and Track Resonance (P2) | 64 |
| 9.3 | Wheel Condition | 66 |
| 9.4 | Areas for Exploration..... | 69 |
| | Appendix A Instrumentation and Calibration Documentation | 71 |
| | Appendix B Site-Specific Field Studies | 71 |

Tables

| | | |
|-----------|--|----|
| Table 1: | FTA Ground-Borne Vibration and Ground-Borne Noise Impact Criteria for General Assessment | 10 |
| Table 2: | WMATA Building Damage Assessment Criteria | 12 |
| Table 3: | FTA Construction Vibration Damage Criteria..... | 12 |
| Table 4: | Rail Roughness Measurements Locations | 19 |
| Table 5: | Measurement Sites & Annoyance Criteria | 21 |
| Table 6: | Site 1 Measurement Positions | 31 |
| Table 7: | Site 1 Vibration and Ground-Borne Noise Assessment Summary | 34 |
| Table 8: | Site 1 PPV Results..... | 35 |
| Table 9: | Site 8 Measurement Positions | 45 |
| Table 10: | Ground-Borne Noise Assessment Summary..... | 49 |
| Table 11: | Ground-Borne Vibration Assessment Summary | 51 |
| Table 12: | Summary of Train Consists That Exceeded Applicable Vibration Criteria | 52 |
| Table 13: | PPV Vibration Data for Residential Survey Sites | 54 |
| Table 14: | Audible Ground-borne Noise – Approximate Wavelength Ranges of Interest | 55 |
| Table 15: | Increase in Ground-Borne Noise and Vibration due to 7000 Series Vehicles..... | 57 |
| Table 16: | Vehicle Design Features | 65 |

Figures

| | |
|--|----|
| Figure 1: FTA Criteria for Detailed Vibration Analysis | 11 |
| Figure 2: Example of WMATA Velocity Profile Chart | 15 |
| Figure 3: Example of WMATA Rail Performance Chart | 16 |
| Figure 4: Example of WMATA SPOTS Report | 17 |
| Figure 5: Study Area and Measurement Locations | 22 |
| Figure 6: Green Line Alignment and Measurement Sites (1 of 7) | 23 |
| Figure 7: Green Line Alignment and Measurement Sites (2 of 7) | 24 |
| Figure 8: Green Line Alignment and Measurement Sites (3 of 7) | 25 |
| Figure 9: Green Line Alignment and Measurement Sites (4 of 7) | 26 |
| Figure 10: Green Line Alignment and Measurement Sites (5 of 7) | 27 |
| Figure 11: Green Line Alignment and Measurement Sites (6 of 7) | 28 |
| Figure 12: Green Line Alignment and Measurement Sites (7 of 7) | 29 |
| Figure 13: Site 1 Aerial Map Residence and Exterior Measurement Locations | 32 |
| Figure 14: Site 1 Cross-section Sketch (not to scale) of Indoor and Exterior Measurement Locations | 33 |
| Figure 15: Site 1 at Location V2 1st Floor Living Room | 36 |
| Figure 16: Site 1 at Location V2 1st Floor Living Room | 37 |
| Figure 17: Site 1 at Location V2 1st Floor Living Room | 38 |
| Figure 18: Site 1 at Location V2 1st Floor Living Room | 39 |
| Figure 19: Site 1 at Microphone N1 in Basement Bedroom | 41 |
| Figure 20: Site 1 at Microphone N1 in Basement Bedroom | 42 |
| Figure 21: Site 1 at Microphone N1 in Basement Bedroom | 43 |
| Figure 22: Site 1 at Microphone N1 in Basement Bedroom | 44 |
| Figure 23: Site 8 Aerial Map of Measurement Positions | 46 |
| Figure 24: Site 8 Average Overall Level vs Distance | 47 |
| Figure 25: WMATA Rail Roughness Data | 55 |
| Figure 26: 7000 Series Minus 6000 Series - Basement Positions..... | 58 |
| Figure 27: 7000 Series Minus 5000 Series- Basement Positions..... | 59 |
| Figure 28: 7000 Series Minus 3000 Series - Basement Positions..... | 60 |
| Figure 29: 7000 Series Minus 2000 Series - Basement Positions..... | 61 |
| Figure 30: 7000 Series Minus Mixed Series - Basement Positions..... | 62 |

Figure 31 Photograph of left ground rail (guage corner at bottom) (Rudeen, C. “WMATA Post-Grind Surface Roughness Report”, Loram Maintenance of Way, December 2013, Figure 1 of Page 2) 68

Figure 32 Photograph of right ground rail (guage corner at bottom) (Rudeen, C. “WMATA Post-Grind Surface Roughness Report”, Loram Maintenance of Way, December 2013, Figure 2 of Page 2) 68

1 Executive Summary

Introduction. Wilson Ihrig conducted an extensive measurement program to investigate reports by residents about increased levels of noise and vibration along subway portions of the Washington Metropolitan Area Transit Authority (WMATA) Green Line. Some residents have inquired about the potential for building damage due to train vibration.

This study addresses the following questions:

1. Are ground-borne noise and/or vibration levels inside homes exceeding design criteria?
2. Is vibration causing any damage to residential structures along the alignment?
3. Have any recent changes to the system caused an increase in noise and/or vibration?

These questions are addressed below.

Method. WMATA compiled a list of reports pertaining to ground-borne noise and vibration from residents along the Green Line. In this area, the Green Line tracks are located underground, generally along New Hampshire Avenue. Of the 48 residences from which reports have been received, ten were selected for field measurements by Wilson Ihrig to cover the geographic range of reports and combinations of tunnel and track construction. In addition to the measurements at selected residences, ground vibration was also measured at six outdoor locations to assess areas where no home was surveyed and to measure the rate of vibration attenuation with distance.

The survey was conducted in June and August 2017. Measurements in the homes typically covered a three- to four-hour period of rail operations. In most cases, vibration was measured in two to four rooms inside the home and at one or two locations outside the home. Noise was typically measured in one or two rooms inside the home. At the outdoor-only locations, vibration was measured at multiple distances from the tunnels. In addition to measuring noise and vibration, the rails in the areas near the ten residences were inspected and the rail head surface roughness was measured at most locations using a device made specifically for this purpose.

Assessment Against Design Criteria. The criteria used for this assessment are those that were established when the Mid-City Segment of the Green Line was designed in the late 1980s and early 1990s. The ground-borne noise criteria were not exceeded in any residence. The vibration criteria were exceeded at four residences by 8% to 29% of train passbys. There were no exceedances of the vibration criteria at the other six residences.

Assessment of Potential for Building Damage. All measured vibration levels are well below that at which structural or architectural (cosmetic) damage, such as the propagation of existing cracks in plaster and drywall, could occur. There is a large difference between vibration levels that can be felt and vibration levels that can cause even minor damage.

Assessment of Changes in Noise and/or Vibration Levels. Because numerous homeowner reports were received in a relatively short period of time after years of operation, it is plausible that a change in the system has resulted in a noticeable increase in noise and/or vibration.

Although rail roughness can change over time, the change is typically not abrupt. Rail roughness measurements indicate that the rails are wearing consistently along the alignment. No major rail defects such as spalls, which can occur precipitously, were observed.

WMATA is currently operating five series of trains from four different manufacturers on the Green Line. Data collected inside residences indicate that the noise levels from all train series, including the 7000 Series, are below the design criteria. On average, the 7000 Series noise levels are noticeably louder than the other series cars in eight of the nine homes in which train noise was detectable, although some individual vehicles of the older series do produce comparable levels. See Table 10 for a summary of the ground-borne noise measurement results. Transit system design criteria are not intended to make transit systems inaudible, but, rather, to make the noise levels acceptable in the context of an urban setting that includes traffic, aircraft, and other transportation noise sources.

Although vibration levels from the 7000 Series are also higher, on average, than those from the other vehicles, the vibration levels in most of the residences are still below the level that is widely considered to be the threshold of perceptibility. Trains that generate vibration above the design criteria include cars from most series, not just the 7000 Series. See Table 11 for a summary of the vibration measurement results.

2 Introduction

Wilson Ihrig conducted a survey of ground-borne noise and vibration levels generated by trains operating along the Washington Metropolitan Area Transit Authority (WMATA) Green Line (E Route) in response to reports of vibration and noise by homeowners. The homeowners have indicated that the ground-borne noise and vibration from subway trains is annoying and that this is a relatively recent occurrence (beginning mid- to late-2016). Further, some homeowners have expressed concern regarding the potential for vibration damage to their homes.

2.1 Purpose

The primary purpose of the survey is to measure ground-borne noise and vibration levels during normal revenue operations and compare them to relevant criteria. A secondary purpose is to ascertain which factors, if any, produce more vibration than the others.

2.2 Background

WMATA compiled a list of residences where homeowners have reported elevated noise and/or vibration levels. Candidate residences for measurement were identified based on homeowner reports of noise and vibration, proximity of the residence to the subway or stations, side of the track (outbound or inbound side), and track design details. The locations of the residences were reviewed in conjunction with track and tunnel design details. Candidate measurement locations were identified to cover the geographic range of reports and the distance from the tunnels as well as combinations of tunnel type and rail fixation type. The survey program was designed to provide a broad set of data documenting the noise and vibration levels inside residences. Vibration data were also collected at outdoor-only locations to investigate areas where no residence was available for measurements and to provide a better understanding of how vibration propagates away from the subway tunnels.

3 Introduction to Decibel Scales

Most people equate decibel readings with sound levels, but both noise and vibration levels may be quantified using a decibel scale.

Sound, or noise, levels are expressed in terms of decibels (dB) using the root mean square (RMS) pressure as measured by a microphone. All noise levels in this report use a decibel scale reference of 20 micro-Pascals (20 μ Pa). Because human hearing does not respond equally to all frequencies (e.g., humans cannot hear a dog whistle), the sound signal is often passed through a frequency filter that approximates typical human hearing response. This process is called A-weighting, and the resulting, single-number sound level reading is denoted by “dBA”, meaning decibels that have been A-weighted. It is also possible to analyze the sound signal into constituent frequency components. While there are many ways this can be done, the most common way when dealing with transportation noise is to resolve the sound data into 1/3-octave bands. When plots of 1/3-octave band spectra are presented in this report, the individual band levels are not A-weighted.

In this report, vibration levels are expressed in terms of decibels using the root mean square (RMS) vibration velocity. All vibration decibels in this report use a decibel reference of 1 micro-inch per second (1 $\mu\text{in}/\text{sec}$). To avoid confusion with sound level decibels, vibration decibels are denoted by “VdB”. No weighting is used when calculating the *overall* vibration level, the single-number level that includes the contributions of all frequencies (denoted “OA”). Like sound levels, vibration levels can be resolved into constituent parts expressed as 1/3-octave band levels.

4 Ground-Borne Noise and Vibration Assessment Criteria

4.1 WMATA Design Criteria

WMATA first adopted design criteria to guide the engineering work for new facilities in 1970. By the late 1980s, when the Mid-City Segment of the Green Line was designed, criteria had been developed to minimize annoyance from airborne noise, ground-borne noise, and vibration. The criteria at that time did not include damage criteria. In 2016, WMATA issued its current design criteria. For single-family residences, the current WMATA ground-borne noise criteria are the same as those in use when the Mid-City Segment of the Green Line was designed, whereas the current vibration criteria are slightly (2 VdB) higher. In other words, the vibration design criterion in homes along the Mid-City Segment is 2 VdB less than it would be if that segment were being designed today.

Most locations assessed in this report are in Columbia Heights and Petworth in Northwest Washington D. C., along the Green Line E-Route Mid-City Segment that was designed in the late 1980s and early 1990s. For these locations, the assessment levels used in this analysis are the design criteria taken directly from the environmental study *Noise and Vibration Impact Analysis, Green Line E-Route Mid-City Segment, Design Sections E-2c, E-3, and E-4*¹. Because the measured ambient noise levels along New Hampshire Avenue NW were fairly high at the time of that study, that corridor was treated as a “commercial” community area category, so the ground-borne noise criterion for single-family homes was 40 dBA and the vibration criterion was 70 VdB.

The residences in Michigan Park in Northwest Washington, D. C. are along sections of tunnel that were constructed prior to the Mid-City Segment. The documentation containing the noise and vibration analyses originally conducted for these tunnels is not currently available; however, the design criteria used for the Michigan Park sections are known. As the design was completed before the first transit-specific criteria were developed, the designers utilized criteria that had been developed for heating, ventilation, and air-conditioning (HVAC) systems to assess ground-borne noise. Since this accommodation is outdated, the WMATA design criteria used in the Mid-City Segment study are being applied to the Michigan Park locations. It is assumed that the community area category for this area is either “average residential” or “high density residential”, either of which results in a ground-borne noise criterion of 35 dBA and a vibration criterion of 70 VdB.

¹ Wilson, Ihrig & Associates, Inc., Noise and Vibration Impact Analysis, Green Line E-Route Mid-City Segment, Design Sections E-2c, E-3, and E-4, Washington Metropolitan Transit Authority (WMATA), Revised November 1990.

The applicable ground-borne noise and vibration criteria for each site are presented in Section 7, Site-Specific Field Studies.

4.2 FTA Criteria

The Federal Transit Administration (FTA), developed guidelines to comply with federal laws related to the assessment of ground transportation noise and vibration impacts for federal or federally supported projects. The FTA published guidelines, titled *Transit Noise and Vibration Impact Assessment*² (FTA guidance manual), contain methodology and criteria to assess noise and vibration impacts from mass transit.

The FTA criteria are presented here as reference information only to provide context for the reader. The FTA methodology includes three levels of detail for assessing ground-borne noise and vibration: Screening, General Assessment, and Detailed Analysis. The General Assessment deals only with the overall vibration velocity level and A-weighted sound level. The General Assessment criteria are presented in Table 1. The ground-borne vibration criterion for residences adjacent to a transit line with more than 70 trains per day is 72 VdB. The ground-borne noise criterion for residences adjacent to a transit line with more than 70 trains per day is 35 dBA.

² U.S. Federal Transit Administration, "Transit Noise and Vibration Impact Assessment" (Final Report No. FTA-VA-90-1003-06, May 2006)

Table 1: FTA Ground-Borne Vibration and Ground-Borne Noise Impact Criteria for General Assessment

| Land Use Category | GBV Impact Levels (VdB re: 1 $\mu\text{in}/\text{sec}$) | | | GBN Impact Levels (dB re: 20 μPa) | | |
|--|--|--------------------------------|--------------------------------|---|--------------------------------|--------------------------------|
| | Frequent Events ¹ | Occasional Events ² | Infrequent Events ³ | Frequent Events ¹ | Occasional Events ² | Infrequent Events ³ |
| Category 1: Buildings where vibration would interfere with interior operations. | 65 VdB ⁴ | 65 VdB ⁴ | 65 VdB ⁴ | N/A ⁵ | N/A ⁵ | N/A ⁵ |
| Category 2: Residences and buildings where people normally sleep. | 72 VdB | 75 VdB | 80 VdB | 35 dBA | 38 dBA | 43 dBA |
| Category 3: Institutional land uses with primarily daytime use. | 75 VdB | 78 VdB | 83 VdB | 40 dBA | 43 dBA | 48 dBA |

Source: FTA 2006

¹ "Frequent Events" is defined as more than 70 vibration events of the same kind per day.

² "Occasional Events" is defined as between 30 and 70 vibration events of the same kind per day.

³ "Infrequent Events" is defined as fewer than 30 vibration events of the same kind per day.

⁴ This criterion limit is based on levels that are acceptable for most moderately sensitive equipment such as optical microscopes. Vibration-sensitive manufacturing or research will require detailed evaluation to define the acceptable vibration levels. Ensuring lower vibration levels in a building often requires special design of the HVAC systems and stiffened floors.


⁵ Vibration-sensitive equipment is not sensitive to ground-borne noise.

GBV = ground-borne vibration

GBN = ground-borne noise

N/A = not applicable

The FTA Detailed Analysis is more complex and also considers the frequency spectrum of the noise and vibration. The Detailed Analysis ground-borne vibration criteria are expressed in terms of 1/3-octave band velocity spectra as shown in Figure 1. The criterion for residences, indicated as Residential (Night), is 72 VdB in the 1/3-octave bands between 8 to 80 Hz. The ground-borne noise criteria for a Detailed Analysis are the same as those in Table 1.



Source: FTA 2006

Figure 1: FTA Criteria for Detailed Vibration Analysis

5 Building Vibration Damage Thresholds

Vibration annoyance criteria such as those presented above are an order of magnitude lower than vibration damage thresholds, so if the annoyance criteria are not exceeded, there is no possibility of physical damage.

WMATA vibration building damage criteria were not in place when the Mid-City Segment of the Green Line was designed. In the absence of such criteria, the current WMATA vibration damage

thresholds for minimizing risk of physical damage to buildings during construction are presented below in Table 2. The WMATA vibration damage criteria are expressed in terms of the peak particle velocity (PPV) vibration, which is the appropriate metric for assessing building damage.

Table 2: WMATA Building Damage Assessment Criteria

| Maximum Ground Vibration Magnitude | Application |
|------------------------------------|---|
| 0.20 in/sec PPV in any direction | For buildings that are in generally sound condition. |
| 0.12 in/sec PPV in any direction | For buildings or historical monuments that are considered particularly fragile (as determined by a competent structural engineer) due either to the method of construction or a weakened condition resulting from the age of the structure. |

Source: WMATA Manual of Design Criteria, Release 9, Revision 3, November 2016

PPV = peak particle velocity, inches per second

The FTA guidance manual also provides guideline vibration damage criteria for various building structural categories. Those are provided for reference purposes in Table 3. The FTA vibration damage criteria are presented in terms of PPV. The table also includes the approximate RMS level based on a crest factor of 4, representing a PPV to RMS difference of 12 VdB. These approximate RMS vibration damage levels can be useful as a point of reference.

Table 3: FTA Construction Vibration Damage Criteria

| Building Category | PPV (in/sec) | Approximate L _v ¹ |
|---|--------------|---|
| I. Reinforced-concrete, steel or timber (no plaster) | 0.5 | 102 |
| II. Engineered concrete and masonry (no plaster) | 0.3 | 98 |
| III. Nonengineered timber and masonry buildings | 0.2 | 94 |
| IV. Buildings extremely susceptible to vibration damage | 0.12 | 90 |

Source: FTA 2006

¹ RMS velocity in VdB (re: 1 μin/sec).

PPV = peak particle velocity

L_v = vibration velocity level

6 Measurement and Analysis Methodology

6.1 Instrumentation and Calibration

All measurement instrumentation was calibrated with National Institute of Standards and Technology (NIST) traceable calibration signals. Refer to Appendix A for a summary of all instrumentation and calibration documentation.

6.2 Residential Measurements

WMATA and Wilson Ihrig coordinated access to ten residential survey locations for measurements. Measurements were performed in the morning/daytime or afternoon/evening. Our understanding is that WMATA was operating normally during all of the measurement periods.

Most data were collected with measurement personnel on-site to monitor field recordings and observe train passby noise and vibration. Observations of outside street traffic were also made during the measurements to note heavy trucks, buses, and other road vehicles that might cause interfering vibration. Activity by residents within the houses were also observed and noted. The measurements made at residential locations are referred to as *attended measurements*.

The attended measurement objective was to obtain data for approximately ten passbys of 7000 Series trains and ten passbys of non-7000 Series trains in each direction during both rush hour and non-rush hour service. Special attention was paid to the 7000 Series vehicles because the reports from residents began around the same time as these vehicles were introduced to the system. This objective was not always possible at each location due to the relative numbers of each type of vehicle put into service on the day of the measurement.

Three types of attended measurements were conducted at each residential site, as described below.

- **RMS Vibration:** The typical setup included one vibration sensor in the basement or lowest floor, one vibration sensor on the first floor, one vibration sensor on the second floor (if applicable), and one vibration sensor outside of the building. Based on feedback from residents about where vibration from trains is of concern and the layouts of some residences, additional vibration sensors were positioned at other locations. These sensors measure actual vibration signals (analogous to audio signals) used to determine passby vibration levels for assessing annoyance. Refer to Section 6.4.3 for vibration analysis details.
- **Ground-Borne Noise:** One microphone was positioned on the lowest habitable floor in a room where the resident indicated ground-borne noise from trains is of concern. Based on feedback from residents and the layouts of some residences, an additional microphone was positioned at another location. Refer to Section 6.4.3 for ground-borne noise analysis details.
- **Peak Particle Velocity (PPV):** One specialized PPV vibration monitor was placed in the basement or on lowest floor to log PPV vibration data. PPV vibration data are used to assess the propensity for cosmetic or architectural damage. Refer to Section 6.5 for PPV vibration data analysis details.

The vibration sensors were connected with cables to portable data recorders at a central location on the building property where the data was monitored for quality during the recording process. During the measurement period within each residence, movement within the residence was avoided or kept to a minimum.

The microphones recorded sound in the residence for post-processing. The microphones recorded all sounds, including voices and other noises within the residence; residents were advised of this prior to measurements. During the measurement period within each residence, conversation was avoided or kept to a minimum.

At most residences, Wilson Ihrig also deployed one long-term vibration monitor in the basement or lowest floor for unattended overnight logging of vibration data. The purpose of the overnight monitor was to provide supplemental RMS vibration data and to document fleet variability.

6.3 Outdoor-Only Vibration Measurements

In addition to the residential survey locations, vibration was measured at six outdoor-only locations on public rights-of-way such as sidewalks or roadways. The intent of the outdoor-only measurements was to measure vibration levels near additional residential report locations and to determine the attenuation of vibration levels with distance from the subway tunnels at various locations. Each outdoor-only site consisted of two to eight vibration sensors connected by cables to data recorders. Where possible, the sensors were placed along cross streets in a line at various distances from the tunnels. The measurements were usually focused on areas close to the WMATA tunnels with sensors near the closest residences; however, locations for outdoor-only measurements also included locations where WMATA had received reports from residences that were located beyond the first row of buildings from the alignment.

6.4 Data Analysis

The amount of vibration and ground-borne noise generated by a given rail vehicle depends on many factors, including its design and its speed. Because there are several types of vehicles currently operating simultaneously on the WMATA system, it is important to know which vehicle type(s) passed the measurement site so the noise and vibration levels could be properly attributed. Knowing the train speeds is useful because faster trains typically, though not always, generate more vibration and noise.

The amount of vibration and ground-borne noise also depends on the distance to the track and depth of the tunnel along with the specific track configuration and rail fixation type near each measurement site. Sites near sections of similar track configuration often provided data with similar train passby noise and vibration frequency content but the levels are unique to each site.

6.4.1 Train Speeds

Trains speeds were provided by WMATA in the form of velocity profile charts showing speed as a function of clock time and track location. These charts were used to determine the train speed for passbys on the near track for the date and time duration of the attended measurement period for each residence site. An example of the velocity profile charts is shown in Figure 2.




Figure 2: Example of WMATA Velocity Profile Chart

6.4.2 Train Vehicles

Rail performance charts and SPOTS reports were provided by WMATA that were used to identify individual train passby events and vehicle type for correlation with measured noise and vibration data. Examples of the rail performance charts and accompanying SPOTS reports are shown in Figure 3 and Figure 4.




Figure 3: Example of WMATA Rail Performance Chart

Select Platform: and/or Select ID: Leave blank to remove criteria
 and/or Select 4-digit car number: Leave blank to remove criteria
 Select Date: Select Times (0-24HRS): From To

| ID | Platform | length | dcode | Right door open | Right door close | dwell | Left door open | Left door close | dwell | Head Arrived | Tail cleared | cars | Headway door open to door open |
|-----|----------|--------|-------|-----------------|------------------|-------|----------------|-----------------|-------|--------------|--------------|---|--------------------------------|
| 503 | E05-1 | 8 | 44 | | | | 09:00:48 | 09:01:01 | 13 | 09:00:22 | 09:01:14 | 7332-7333.7335-7334.7304-7305.7275-7274 | - |
| 351 | E05-1 | 6 | 24 | | | | 09:03:08 | 09:03:11 | 3 | 09:02:39 | 09:03:11 | 3290-3291.5097-5096.5038-5039 | 2:20 |
| 351 | E05-1 | 6 | 24 | | | | 09:03:15 | 09:03:21 | 6 | 09:03:15 | 09:03:32 | 3290-3291.5097-5096.5038-5039 | 0:07 |
| 504 | E05-1 | 6 | 44 | | | | 09:05:36 | 09:05:59 | 23 | 09:05:10 | 09:06:10 | 3276-3277.3210-3211.3084-3085 | 2:21 |
| 518 | E05-1 | 6 | 44 | | | | 09:10:10 | 09:10:23 | 13 | 09:09:42 | 09:10:35 | 3092-3093.1060-1061.5126-5127 | 4:34 |
| 353 | E05-1 | 6 | 24 | | | | 09:13:09 | 09:13:18 | 9 | 09:12:41 | 09:13:29 | 6033-6032.5033-5032.6055-6054 | 2:59 |
| 505 | E05-1 | 6 | 44 | | | | 09:16:16 | 09:16:31 | 15 | 09:15:52 | 09:16:44 | 3222-3223.1168-1169.3122-3123 | 3:07 |
| 506 | E05-1 | 6 | 44 | | | | 09:23:59 | 09:24:14 | 15 | 09:23:30 | 09:24:24 | 6005-6004.6117-6116.6171-6170 | 7:43 |
| 354 | E05-1 | 6 | 24 | | | | 09:28:24 | 09:28:37 | 13 | 09:27:55 | 09:28:48 | 3250-3251.3235-3234.3243-3242 | 4:25 |
| 507 | E05-1 | 6 | 44 | | | | 09:32:12 | 09:32:25 | 13 | 09:31:45 | 09:32:34 | unknown | 3:48 |
| 512 | E05-1 | 8 | 44 | | | | 09:39:34 | 09:39:45 | 11 | 09:39:01 | 09:39:57 | 7122-7123.7301-7300.7234-7235.7139-7138 | 7:22 |
| 352 | E05-1 | 6 | 24 | | | | 09:42:09 | 09:42:35 | 26 | 09:41:39 | 09:42:46 | 3009-3008.5135-5134.6115-6114 | 2:35 |
| 508 | E05-1 | 6 | 44 | | | | 09:43:54 | 09:44:08 | 14 | 09:43:24 | 09:44:18 | unknown | 1:45 |
| 511 | E05-1 | 8 | 44 | | | | 09:49:01 | 09:49:15 | 14 | 09:48:36 | 09:49:26 | 3073-3072.6119-6118.6066-6067.6081-6080 | 5:07 |
| 302 | E05-1 | 6 | 29 | | | | 09:54:25 | 09:54:38 | 13 | 09:53:53 | 09:54:46 | 3153-3152.3175-3174.3188-3189 | 5:24 |

Figure 4: Example of WMATA SPOTS Report

6.4.3 Ground-Borne Noise and Vibration Levels

The ground-borne noise and RMS vibration levels for each individual train were calculated over the duration of the passby, typically 3 to 5 seconds. As described above, the residential criteria are based on the RMS levels.

Reasonable effort has been made to exclude from train passby samples any data contaminated by street traffic, resident activity within the house, or other clearly discernable sources not related to the trains. Ambient background noise and vibration spectra (in the absence of trains) were analyzed for comparison. The ambient background spectra shown are averages of multiple samples taken during steady quiet lulls in between train events.

6.5 PPV Vibration Data Analysis

At each residential measurement site, PPV vibration was logged during the entire attended measurement duration using triaxial instruments designed just for that purpose. For this analysis, individual train passages were not analyzed. Rather, the highest and average PPV readings during the entire attended measurement period at each residence are reported. No effort was made to distinguish train vibration from other vibration with the PPV vibration data. The analysis is, thus, inherently conservative because it includes all sources of vibration, not just trains.

6.6 Rail Roughness Measurements

Roughness in the running surface of the rail can lead to increased ground-borne noise and vibration levels. The acoustic roughness of the rail can be measured to determine the variation in height of the rail running surface associated with train wheel rolling noise excitation.

The rail roughness measurement locations are summarized in Table 4. These locations can be found on Figure 6 through Figure 12. Each measurement location is denoted by the rail section over which rail roughness was measured (start and end position), track direction, and specific rail upon which the roughness trace was measured. The individual rail for the roughness trace is denoted by L for left rail and R for right rail. The left and right designations relate to the direction of train travel. The corresponding ground-borne noise and vibration measurement sites that are covered by the rail roughness measurement sections are included in the table. Rail roughness was not measured at all sections corresponding to the noise and vibration measurement sites because the rail roughness measurement equipment is not suitable for use through sections of special track work (such as crossovers and turnouts) or through curved sections of track. However, the rail in all sections corresponding to residential measurement sites was visually inspected for signs of corrugation and/or mechanical defects. No visual evidence of rail corrugation, chips, spalls, etc., was observed at any location.

Table 4: Rail Roughness Measurements Locations

| Location # ¹ | Rail Roughness Measurement Designation ^{2, 3} | Start Position (Track Chainage) | End Position (Track Chainage) | Noise and Vibration Measurement Site ⁴ |
|-------------------------|--|---------------------------------|-------------------------------|---|
| 1 | T1-R-188 | 188+00 (T1) | 196+00 (T1) | Site 6 |
| 2 | T1-L-196 | 196+00 (T1) | 188+00 (T1) | Site 6 |
| 3 | T1-R-201 | 201+00 (T1) | 205+00 (T1) | Sites 7, 8, 9 |
| 4 | T1-L-205 | 205+00 (T1) | 201+00 (T1) | Sites 7, 8, 9 |
| 5 | T2-L-201 | 201+00 (T2) | 205+00 (T2) | Sites 7, 8, 9 |
| 6 | T2-R-205 | 205+00 (T2) | 201+00 (T2) | Sites 7, 8, 9 |
| 7 | T2-R-194 | 194+00 (T2) | 188+00 (T2) | Site 6 |
| 8 | T2-L-188 | 188+00 (T2) | 194+00 (T2) | Site 6 |
| 9 | T2-R-186 | 186+00 (T2) | 180+00 (T2) | Site 5 |
| 10 | T2-L-180 | 180+00 (T2) | 186+00 (T2) | Site 5 |
| 11 | T1-R-286 | 286+40 (T1) | 290+00 (T1) | Sites 14, 15 |
| 12 | T1-L-290 | 290+00 (T1) | 286+40 (T1) | Sites 14, 15 |
| 13 | T2-L-286 | 286+44 (T2) | 290+00 (T2) | Sites 14, 15 |
| 14 | T2-R-290 | 290+00 (T2) | 286+44 (T2) | Sites 14, 15 |
| 15 | T2-L-213 | 213+00 (T2) | 218+00 (T2) | Sites 11, 12, 13 |
| 16 | T2-R-218 | 218+00 (T2) | 213+00 (T2) | Sites 11, 12, 13 |
| 17 | T1-R-213 | 213+00 (T1) | 218+00 (T1) | Sites 11, 12, 13 |
| 18 | T1-L-218 | 218+00 (T1) | 213+00 (T1) | Sites 11, 12, 13 |

¹ Measurements are listed in the order that they were conducted.

² T1 refers to Track 1, the Outbound track. T2 refers to Track 2, the Inbound track.

³ L and R denote left and right rail, respectively, with respect to the direction of train travel.

⁴ The noise and vibration measurement sites located near each rail roughness measurement location are listed.

Roughness was measured with a Corrugation Analysis Trolley (CAT)³ in conformance with reference standard EN 15610:2009(E) Railway Applications – Noise emission – Rail Roughness Measurement Related to Rolling Noise Generation.⁴ Measurements were made over distances in the range of 400 to 800 feet depending on location.

Roughness data were post-processed with the CAT software version 12.01.18805. The software produced the 1/3-octave band roughness spectra as a function of wavelength for each trace.

³ Manufactured by Rail Measurement, Ltd.

⁴ EN 15610 specifies a direct method for characterizing the surface roughness of the rail associated with rolling noise ("acoustic roughness"), in the form of a 1/3-octave band spectrum.

7 Site-Specific Field Studies

Table 5 provides a summary of the measurement sites and the dates and times for the attended measurement period. Measurements were conducted at ten residences and six outdoor-only locations. The table includes the applicable ground-borne noise and vibration assessment criteria for each residential site. Detailed measurement information and data summaries for each site are provided in Appendix B. At the residential sites, the measurements included RMS vibration, ground-borne noise, and PPV vibration. At outdoor-only sites, only RMS vibration was measured.

Figure 5 shows an overview of the area studied and measurement locations. Figure 6 through Figure 12 show closer views of all 16 measurement sites as well as all reporting homeowner locations. The residential measurement sites are indicated in red and the outdoor vibration sites are indicated in yellow. The figures also show track chainage, track type, tunnel type, and the locations of Georgia Avenue-Petworth Station and Fort Totten Station.

Table 5: Measurement Sites & Annoyance Criteria

| Site # | Address | Type ¹ | Chainage T1 = Track 1 T2 = Track 2 | Attended Measurement Period (Day, Date, Hours) | Criteria | |
|--------|---|-------------------|--|--|-----------------|-----------------|
| | | | | | GBN (dBA) | Vibr (VdB) |
| 1 | 1300 block of Park Rd NW | Residence | 143+75 (T2) | Mon, 5 June 2017 16:43 to 20:45 | 40 | 70 |
| 2 | 3600 block of New Hampshire Ave NW | Residence | 163+90 (T2) | Wed, 16 August 2017 09:05 to 12:56 | 40 | 70 |
| 3 | 700 block of Princeton Pl | Residence | 169+00 (T1) | Tue, 6 June 2017 15:50 to 19:15 | 40 | 70 |
| 4 | Rock Creek Church Rd NW & 9 th St NW | Outdoor-Only | 169+00 to 170+00 (T2) | Fri, 2 June 2017 12:22 to 15:23 | N/A | N/A |
| 5 | New Hampshire Ave NW & Randolph St NW | Outdoor-Only | 181+50 to 184+00 (T1) | Fri, 2 June 2017 08:37 to 11:00 | N/A | N/A |
| 6 | 4100 block of New Hampshire Ave NW, Unit [REDACTED] | Residence | 191+75 (T2) | Tue, 15 August 2017 09:01 to 13:02 | 40 | 70 |
| 7 | 4300 block of New Hampshire Ave NW | Residence | 203+50 (T1) | Wed, 7 June 2017 08:30 to 12:40 | 40 | 70 |
| 8 | New Hampshire Ave NW & Webster St NW | Outdoor-Only | 203+50 to 206+00 (T1 & T2) | Thu, 1 June 2017 09:12 to 11:40 | N/A | N/A |
| 9 | 4400 block of 5 th St NW | Residence | 204+50 (T2) | Wed, 9 August 2017 10:07 to 14:00 | 40 | 70 |
| 10 | 4400 block of New Hampshire Ave NW | Residence | 206+75 (T1) | Tue, 8 August 2017 10:03 to 13:59 | 40 | 70 |
| 11 | New Hampshire Ave NW & Buchanan St NW | Outdoor-Only | 213+00 to 215+00 (T1 & T2) | Thu, 1 June 2017 13:10 to 15:21 | N/A | N/A |
| 12 | 4600 block of 4 th St NW | Residence | 214+75 (T2) | Mon, 14 August 2017 14:35 to 18:36 | 40 | 70 |
| 13 | 4600 block of New Hampshire Ave NW | Residence | 216+10 (T2) | Thu, 8 June 2017 14:58 to 19:26 | 40 | 70 |
| 14 | Gallatin St NE & 8 th St NE | Outdoor-Only | 284+50 to 287+50 (T1) | Thu, 1 June 2017 16:45 to 19:55 | N/A | N/A |
| 15 | 800 block of Gallatin St NE | Residence | 288+00 (T1) | Wed, 16 August 2017 17:00 to 20:15 | 35 ² | 70 ² |
| 16 | 1200 block of Gallatin St NE | Outdoor-Only | 303+50 to 304+50 (T1) | Wed, 16 August 2017 17:45 to 19:45 | N/A | N/A |

¹ At residences, RMS (root mean square) vibration, ground-borne noise, and PPV (peak particle velocity) vibration were all measured. At outdoor-only locations, only RMS vibration was measured.

² The criteria shown for Site 15 are provided for reference only. See Section 4 of this report for further information.

N/A = Not Applicable. Design criteria only apply to indoor spaces. There are no criteria for outdoor locations.

GBN = ground-borne noise, dBA

Vibr = vibration, VdB




Figure 5: Study Area and Measurement Locations




Figure 6: Green Line Alignment and Measurement Sites (1 of 7)




Figure 7: Green Line Alignment and Measurement Sites (2 of 7)




Figure 8: Green Line Alignment and Measurement Sites (3 of 7)




Figure 9: Green Line Alignment and Measurement Sites (4 of 7)




Figure 10: Green Line Alignment and Measurement Sites (5 of 7)




Figure 11: Green Line Alignment and Measurement Sites (6 of 7)



Figure 12: Green Line Alignment and Measurement Sites (7 of 7)

The following sections presents a sample of the ground-borne noise and vibration survey data at one residential location, Site 1, 1300 block of Park Road NW, and one outdoor-only location, Site 8, New Hampshire Avenue NW & Webster Street NW. Refer to Appendix B for detailed measurement information and survey data summaries for each site.

7.1 Sample Residential Survey Site – Site 1, 1300 block of Park Road NW

7.1.1 Site 1 - Building and Tunnel Notes

| | |
|---------------------|--|
| Location: | Inbound, Track 2, at 143+75 |
| Building Notes: | Residential townhouse, 4 floors comprised of partial underground basement plus 3 upper floors, exterior wall of brick construction |
| Tunnel Structure: | Earth Tunnel |
| Track Type: | Transition from stiff DF to soft Egg Fasteners |
| T/R Depth: | 73 to 74 feet (Track 2) / 45 feet (Track 1) |
| Train Speed: | 34 to 42 mph |
| Measurement Period: | Monday, 5 June 2017, 16:43 to 20:45 |
| Field Observations: | Homeowners present during the measurements, children playing inside the home on the first and second floors. |

7.1.2 Site 1 - Measurement Positions

The following table lists the sensor positions and distances to the tunnels for Site 1.

Table 6: Site 1 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|----------------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| Triaxial Geo. | Basement Bedroom | 31 | 74 | 80 | 38 | 45 | 59 |
| V1 | | | | | | | |
| N1 | | | | | | | |
| N2 | | | | | | | |
| V2 | | | | | | | |
| V3 | 1 st Floor Livingroom | 25 | 74 | 78 | 32 | 45 | 55 |
| V4 | 2 nd Floor Playroom | | | | | | |
| V5 | Across Street | | | | | | |
| V6 | Across Street | | | | | | |
| V6 | Across Street | | | | | | |

Notes:

- Triaxial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth

The following figure presents an aerial map showing track centerlines and the residential measurement location for Site 1.




Figure 13: Site 1 Aerial Map Residence and Exterior Measurement Locations

The following figure presents a cross-section sketch to illustrate the multi-story sensor locations and arrangement with respect to the tunnels.




Figure 14: Site 1 Cross-section Sketch (not to scale) of Indoor and Exterior Measurement Locations

7.1.3 Site 1 - Vibration and Ground-Borne Noise Assessment Summary

The following table presents a summary of whether or not the passby vibration and ground-borne noise data exceeded the applicable assessment criteria. As can be seen in the table, no passbys exceeded the assessment criteria for vibration or ground-borne noise at Site 1.

Table 7: Site 1 Vibration and Ground-Borne Noise Assessment Summary

| SITE 1 | 1300 BLOCK OF PARK ROAD NW – ATTENDED PASSBY MEASUREMENT ASSEMENT | |
|---------------|--|--------------------|
| | Vibration | >70 VdB? |
| | 7000 Series - Average of Multiple Passbys | NO |
| | 6000 Series - Average of Multiple Passbys | NO |
| | 3000 Series - Average of Multiple Passbys | NO |
| | Mixed Legacy with 4000 Series (Single Passby) | NO |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO |
| | 7000 Series - Individual Train with Highest Overall Vibration | NO |
| | 6000 Series - Individual Train with Highest Overall Vibration | NO |
| | 3000 Series - Individual Train with Highest Overall Vibration | NO |
| | Mixed Legacy - Individual Train with Highest Overall Vibration | NO |
| | Ground-borne Noise (GBN) | >40 dBA? |
| | 7000 Series - Average of Multiple Passbys | NO |
| | 6000 Series - Average of Multiple Passbys | NO |
| | 3000 Series - Average of Multiple Passbys | NO |
| | Mixed Legacy without 4000 Series (Average of Multiple Passbys) | NO |
| | 7000 Series - Individual Train with Highest A-weighting | NO |
| | 6000 Series - Individual Train with Highest A-weighting | NO |
| | 3000 Series - Individual Train with Highest A-weighting | NO |
| | Mixed Legacy - Individual Train with Highest A-weighting | NO |

7.1.4 Site 1 - PPV Results

The following table presents a summary of the building vibration damage assessment. As can be seen in the table, the PPV vibration data did not exceed the threshold for vibration damage at Site 1 for the entire duration of the measurement period.

Table 8: Site 1 PPV Results

| SITE 1 | 1300 BLOCK OF PARK ROAD NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|------------------------------------|--|--------------------|--------|--------|--------------------|--------|--------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | Highest PPV (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0012 | 0.0009 | 0.0006 | 0.0326 | 0.0360 | 0.0801 |
| Basement | | | | | | | |
| 5-Jun-17, 4:58:00 PM to 9:10:50 PM | | | | | | | |

7.1.5 Site 1 - Passby Vibration Spectra and Overall Levels


The section presents samples of the passby vibration spectra and overall levels measured at Site 1. Each chart shows the 1/3-octave band velocity spectra for each measured train series compared against the ambient background vibration in the absence of trains.

The vertical axis is the 1/3-octave band velocity level in VdB. The horizontal axis is the 1/3-octave band center frequency (Hz). The overall level (denoted “OA” on the left-hand side of the chart) is the energy sum of the 1/3-octave band velocity levels over the range of frequencies shown.


There are four plots for each sensor as follows:

1. Average by Vehicle Type, Track 1
2. Average by Vehicle Type, Track 2
3. Highest Individual Train by Vehicle Type, Track 1
4. Highest Individual Train by Vehicle Type, Track

In this summary section, only the data from one vibration sensor are shown for brevity. The complete set of data is included in Appendix B for this and every other location.



**Figure 15: Site 1 at Location V2 1st Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type**



**Figure 16: Site 1 at Location V2 1st Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type**





Figure 17: Site 1 at Location V2 1st Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration



**Figure 18: Site 1 at Location V2 1st Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration**

Passby Ground-borne Noise Spectra and A-weighted Levels


The section presents samples of the passby noise spectra and A-weighted noise levels measured at Site 1. Each chart shows the 1/3-octave band noise spectra for each measured train series compared against the ambient background noise in the absence of trains.

The vertical axis is the 1/3-octave band sound pressure level in dB re 20 μ Pa. The horizontal axis is the 1/3-octave band center frequency (Hz). The A-weighted noise level (denoted "AW" on the right-hand side of the chart) is the A-weighted energy sum of the 1/3-octave band sound pressure levels over the range of frequencies shown.


There are four plots for each sensor as follows:

1. Average by Vehicle Type, Track 1
2. Average by Vehicle Type, Track 2
3. Highest Individual Train by Vehicle Type, Track 1
4. Highest Individual Train by Vehicle Type, Track 2


In this summary section, only the data from one microphone are shown for brevity. The complete set of data is included in Appendix B for this and every other location.




**Figure 19: Site 1 at Microphone N1 in Basement Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type**



**Figure 20: Site 1 at Microphone N1 in Basement Bedroom
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type**



**Figure 21: Site 1 at Microphone N1 in Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level**



**Figure 22: Site 1 at Microphone N1 in Basement Bedroom
 Inbound Trains on Track 2
 Individual Train with Highest A-weighted Level**

7.2 Sample Outdoor Survey Site – Site 8, New Hampshire Avenue NW & Webster Street NW

7.2.1 Tunnel Notes

The following notes pertain to the tunnel and track at Site 8.

Tunnel Structure: Earth Tunnel
Track Type: Egg Fasteners
T/R Depth: 65 to 70 feet

Measurement Period: Thursday, 1 June 2017, 9:12 to 11:40

7.2.2 Measurement Positions

The following table lists the horizontal distances, top-of-rail depth, and total slant distance for each sensor with respect to the inbound and outbound tracks.

Table 9: Site 8 Measurement Positions

| Recorder Channel | Chainage | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|----------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 205+00 | 80 | 67 | 104 | 43 | 67 | 80 |
| A2 | 205+00 | 130 | 67 | 146 | 94 | 67 | 115 |
| A3 | 205+50 | 189 | 69 | 201 | 153 | 69 | 168 |
| A4 | 206+00 | 244 | 70 | 254 | 208 | 70 | 219 |
| B1 | 204+00 | 45 | 65 | 79 | 81 | 65 | 104 |
| B2 | 203+50 | 96 | 66 | 116 | 133 | 66 | 148 |
| B3 | 203+50 | 124 | 66 | 140 | 161 | 66 | 174 |
| B4 | 203+50 | 156 | 66 | 169 | 192 | 66 | 203 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth

The following figure presents an aerial map showing the track centerlines and measurement locations.



Figure 23: Site 8 Aerial Map of Measurement Positions

7.2.3 Overall Level vs Distance Plot

The following chart presents the overall vibration level (VdB) on the vertical axis vs the distance to track centerline on the horizontal axis. Each data point is an average of the overall vibration levels for 7000 Series passbys (purple color symbol) and non-7000 Series (pink color symbol) for each sensor position as a function of horizontal plan distance from track centerline. The data are sorted by 7000 Series and non-7000 Series vehicles on each track. The circle symbol denotes Track 1 data and the square symbol denotes Track 2 data. Distance shown on the graph represents the horizontal distance from the track centerline to the measurement location.




Figure 24: Site 8 Average Overall Level vs Distance

8 Discussion of Findings

8.1 Passby Ground-Borne Noise and Vibration Assessment

Since the ground-borne noise and vibration criteria are only assessed inside buildings, only interior results are presented for each location. Even though measurements were made in multiple rooms in each residence, the criterion apply to every room. Therefore, only the data from the room where the ground-borne noise and vibration levels were highest are presented in this section. All data may be found in Appendix B.

At each site, the data are summarized by both the average and the highest vibration level. Both types of data are presented by vehicle type. For sites where data were collected at multiple locations (the norm), the data presented is that from the location that provided the highest levels.

By way of an example, at Site 1, vibration measurements were made in the Basement Bedroom, the Living Room, and 2nd floor Playroom; and data were collected from trains running on both Track 1 and Track 2. For this site, the highest Average and Highest vibration levels were measured at the 1st floor Living Room location from passbys on the outbound track (Track 1), so these are the levels presented in Table 11. For this site, the outbound track (Track 1) is actually closer to the residence than the inbound track (Track 2) due to the depth of the tunnels, even though the residence is on the inbound T2 side of the alignment.

For rooms where some trains generated noise over the criteria, the “% >” column indicates the percentage of train passbys that exceeded the criterion calculated as a percent of all passbys analyzed for that location on the dominant track. The percentage provides a rough indication of passbys that currently exceed the design criteria to the extent that the fleet mix at the time of the measurements is representative of current operations.

8.1.1 Ground-Borne Noise

Table 10 summarizes the results of the ground-borne noise criteria assessment. Table 10 indicates that all trains generated noise levels below the respective design criterion. The average ground-borne noise level from the 7000 Series vehicles is noticeably higher than the non-7000 vehicles, but the maximum level is often similar for both 7000 and non-7000 vehicles. Ground-borne noise from the trains could be heard except at Site 3. Train noise below 25 dBA is usually difficult to discern from the ambient.

Table 10: Ground-Borne Noise Assessment Summary

| Site # | Ground-Borne Noise (dBA) 7000 Series ⁵ | | | Ground-Borne Noise (dBA) Non-7000 Series ⁵ | | |
|-----------------|--|------------------|------------|--|------------------|------------|
| | Average | Highest | % > 40 dBA | Average ² | Highest | % > 40 dBA |
| 1 | 38 | 39 | --- | 30 | 40 | --- |
| 2 | 29 | 30 | --- | 23 | 31 | --- |
| 3 | --- ⁴ | --- ⁴ | --- | --- ⁴ | --- ⁴ | --- |
| 4 | N/A | N/A | --- | N/A | N/A | --- |
| 5 | N/A | N/A | --- | N/A | N/A | --- |
| 6 | 30 | 35 | --- | 26 | 30 | --- |
| 7 | 32 | 35 | --- | 24 | 28 | --- |
| 8 | N/A | N/A | --- | N/A | N/A | --- |
| 9 | 24 ¹ | 24 | --- | 22 | 31 | --- |
| 10 | 32 | 37 | --- | 25 | 34 | --- |
| 11 | N/A | N/A | --- | N/A | N/A | --- |
| 12 | 29 | 32 | --- | 18 | 22 | --- |
| 13 | 31 | 32 | --- | 32 | 33 | --- |
| 14 | N/A | N/A | --- | N/A | N/A | --- |
| 15 ³ | 30 ¹ | 30 | --- | 25 | 30 | --- |
| 16 | N/A | N/A | --- | N/A | N/A | --- |

¹ Single passby.

² Average of all non-7000 Series trains measured at the site. Refer to site-specific field studies in Appendix B for all data.

³ Ground-borne noise criterion for Site 15 of 35 dBA is provided for reference only. See Section 4 of this report for further information.

⁴ Ground-borne train noise was not discernable at Site 3. All train noise was below the criterion at Site 3.

⁵ This table does not include data from any train passbys where the ROCS SPOTS reports indicated an "unknown" train type.

N/A = Not Applicable. Design criteria only apply to indoor spaces. There are no criteria for outdoor locations.

8.1.2 Vibration

Table 11 presents the summary assessment for vibration annoyance. As with the ground-borne noise assessment, only the data from the room with the highest levels are presented.

As can be seen in Table 11, the average vibration level from 7000 Series train passbys was above the design criterion at one residence, Site 10. The average from the other series did not exceed the criterion at any residence.

Individual trains, some of which were 7000 Series and others of which consisted of other series vehicles, exceeded the vibration criteria in four residences. In all likelihood, these trains had rougher than average wheels or wheels with flat spots formed during hard braking. Wheel flats and rough wheels are the most common cause of higher than average vibration levels.

At Site 10, 4400 block of New Hampshire Ave NW, 7000 Series trains exceeded the criterion of 70 VdB during 6 of 9 passbys on both tracks. The highest vibration level measured for the 7000 Series was 7 VdB over the criterion, which is a noticeable amount. The highest vibration level measured at Site 10 was from a 3000 Series vehicle. This vehicle was 10 VdB over the criterion, which is a noticeable amount. Non-7000 Series trains exceeded the criterion at Site 10 during 7 of 60 passbys on both tracks.

Table 11: Ground-Borne Vibration Assessment Summary

| Site # | Ground-Borne Vibration (VdB) 7000 Series ⁷ | | | Ground-Borne Vibration (VdB) Non-7000 Series ⁷ | | |
|-----------------|--|------------------------|-------------------------|--|------------------------|-------------------------|
| | Average (VdB) | Highest (VdB) | % > 70 VdB ⁶ | Average ² (VdB) | Highest (VdB) | % > 70 VdB ⁶ |
| 1 | 63 | 68 | --- | 57 | 64 | --- |
| 2 | 70 | 71 ⁴ | 1 of 2 50% | 59 | 71 ⁴ | 2 of 21 10% |
| 3 | --- ³ | --- ³ | --- | --- ³ | --- ³ | --- |
| 4 | N/A | N/A | --- | N/A | N/A | --- |
| 5 | N/A | N/A | --- | N/A | N/A | --- |
| 6 | 62 | 64 | --- | 62 | 69 | --- |
| 7 | 67 | 69 | --- | 59 | 64 | --- |
| 8 | N/A | N/A | --- | N/A | N/A | --- |
| 9 | 61 ¹ | 61 | --- | 55 | 63 | --- |
| 10 | 74 ⁴ | 77 ⁴ | 6 of 9 67% | 66 | 80 ⁴ | 7 of 60 12% |
| 11 | N/A | N/A | --- | N/A | N/A | --- |
| 12 | 60 | 62 | --- | 63 | 71 ⁴ | 2 of 22 9% |
| 13 | 66 | 72 ⁴ | 1 of 8 13% | 68 | 79 ⁴ | 9 of 28 32% |
| 14 | N/A | N/A | --- | N/A | N/A | --- |
| 15 ⁵ | 64 | 64 | --- | 61 | 65 | --- |
| 16 | N/A | N/A | --- | N/A | N/A | --- |

¹ Single passby.

² Average of all non-7000 Series trains measured at the site. Refer to site-specific field studies in Appendix B for all data.

³ Train vibration detectable in 63 Hz 1/3-octave band but overall vibration levels dominated by non-train ambient sources. All train vibration was below the criterion at Site 3.

⁴ Vibration levels in **boldface** font exceed the applicable criterion.

⁵ Ground-borne vibration criterion for Site 15 of 70 VdB are provided for reference only. See Section 4 of this report for further information.

⁶ At sites where passby event levels exceeded the criterion, the number of passbys that exceeded, the total number of passbys, and the resulting percentage that exceeded the criterion are provided. These numbers are specific to the vehicle series.

⁷ This table does not include data from any train passbys where the ROCS SPOTS reports indicated an “unknown” train type.

N/A = Not Applicable. Design criteria only apply to indoor spaces. There are no criteria for outdoor locations.

Table 12 provides a summary of all the individual train car consists that caused exceedances of vibration criterion at the residential measurement sites. The table lists the specific sensor locations at each site, the date and time, and the overall vibration level of the exceedances. The table also includes the train ID, the track the train was traveling on, and the train consist individual car numbers. Our understanding is that WMATA checked the maintenance records for each train car that

caused an exceedance on the day of testing as well as the days preceding and following the testing and did not find any maintenance logs pertaining to those cars.

Table 12: Summary of Train Consists That Exceeded Applicable Vibration Criteria

| Site # | Sensor | Location | Day | Time | Overall Vibration (VdB) | Track | Train ID | Consist |
|--------|-------------------------|-------------------------|------------------|----------|-------------------------|------------------|--|--|
| 2 | V5 | First Floor Dining Room | Wed, 16 Aug 2017 | 10:49 AM | 71 | Inbound Track 2 | 304 | 3012-3013.3165-3164.3062-3063 |
| | V5 | First Floor Dining Room | Wed, 16 Aug 2017 | 09:19 AM | 71 | Inbound Track 2 | 512 | 7352-7353.7011-7010.7390-7391.7389-7388 |
| | V4 | First Floor Living Room | Wed, 16 Aug 2017 | 10:13 AM | 71 | Inbound Track 2 | 301 | 3057-3056.2000-2001.2049-2048 |
| 10 | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:46 AM | 73 | Outbound Track 1 | 302 | 2014-2015.2062-2063.2008-2009 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 01:24 PM | 73 | Outbound Track 1 | 302 | 2014-2015.2062-2063.2008-2009 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 10:55 AM | 80 | Outbound Track 1 | 306 | 3067-3066.3222-3223.3019-3018 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 12:38 PM | 71 | Outbound Track 1 | 306 | 3067-3066.3222-3223.3019-3018 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:10 AM | 71 | Outbound Track 1 | 307 | 6147-6146.6127-6126.6181-6180 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 10:42 AM | 77 | Outbound Track 1 | 501 | 7076-7077.7383-7382.7112-7113.7099-7098 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 12:41 PM | 76 | Outbound Track 1 | 501 | 7076-7077.7383-7382.7112-7113.7099-7098 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:02 AM | 72 | Outbound Track 1 | 503 | 7172-7173.7225-7224.7184-7185.7103-7102 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:26 AM | 75 | Outbound Track 1 | 308 | 7218-7219.7371-7370.7170-7171.7381-7380 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:33 AM | 75 | Outbound Track 1 | 301 | 2016-2017.2029-2028.2064-2065 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 10:49 AM | 74 | Outbound Track 1 | 305 | unknown (WMATA ROCS SPOTS did not provide) |
| V2 | First Floor Living Room | Tue, 8 Aug 2017 | 12:22 PM | 71 | Outbound Track 1 | 305 | unknown (WMATA ROCS SPOTS did not provide) | |

| Site # | Sensor | Location | Day | Time | Overall Vibration (VdB) | Track | Train ID | Consist |
|--------|--------|-------------------------|------------------|----------|-------------------------|-----------------|----------|---|
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 01:57 PM | 72 | Inbound Track 2 | 304 | 2053-2052.6151-6150.2021-2020 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 11:29 AM | 72 | Inbound Track 2 | 501 | 7098-7099.7113-7112.7382-7383.7077-7076 |
| | V2 | First Floor Living Room | Tue, 8 Aug 2017 | 01:27 PM | 72 | Inbound Track 2 | 501 | 7098-7099.7113-7112.7382-7383.7077-7076 |
| 12 | V4 | First Floor Dining Room | Mon, 14 Aug 2017 | 03:51 PM | 71 | Inbound Track 2 | 504 | 6103-6102.6044-6045.6111-6110.6141-6140 |
| | V4 | First Floor Dining Room | Mon, 14 Aug 2017 | 05:34 PM | 71 | Inbound Track 2 | 504 | 6103-6102.6044-6045.6111-6110.6141-6140 |
| 13 | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 03:25 PM | 75 | Inbound Track 2 | 304 | 3033-3032.6020-6021.6028-6029 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 03:22 PM | 71 | Inbound Track 2 | 505 | 3092-3093.1060-1061.5126-5127 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 05:00 PM | 72 | Inbound Track 2 | 504 | 3092-3093.1060-1061.5126-5127 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 06:20 PM | 71 | Inbound Track 2 | 360 | 5016-5017.1226-1227.3034-3035 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 03:40 PM | 73 | Inbound Track 2 | 358 | 5135-5134.1214-1215.1137-1136.5058-5059 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 04:55 PM | 74 | Inbound Track 2 | 353 | 6027-6026.6107-6106.3278-3279 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 06:50 PM | 75 | Inbound Track 2 | 300 | 6078-6079.1118-1119.4038-4039.3068-3069 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 04:40 PM | 75 | Inbound Track 2 | 352 | 6134-6135.6172-6173.6053-6052 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 05:07 PM | 79 | Inbound Track 2 | 354 | 6169-6168.5032-5033.5114-5115 |
| | V3 | Second Floor Bedroom | Thu, 8 Jun 2017 | 04:10 PM | 72 | Inbound Track 2 | 501 | 7340-7341.7343-7342.7304-7305.7275-7274 |

8.2 Potential for Building Damage Assessment

Table 13 presents the average and highest PPV vibration data measured at each residential site in comparison to the building vibration damage threshold of 0.12 in/sec PPV that applies to fragile buildings. No structural survey of any residence was conducted as part of this study, so there is no basis for determining whether or not any of the buildings along the Green Line route are actually fragile enough to warrant application of the more conservative threshold.

As seen in Table 13, not a single PPV reading exceeded the conservative threshold for cosmetic damage to a fragile building. Therefore, the measurement data indicates that WMATA's operations are not causing any physical damage to any residences.

Table 13: PPV Vibration Data for Residential Survey Sites

| Potential for Building Vibration Damage Assessment | | | | | | | |
|--|-------------------------------------|----------------------|--------|---------------------|----------------------|--------|--------|
| Site # ¹ | > 0.12 in/sec PPV in any direction? | Average PPV (in/sec) | | | Highest PPV (in/sec) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| 1 | NO | 0.0012 | 0.0008 | 0.0005 | 0.0236 | 0.0062 | 0.0801 |
| 2 | NO | 0.0034 | 0.0034 | 0.0021 | 0.0340 | 0.0250 | 0.0120 |
| 3 | NO | 0.0012 | 0.0005 | 0.0004 | 0.0016 | 0.0071 | 0.0016 |
| 6 | NO | 0.0031 | 0.0032 | 0.0021 | 0.0050 | 0.0130 | 0.0070 |
| 7 | NO | 0.0006 | 0.0005 | 0.0003 ² | 0.0012 | 0.0118 | 0.0016 |
| 9 | NO | 0.0029 | 0.0029 | 0.0020 | 0.0030 | 0.0070 | 0.0040 |
| 10 | NO | 0.0031 | 0.0032 | 0.0027 | 0.0110 | 0.0230 | 0.0170 |
| 12 | NO | 0.0032 | 0.0030 | 0.0021 | 0.0180 | 0.0080 | 0.0270 |
| 13 | NO | 0.0005 | 0.0006 | 0.0003 ² | 0.0022 | 0.0115 | 0.0102 |
| 15 | NO | 0.0030 | 0.0029 | 0.0020 | 0.0080 | 0.0140 | 0.0070 |

¹ PPV vibration was only measured at residential measurement sites.

² Resolution of monitoring equipment is 0.00031 inches per second.

PPV = peak particle velocity, inches per second

8.3 WMATA Rail Roughness Measurement Results

Wilson Ihrig conducted rail roughness measurements at locations adjacent to residential measurement sites during the week of 7 August 2017. The intent of the measurements was to benchmark rail roughness when and where the passby measurements were performed. No rail grinding occurred between the time of the residential measurements and the time of the rail roughness measurements. The rail was last ground in March 2017 to remove corrugation according to [REDACTED] (email correspondence, 3 April 2017).

The RMS spectra for each site and all measurement traces are plotted below in Figure 25. Wavelength can be related to frequency relative to train speed by the formula, $\lambda = v / f$, where v is the train speed

and f is the frequency. For a given wavelength, as train speed increases, the vibration frequency increases. Table 14 shows the approximate wavelength ranges of interest for 15 miles per hour (mph) to 60 mph train speeds.

Table 14: Audible Ground-borne Noise – Approximate Wavelength Ranges of Interest

| Train Speed (mph) | Acoustic Frequency Range (Hz) | Rail Roughness Wavelength Range (mm) |
|-------------------|-------------------------------|--------------------------------------|
| 15 | 25 to 250 | 315 to 31.5 |
| 30 | 25 to 250 | 630 to 63 |
| 45 | 25 to 250 | 800 to 80 |
| 60 | 25 to 250 | 1,000 to 100 |

mph = miles per hour
Hz = Hertz (cycles per second)
mm = millimeter




Figure 25: WMATA Rail Roughness Data

For this study, the main interest was to see if one or a few of the locations had significantly rougher rails than the others. The roughness data collected from all measurement sites are consistent and group together within about 7 dB. The only strong peak seen in the spectra occurs in the 31.5 mm band, which peak is associated with grinding patterns left by the rail grinder and is typical. This wavelength would not result in audible ground-borne noise at train speeds observed during the measurements.

Reducing rail roughness could be explored further as a means to reduce wayside ground-borne noise. However, the rails were ground in March 2017, and significant roughness or rail corrugation would not likely have developed between then and the measurements. Even if it had, additional rail grinding alone would not be expected to reduce vibration if wheel roughness is the primary cause. Wheels get rough through normal wear and from braking events that can cause flat spots to form on the metal tread. The RMS roughness is the square root of the sum of the squares of wheel roughness and rail roughness, and both roughnesses must be reduced to achieve low vibration and noise.

8.4 7000 Series Fleet Compared to Other Fleets

8.4.1 Comparison of Single-Number Decibel Metrics

Table 15 compares the average ground-borne noise and vibration levels from the 7000 Series passbys to the average levels of all other types at each residence. As with Table 10 and Table 11, the summary is based on the indoor location at each residence with the highest levels.

While certain passbys of non-7000 Series vehicles generated levels comparable to 7000 Series vibration, on average the 7000 Series produced higher ground-borne noise and vibration levels than the older series vehicles did.

The ground-borne noise produced by earlier series trains was either not noticeable or barely noticeable, and ground-borne noise produced by the 7000 Series cars is typically noticeable. The difference in most residences surveyed is distinctly perceptible and would explain why residents have noticed and expressed concern about the passby ground-borne noise whereas they had not expressed concern prior to the introduction of the vehicles. Perceptibility does not equate with exceeding design criteria, and 7000 Series ground-borne noise levels are within the design criteria.

The average ground-borne noise levels from the 7000 Series vehicles relative to those from older series vehicles ranges from minus (-) 1 dBA to plus (+) 11 dBA. “Relative” in this sense means the level from the 7000 Series compared to the non-7000 Series, i.e., the difference. For example, if the 7000 Series level were 38 dBA and the non-7000 Series were 30 dBA, the relative level would be +8 dBA.

Vibration levels from 7000 Series vehicles are higher, on average, than for older series vehicles, but they are also still largely below generally accepted criteria for floor vibration in residences, except perhaps at Site 10, where the level was above 74VdB. The average overall vibration levels from the 7000 Series relative to the older series ranges from -3 VdB (meaning the 7000 Series produces less vibration) to +11 VdB (meaning the 7000 Series produces more vibration).

Table 15: Increase in Ground-Borne Noise and Vibration due to 7000 Series Vehicles

| Site # | Ground-Borne Noise (dBA) | | | Ground-Borne Vibration (VdB) | | |
|--------|--------------------------|------------------|------------------|------------------------------|------------------|------------------|
| | 7000 Series | All Others | Increase | 7000 Series | All Others | Increase |
| 1 | 38 | 30 | 8 | 63 | 57 | 6 |
| 2 | 29 | 23 | 6 | 70 | 59 | 11 |
| 3 | --- ¹ | --- ¹ | --- ¹ | --- ² | --- ² | --- ² |
| 4 | N/A | N/A | N/A | N/A | N/A | N/A |
| 5 | N/A | N/A | N/A | N/A | N/A | N/A |
| 6 | 30 | 26 | 4 | 62 | 62 | 0 |
| 7 | 32 | 24 | 8 | 67 | 59 | 8 |
| 8 | N/A | N/A | N/A | N/A | N/A | N/A |
| 9 | 24 | 22 | 2 | 61 | 55 | 6 |
| 10 | 32 | 25 | 7 | 74 | 66 | 8 |
| 11 | N/A | N/A | N/A | N/A | N/A | N/A |
| 12 | 29 | 18 | 11 | 60 | 63 | -3 |
| 13 | 31 | 32 | -1 | 66 | 68 | -2 |
| 14 | N/A | N/A | N/A | N/A | N/A | N/A |
| 15 | 30 | 25 | 5 | 64 | 61 | 3 |
| 16 | N/A | N/A | N/A | N/A | N/A | N/A |


¹ Ground-borne train noise was not discernable at Site 3.

² Vibration at Site 3 was dominated by non-train sources.

N/A = Not Applicable. Increase was not analyzed for outdoor sites.

8.4.2 Comparison of 1/3-Octave Band Spectra

Figure 26 through Figure 30 compare the average 1/3-octave band vibration spectra for the 7000 Series with each of the other series that were in operation at the time of the measurements. Each chart shows the respective vehicle comparison for all basement vibration locations at all sites. For example, Figure 26 presents the average passby data for the 7000 Series relative to the 6000 Series (7000 Series minus the 6000 Series) for each residential site. The charts show the relative vibration levels in VdB. Data above the 0 VdB line indicate that the 7000 Series vibration data is higher than the 6000 Series vibration. For all sites, the 7000 Series levels were higher than the 6000 Series levels by a significant amount, roughly 10 to 12 VdB, between 31.5 Hz and 500 Hz, inclusive, which are frequencies in the audible frequency range.



- Site 1 - T1 - Egg, 34-42 mph, S/D 59 ft, T/R 45ft
- Site 2 - T2 - Egg, 24-40mph, S/D 62 ft, T/R 45ft
- ◇—◇ Site 6 - T1- Egg, 30-55mph, S/D 127ft, T/R 65ft
- △—△ Site 7 - T1 - Egg, 29-61mph, S/D 77ft, T/R 65ft
- △····△ Site 9 - T2 - (Single 7K train), Egg, 23 to 73mph, S/D 208ft, T/R 75ft
- ×---× Site 10 - T1 - Egg, 33-63 mph, S/D 86 ft, T/R 75 ft
- ◀—▶ Site 12 - T2 - DF, 39-69mph, S/D 208 ft, T/R 95 ft
- ▶····▶ Site 13 - T2 - DF, 43-74mph, S/D 131ft, T/R 97-98ft
- +····+ Site 15 - T1 - DF, 31-59 mph, S/D 106ft, T/R 42ft
- L Avg. - 7000 - 6000 differences

Figure 26: 7000 Series Minus 6000 Series - Basement Positions




Figure 27: 7000 Series Minus 5000 Series- Basement Positions




Figure 28: 7000 Series Minus 3000 Series - Basement Positions





Figure 29: 7000 Series Minus 2000 Series - Basement Positions



- Site 1 - T1 - w/out 4000 Series - Egg, 34-42 mph, S/D 59 ft, T/R 45ft
- ◇.....◇ Site 2 - T2 - w/out 4000 Series - Egg, 24-40mph, S/D 62 ft, T/R 45ft
- △---△ Site 6 - T1 - w/out 4000 Series - Egg, 30-55mph, S/D 127ft, T/R 65ft
- ×.....× Site 7 - T1 - w/ 4000 Series -Egg, 29-61mph, S/D 77ft, T/R 65ft
- ×---× Site 7 - T1 - w/out 4000 Series - Egg, 29-61mph, S/D 77ft, T/R 65ft
- ◀---▶ Site 9 - T2 - w/out 4000 Series - (Single 7K train), Egg, 23 to 73mph, S/D 208ft
- ▶---▶ Site 10 - T1 - 6000/2000 Series - Egg, 33-63 mph, S/D 86 ft, T/R 75 ft
- +.....+ Site 13 - T2 - w/out 4000 Series - DF, 43-74mph, S/D 131ft, T/R 97-98ft
- +.....+ Site 15 - T1 - 3000/2000 Series - DF, 31-59 mph, S/D 106ft, T/R 42ft
- L Avg. 7000 - Mixed Legacy Differences

Figure 30: 7000 Series Minus Mixed Series - Basement Positions

9 Vehicle Characteristics

Table 16 summarizes the main design features of a vehicle that may affect ground vibration generation.⁵ Overall, the main differences between the vehicles appear to be related to their primary suspension systems. The 7000 Series and earlier 2000/3000/4000 Series vehicles have elastomer chevron suspensions with nominal vertical stiffnesses ranging from 9,750 to 10,360 pounds per inch (lbs/in) for the 2000/3000/4000 Series vehicles, and 7,530 (AW0) to 8,083 (AW3) lbs/in for the 7000 Series vehicles. The primary suspensions of the original 1000 Series vehicles and the 5000/6000 Series vehicles are elastomer journal bushing suspensions with nominal stiffness of 60,000 and 74,300 lbs/in, respectively.

9.1 Primary Resonance Frequency

The primary resonance frequency of a vehicle is determined by the mass of the truck frame and other suspended components acting against the combined stiffness of the primary suspension and secondary suspension. The secondary suspension stiffnesses are very similar for all vehicle types. Thus, the major suspension component affecting differences between the primary resonance frequencies of various vehicle series is the primary suspension stiffness. The solid elastomer journal bushing of the 1000 Series vehicle may well be stiff enough to produce a resonance frequency above 20 Hz.⁶ The primary resonance frequency of the chevron suspension trucks at transit systems are typically 6.3 to 10 Hz. (The static stiffnesses shown in Table 16 must be multiplied by a factor of at least 1.5 to obtain the dynamic stiffnesses when calculating resonance frequencies for elastomer springs.⁷)

One may expect higher levels of ground vibration for elastomer journal bushing suspensions than for chevron suspensions for the 1/3-octave bands between 12.5 Hz and 31.5 Hz. This appears to be the case as shown in Figure 26 and Figure 27 for the 6000 and 5000 Series vehicles, respectively.

The vibration produced by the 7000 Series vehicles would be expected to be greater than that produced by the 5000/6000 Series vehicles at about 8 Hz. This is not apparent in the data shown in Figure 26 and Figure 27, though this may be due to the background vibration dominating the ground vibration spectrum at these frequencies.

The ground vibration and ground-borne noise levels for the 7000 Series vehicles are consistently much higher than those produced by the 4000/5000/6000 Series, regardless of suspension type. The foregoing suggests that the cause is something other than differences between the primary suspension.

⁵ Email correspondence from [REDACTED], 14 July 2017.

⁶ Based on Wilson Ihrig experience with the Atchison Casting trucks of the Rohr vehicles used at BART and WMATA.

⁷ The 1.5 factor is referred to as the “dynamic-to-static stiffness ratio”. See, for example, Use of Rubber in Engineering, P. W. Allen, P. B. Lindley, and A. R. Payne editors, Maclaren & Sons, Ltd., London, 1967.

9.2 Un-Sprung Mass and Track Resonance (P2)

The principal features that affect ground vibration loading at frequencies in the 31.5 Hz and higher bands are the un-sprung masses of the wheel sets consisting of the wheels, axles, brake discs, bearings, and gear units, and to a lesser extent the motors. The un-sprung mass combined with the rail and rail support modulus⁸ determine the track resonance frequency (P2 resonance), which may range from 50 Hz to well above 100 Hz, depending on rail support stiffness. The resonance frequency is usually best represented by the parallel impedance model of wheel/rail interaction.^{9,10} Additional factors include the bending resonance of the axle, which should be about 100 Hz or higher for the hollow axle, but is reduced by the mass of the gear unit hanging on the axle. All of the vehicles apparently have gear units that are supported directly by the axles, without flexible coupling between the gear unit drive gear and axle. (This differs from many light rail vehicle configurations.) As listed in Table 16, the un-sprung weight of the 7000 Series vehicle is very similar to that of the 5000 and 6000 Series vehicles. All of the vehicles appear to have similar wheel set configurations, and thus should produce similar levels of ground-borne noise and vibration above 31.5 Hz.

⁸ The rail support dynamic modulus is the direct fixation fastener stiffness (about 80,000 lbs/in for the high-compliance egg) divided by the fastener pitch (typically 30 in), and is about 2,700 lb/in/in.

⁹ Transportation Cooperative Research Program (TCRP) Report 23.

¹⁰ TCRP Report 155, Chapter 9.

Table 16: Vehicle Design Features

| Feature | Unit of Measure | Car Series | | | |
|---|-----------------|---------------------------|---------------------|--|------------------------|
| | | 1000 | 2000/3000/4000 | 5000/6000 | 7000 |
| Manufacturer | --- | Rohr | Breda | CAF/Alstom | Kawasaki |
| A-Car Weight | lbs | 77,500 | 77,100 - 79,050 | 76,465 - 78,580 | 84,289 |
| B-Car Weight | lbs | ~80,000 | 77,650 | 77,335 - 79,340 | 84,289 |
| Truck Manufacturer | --- | Atchison | Breda | Bradken (Atchison) | Kawasaki |
| Truck Weight | lbs | 12,838 | 13,773 | 12,838 - 13,231 | 13,961 |
| Primary Suspension Type | --- | Elastomer Journal Bushing | Chevron (Lord/Saga) | Elastomer Journal Bushing | Chevron (Tokai Rubber) |
| Primary Suspension Vertical Stiffness (Static) | lbs/in | 60,000 | 9,750 - 10,360 | 74,300 | 7,530 - 8,083 |
| Primary Lateral Stiffness (Static) | lbs/in | 19,000 | 19,555 | 62,300 | 14,430 |
| Primary Longitudinal | lbs/in | 106,000 | 139,700 | 115,000 | 138,054 |
| Wheel Diameter | in | 28 – 25 | 28 – 25 | 28 - 25 | 28 - 25 |
| Flange Angle | degrees | 70 | 70 | 70 | 63 |
| Axle | --- | Hollow/Solid | Hollow | Hollow | Hollow |
| Wheels¹ | --- | Solid | Solid | Solid | Solid |
| Wheelset Weight | lbs | No data | No data | 2,077 | 2,259 |
| Motor/Gear Unit Weight | lbs | No data | No data | 1,452 (5000 Series) 2,234 (6000 Series) | 1,102/661 |
| Total Un-sprung Weight | lbs | No data | No data | 3,529 (5000 Series) 4,311 (6000 Series) | 4,022 |

¹ Assumed

9.3 Wheel Condition

Table 11 shows that non-7000 Series vehicles generated vibration that exceeded the design criterion of 70 VdB in four of ten houses tested. In these houses, the number of passbys that exceeded the criterion ranged from 8% to 29%.¹¹ Table 11 also shows that 7000 Series vehicles exceeded the design criterion in three of ten houses and that 13% to 67% of the passbys did so. The particular trains that generated the highest vibration very likely had wheels with wheel flats.

Wheel surface condition degrades with wear, and infrequent truing may result in increased ground vibration loading. Rough wheels with flats that may or may not be visible may produce vibration levels that are 7 to 10 decibels greater than newly trued wheels. Wheel flats would manifest themselves in wayside noise as well as ground vibration.

Wilson Ihrig consultants aurally observed wayside and car interior noise produced by the 7000 Series vehicles and 6000 Series vehicles on the Green Line and on the Red Line. The 7000 Series produced greater rumbling noise than did the 6000 Series vehicles. This was observed at the Mt. Vernon Sq. Station, the West Hyattsville Station, Gallery Place, and Metro Center platforms. Low frequency rumbling noise is much more apparent inside the 7000 Series vehicle compared to the 6000 Series vehicles that were observed. Additionally, hunting of the 7000 Series vehicle was more apparent than with the 6000 Series vehicle. The nature of the noise is consistent with excessive wheel/rail roughness. Moreover, the rumbling noise appeared to subside on the curves, and also during braking. The pitch of the rumbling noise did not appear to change significantly with train speed, but remain focused at the track resonance frequency.¹²

If any of the vehicles have experienced emergency braking and or if the 7000 Series vehicles were subjected to braking tests as part of their acceptance, they may have wheel flats that may be a factor (possibly the only factor) in wayside ground-borne noise and vibration. However, the wheels of all trains and those of the 7000 Series vehicles have evidently been trued. Wilson Ihrig consultants listened carefully to analog data recorded in these homes but were unable to determine if any of the trains had wheel flats. This is not to say that the wheels did not have flats; they might be obscured by reverberation of vibration in the ground

As shown in Figure 26 through Figure 29, the ground vibration at frequencies above 30 Hz is much higher for the 7000 Series vehicles compared to the 2000/3000/5000/6000 Series vehicles. This suggests that other factors may be influencing the ground vibration loading from the 7000 Series besides wheel flats and roughness. Given that the truck and suspension characteristics of the 7000 Series are similar to the 2000/3000/4000 Series vehicles, the most likely difference is the wheel profile.

Wheel profiles may affect ground vibration, especially at curves. Ground vibration levels at curves may be three to five decibels higher than at tangent track. Most of the measurements in this report

¹¹ These percentages are based on the number of passbys, not the number of train consists. A given consist may have passed the measurement location more than once during the measurement period.

¹² Observations by the author, James Nelson, P.E., on 9 January 2018

were conducted at tangent track sections, so curving performance should not be a factor.¹³ However, Table 16 indicates that the flange angle of the 7000 Series vehicles that have been delivered is 63-degrees, which differs from the 70-degree flange angle of the remaining fleet. The possibility exists that the taper near the throat may be greater with the 7000 Series vehicles than with the earlier vehicles, with the result that the contact between the wheel and rail is not entirely on the top running surface of the rail in tangent track, but may be shifted toward the gauge side of the rail head. Visual observation from the platform of the rail head at Metro Center and Gallery Place indicate wear and possibly incipient corrugation of the top of the rail between the wear band and gauge corner. The tracks in this area are tangent, so that wear in this area would not be expected unless there is a high degree of conformal contact across the rail head, possibly involving the throat.

Photographs shown in Figure 31 and Figure 32 of freshly ground rail suggest that the profile of the ground rail is not rounded across the rail head with a uniform ball radius, but includes a top running band and a band between the top running band and gauge corner. Wheels trued to the 63-degree profile and running on the top running band and on the area between the top running band may experience excess roughness at this dividing line. Lateral variation of the position of the dividing line between these surfaces will contribute to rail roughness, regardless of smoothness of the wheel and rail. A possibility exists that the wheels are running entirely on the rail head between the running band and gauge corner, leading to excessive hunting as well as roughness.

The 7000 Series vehicles up to Car Number 7464 were delivered with a 63-degree flange angle, and cars delivered after Car Number 7464 will be delivered with a 70-degree flange angle. Further, the flange angle wears to 68 to 69-degrees after a few months of service. In 2013, WMATA changed the flange angle from 63-degrees to 70-degrees to reduce the propensity of flange climb, reduce gauge corner stress, and increase life. When cars are brought in for wheel truing, the wheels are profiled to the new flange angle of 70-degrees. The majority of the WMATA 7000 Series cars have been trued at least once and now conform to 70-degrees.¹⁴ At this point, the proportion of the 7000 Series vehicles that remain to be trued to the 70-degree profile has not been determined for this report. A possibility exists that the ground-borne noise and wayside rumbling noise of the 7000 Series vehicles will decrease to that produced by the 6000 Series vehicles after the 7000 Series vehicle wheels have been trued to the 70-degree profile.

The longitudinal stiffness of the 7000 Series chevron suspension is moderately higher than that of the 1000 Series and 5000/6000 Series vehicles. Self-steering of the wheel sets in curves may be less easily accommodated by the chevron suspensions of the 7000 Series than the journal bushing suspensions of the 5000/6000 Series vehicles, thus inducing greater wear rates in the 7000 Series vehicles. However, the higher vibration levels for the 7000 Series vehicles relative to those of the 2000/3000/4000 Series vehicles, also with chevron suspensions, suggests that this is not a factor.

¹³ Good curving performance involves minimal lateral slip, minimal hunting, and good ride quality. In curves, the vehicle wheels may steer around the curve with little or no contact between the wheel flanges and the rails. However, it may also be the case that contact occurs to varying degrees. This induces additional vibration.

¹⁴ Memorandum from [REDACTED], P.E. to Andrew Off, 5 January 2018



Figure 31 Photograph of left ground rail (guage corner at bottom) ([REDACTED] "WMATA Post-Grind Surface Roughness Report", Loram Maintenance of Way, December 2013, Figure 1 of Page 2)



Figure 32 Photograph of right ground rail (guage corner at bottom) ([REDACTED] "WMATA Post-Grind Surface Roughness Report", Loram Maintenance of Way, December 2013, Figure 2 of Page 2)

If wheel profiles, and wheel gauges of the 7000 Series vehicles and 6000 Series vehicles are all essentially identical, one may conclude that the 7000 Series vehicles are not steering properly on tangent track, and involve lateral slip. Such may produce high levels of ground vibration and rumbling noise. This is highly unlikely, but must be considered.

9.4 Areas for Exploration

Vehicles that Exceed the Vibration Design Criterion

- Review maintenance records for all vehicles identified as being part of a consist that generated vibration levels greater than the design criterion. If none have been trued, inspect the wheels of those vehicles for flats, spalls, and/or unusual wear patterns.
- Alternatively, arrange for more ground-borne noise and vibration measurements to be made with the intent of inspecting very quickly the wheels of trains that generate vibration levels that exceed the criterion. In addition to making measurements in the homes, measurements could be made in the tunnel either on the rails or nearby on the safety walk. These in-tunnel measurements would facilitate identifying which wheel(s) are contributing to the high vibration levels.
- Once vehicles that exceed the vibration criterion are identified, true the wheels of those vehicles and then re-test in the tunnel and, possibly, in the homes.

The 7000 Series

The measurement data indicate that a fundamental difference exists between the 7000 Series vehicles and the earlier series vehicles. Table 16 does not indicate any apparent design features that would contribute to higher vibration levels for the 7000 Series vehicles except perhaps differences in the flange angle. The acceptance test report indicates no significant difference between ground vibration produced by the 7000 Series vehicle and the baseline vehicle. The findings in this report indicate that the cause of higher levels of ground vibration produced by the 7000 Series vehicle relative to that produced by the earlier series vehicles is related to wheel/rail roughness with wavelengths of 100mm or longer, lack of truing, and tread profile. The following is suggested:

- Review the wheel and rail profiles and compare the profiles of the 7000 Series vehicles and 6000 Series vehicles with the rail grinding profiles currently used on the Green Line and Red Line.
- Review maintenance records for the 7000 Series vehicles and compare wheel tread profiles and wheel gauge with the 6000 Series and earlier vehicles. Other maintenance practices may have some relevance. This should include a visit to the maintenance shop.
- Identify differences in shop practices that may be relevant to ground vibration. These include truing intervals, type of truing machine (lathe or milling type), and profiles.
- Investigate differences in wheel profiles and wheel gauges of the 7000 Series vehicles relative to those of the earlier series vehicles.

- True the wheels of a test train and conduct a controlled survey of the test train with trued wheels and a test train with un-trued wheels at two of the outdoor-only ground surface measurement locations used in this study. If significant reductions are obtained with the trued wheels, consider repeating the measurements in one or two basements.
- Measure wayside noise for the trued and un-trued wheels to correlate wayside noise with ground vibration.
- Visually inspect unloaded trucks of 7000 Series vehicles and earlier design vehicles at the maintenance shops to possibly identify differences that may contribute to wayside ground vibration.
- Measure wheel surface roughness.

Finally, a test procedure has been developed for measuring the in-situ mechanical impedance of transit vehicles in track.¹⁵ The test was conducted at BART on the Rohr vehicles, and at the Transportation Test Center in Pueblo, Colorado. The test involves instrumenting the rail with strain gauges and parking the vehicle on the instrumented section of rail. Dynamic excitation of the rail and simultaneously analyzing the response velocity of the wheel and reaction forces acting on the rail, as obtained with the strain gauges, yields the mechanical impedance of the vehicle as seen by the rail. A high mechanical impedance, possibly due to mechanical shorting of the primary suspension, would produce high ground vibration loading. This test is not yet recommended, but remains as a possible tool in the event that a cause is not found by other means.

¹⁵ Department of Transportation/Transportation Systems Center (DOT/TSC) Ground-Borne Noise and Vibration Study Memorandum (1984).

Appendix A Instrumentation and Calibration Documentation

Appendix B Site-Specific Field Studies



WILSON IHRIG
ACOUSTICS, NOISE & VIBRATION

CALIFORNIA
WASHINGTON
NEW YORK

Appendix A Instrumentation and Calibration Documentation

Table of Contents

| | | |
|------------|--|---|
| Appendix A | Instrumentation and Calibration Documentation..... | 1 |
| A.1 | Attended Vibration and Noise | 3 |
| A.2 | Peak Particle Velocity | 4 |
| A.3 | Overnight Vibration Logging..... | 4 |
| A.4 | Rail Roughness..... | 5 |

A.1 Attended Vibration and Noise

All vibration was measured with high-sensitivity Endevco accelerometers. The accelerometers were adhered to the floor with wax. Where carpet was present, the accelerometers were mounted on a carpet spike, which is a heavy steel plate with three slender spikes to poke through to the floor underneath. Outdoor accelerometers were adhered to sidewalk or curb with wax. At one location, the accelerometer was mounted on a ground spike driven into the soil.

The analog acceleration signals were conditioned and amplified with Wilson Ihrig (WI) 112L preamplifiers. The outputs of the charge amplifiers were recorded on 4-channel Rion data recorders for subsequent data processing.

All noise measurements were made with Type 1 precision microphones and sound level meters output to a Sony PCM-D50 or Rion multi-channel data recorders for subsequent data processing. The sound level meter microphones were fitted with windscreens and mounted on tripods.

A complete list of all instrumentation used for the attended vibration and noise measurements, including model and serial number, are included in the following table.

| Type/Model | Quantity | Serial Number(s) | Description |
|-------------------------|----------|--------------------------------|---|
| Endevco 7701A-1000 | 2 | 11013, 11035 | Accelerometer, 1000 pC/g sensitivity |
| Endevco 7703A-1000 | 2 | 11219, 11220 | Accelerometer, 1000 pC/g sensitivity |
| Endevco 7707-1000 | 4 | AV22, BB64, BA11, BB92 | Accelerometer, 1000 pC/g sensitivity |
| WI Type 112L | 8 | 20, 21, 22, 26, 28, 36, 37, 39 | Low-noise Charge Amplifier, 1V/1000 pC |
| Bruel & Kjaer Type 4155 | 1 | 1082896 | Microphone, ½" diameter |
| Bruel & Kjaer Type 2230 | 1 | 1428412 | Sound Level Meter |
| Norsonic N-1225 | 1 | 96046 | Microphone, ½" diameter |
| Norsonic N-1209 | 1 | 12328 | Preamplifier, goes with N-1225 mic |
| Norsonic Nor140 | 1 | 1403173 | Sound Level Meter/Vibration Logger |
| Rion DA-21 | 1 | 00150211 | Digital Recorder, 4-channel |
| Rion DA-20 | 1 | 34321679 | Digital Recorder, 4-channel |
| Sony PCM-D50 | 1 | 1039262 | Digital Recorder, 2-channel |
| Kistler 808K | 1 | 849 | Reference Accelerometer for Vibration Calibration |
| Bruel & Kjaer 4291 | 1 | 398328 | Lab Vibration Shaker/Calibrator |
| PCB 394C06 | 1 | 3378 | Field Vibration Shaker/Calibrator |
| Bruel & Kjaer Type 4220 | 1 | 159016 | Reference Pistonphone for Acoustic Calibration |
| Bruel & Kjaer Type 4230 | 1 | 992709 | Field Acoustic Calibrator |

The vibration measuring systems are checked prior to field use and calibrated with Bruel & Kjaer Type 4291 and PCB 394C06 vibration calibrators, which are cross-calibrated with a reference accelerometer used solely for this purpose. The reference accelerometer is a Kistler Type 808K, SN# 849, which was calibrated by Odin Metrology on August 1, 2017. This calibration is traceable to NIST Test No. 6831283402-13 BK256.

Noise measuring systems were calibrated before and after testing with a Bruel & Kjaer Type 4230 acoustic calibrator, SN# 992709, which is cross-calibrated with a reference pistonphone traceable to NIST. The reference pistonphone was Bruel & Kjaer pistonphone type 4220 SN# 159016, last calibrated by Odin Metrology on August 2, 2017. The NIST Test No. is TN-683/286992-15.

A.2 Peak Particle Velocity

Instrumentation used for the peak particle velocity (PPV) monitoring is included in the following table.

| Type/Model | Quantity | Serial Number(s) | Description |
|-------------------------|----------|------------------|--------------------------|
| InstanTel Geophone | 1 | SE12863 | ISEE Triaxial Geophone |
| InstanTel MiniMate Pro4 | 1 | MP12883 | Vibration Monitor/Logger |

The geophone and monitor are sent to InstanTel for annual calibration; both were last calibrated on April 12, 2017.

A.3 Overnight Vibration Logging

Overnight vibration was measured with the same high-sensitivity Endevco type accelerometers. The accelerometers were adhered to the floor with wax. The analog acceleration signals were conditioned and amplified with a Wilson Ihrig (WI) 112L preamplifier. The output of the charge amplifier was recorded using Norsonic Nor140 set to log 1/3 octave band root mean square (RMS) acceleration levels at 1-second intervals.

| Type/Model | Quantity | Serial Number(s) | Description |
|-------------------|----------|------------------|--|
| Endevco 7707-1000 | 1 | BA11 | Accelerometer, 1000 pC/g sensitivity |
| WI Type 112L | 1 | 21 | Low-noise Charge Amplifier, 1V/1000 pC |
| Norsonic Nor140 | 2 | 1403200 | Sound Level Meter/Vibration Logger |

The overnight vibration measuring system was calibrated with the same calibration equipment and method as the attended vibration system.

A.4 Rail Roughness

Rail roughness was measured with a Corrugation Analysis Trolley (CAT). The instrumentation used is included in the following table.

| Type/Model | Quantity | Serial Number(s) | Description |
|--------------------------|-----------------|-------------------------|------------------------------|
| RailMeasurement CAT 3 | 1 | 641002 | Corrugation Analysis Trolley |



WILSON IHRIG
ACOUSTICS, NOISE & VIBRATION

CALIFORNIA
WASHINGTON
NEW YORK

Appendix B Site-Specific Field Studies

Table of Contents

| | | |
|------------|---|-----|
| Appendix B | Site-Specific Field Studies | 1 |
| B.1 | Site 1 – 1300 block of Park Road NW (Residence) | 7 |
| B.1.1 | Building and Tunnel Notes | 7 |
| B.1.2 | Measurement Positions | 7 |
| B.1.3 | GBNV Assessment Summary | 10 |
| B.1.4 | PPV Results | 10 |
| B.1.5 | Passby Vibration Spectra and Overall Levels | 11 |
| B.1.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 35 |
| B.2 | Site 2 – 3600 block of New Hampshire Avenue NW (Residence) | 43 |
| B.2.1 | Building and Tunnel Notes | 43 |
| B.2.2 | Measurement Positions | 43 |
| B.2.3 | GBNV Assessment Summary | 46 |
| B.2.4 | PPV Results | 47 |
| B.2.5 | Passby Vibration Spectra and Overall Levels | 47 |
| B.2.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 72 |
| B.3 | Site 3 – 700 block of Princeton Place (Residence) | 80 |
| B.3.1 | Building and Tunnel Notes | 80 |
| B.3.2 | Measurement Positions | 80 |
| B.3.3 | GBNV Assessment Summary | 83 |
| B.3.4 | PPV Results | 83 |
| B.3.5 | Statistical Vibration Spectra | 84 |
| B.4 | Site 4 – Rock Creek Church Road NW & 9th Street NW (Outdoor Only) | 114 |
| B.4.1 | Tunnel Notes | 114 |
| B.4.2 | Measurement Positions | 114 |
| B.4.3 | Overall Level vs Distance Plot | 116 |
| B.5 | Site 5 – New Hampshire Avenue & Randolph Street NW (Outdoor Only) | 117 |
| B.5.1 | Tunnel Notes | 117 |
| B.5.2 | Measurement Positions | 117 |
| B.5.3 | Overall Level vs Distance Plot | 119 |
| B.6 | Site 6 – 4100 block of New Hampshire Avenue NW (Residence) | 120 |
| B.6.1 | Building and Tunnel Notes | 120 |
| B.6.2 | Measurement Positions | 120 |
| B.6.3 | GBNV Assessment Summary | 123 |

| | | |
|--------|--|-----|
| B.6.4 | PPV Results..... | 123 |
| B.6.5 | Passby Vibration Spectra and Overall Levels | 124 |
| B.6.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 140 |
| B.7 | Site 7 – 4300 block New Hampshire Avenue NW (Residence) | 148 |
| B.7.1 | Building and Tunnel Notes..... | 148 |
| B.7.2 | Measurement Positions..... | 148 |
| B.7.3 | GBNV Assessment Summary..... | 151 |
| B.7.4 | PPV Results..... | 151 |
| B.7.5 | Passby Vibration Spectra and Overall Levels | 152 |
| B.7.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 168 |
| B.8 | Site 8 – New Hampshire Avenue NW & Webster Street NW (Outdoor Only)..... | 176 |
| B.8.1 | Tunnel Notes | 176 |
| B.8.2 | Measurement Positions..... | 176 |
| B.8.3 | Overall Level vs Distance Plot | 178 |
| B.9 | Site 9 – 4400 block of 5th Street NW (Residence) | 179 |
| B.9.1 | Building and Tunnel Notes..... | 179 |
| B.9.2 | Measurement Positions..... | 179 |
| B.9.3 | GBNV Assessment Summary..... | 182 |
| B.9.4 | PPV Results..... | 183 |
| B.9.5 | Passby Vibration Spectra and Overall Levels | 184 |
| B.9.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 208 |
| B.10 | Site 10 – 4400 block of New Hampshire Avenue NW (Residence) | 216 |
| B.10.1 | Building and Tunnel Notes..... | 216 |
| B.10.2 | Measurement Positions..... | 216 |
| B.10.3 | GBNV Assessment Summary..... | 219 |
| B.10.4 | PPV Results..... | 220 |
| B.10.5 | Passby Vibration Spectra and Overall Levels | 221 |
| B.10.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 237 |
| B.11 | Site 11 – New Hampshire Avenue NW & Buchanan Street NW (Outdoor Only)..... | 241 |
| B.11.1 | Tunnel Notes | 241 |
| B.11.2 | Measurement Positions..... | 241 |
| B.11.3 | Overall Level vs Distance Plot | 243 |
| B.12 | Site 12 – 4600 block of 4th Street NW (Residence) | 244 |
| B.12.1 | Building and Tunnel Notes..... | 244 |

| | | |
|--------|---|-----|
| B.12.2 | Measurement Positions..... | 244 |
| B.12.3 | GBNV Assessment Summary..... | 247 |
| B.12.4 | PPV Results..... | 247 |
| B.12.5 | Passby Vibration Spectra and Overall Levels | 248 |
| B.12.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 268 |
| B.13 | Site 13 – 4600 block of New Hampshire Avenue NW (Residence) | 272 |
| B.13.1 | Building and Tunnel Notes..... | 272 |
| B.13.2 | Measurement Positions..... | 272 |
| B.13.3 | GBNV Assessment Summary..... | 275 |
| B.13.4 | PPV Results..... | 276 |
| B.13.5 | Passby Vibration Spectra and Overall Levels | 277 |
| B.13.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 293 |
| B.14 | Site 14 – Gallatin Street NE & 8 th Street NE (Outdoor Only) | 301 |
| B.14.1 | Tunnel Notes..... | 301 |
| B.14.2 | Measurement Positions..... | 301 |
| B.14.3 | Overall Level vs Distance Plot | 303 |
| B.15 | Site 15 – 800 block of Gallatin Street NE (Residence)..... | 304 |
| B.15.1 | Building and Tunnel Notes..... | 304 |
| B.15.2 | Measurement Positions..... | 304 |
| B.15.3 | GBNV Assessment Summary..... | 307 |
| B.15.4 | PPV Results..... | 307 |
| B.15.5 | Passby Vibration Spectra and Overall Levels | 308 |
| B.15.6 | Passby Ground-borne Noise Spectra and A-weighted Levels | 324 |
| B.16 | Site 16 – Gallatin Street NE (Outdoor Only) | 334 |
| B.16.1 | Tunnel Notes..... | 334 |
| B.16.2 | Measurement Positions..... | 334 |
| B.16.3 | Overall Level vs Distance Plot | 336 |

“Road Map” for Reviewing the Site-Specific Field Studies

The following provides a brief description about how the field studies are organized.

Residential Sites (1, 2, 3, 6, 7, 9, 10, 12, 13, 15)

| Item (in order of presentation) | Description |
|---|--|
| Building and Tunnel Notes | Building type, track type, observations |
| Distance Table | List of sensor positions and distances to tunnels |
| Aerial map | Shows track centerlines, residential buildings, and exterior sensor position points on aerial map |
| Cross-section sketch | Sketch depicting multi-story sensor locations and proximity to tunnels |
| GBNV Assessment Table | Lists the vehicle types analyzed for each site and whether the average of multiple trains or highest individual train exceed ground-borne noise and vibration (GBNV) assessment thresholds |
| PPV Results Table | Presents the average and range of peak particle velocity to address whether there is potential for building vibration damage |
| Passby Vibration Spectra and Overall Levels | 1/3 octave band velocity spectra plot with overall (OA) level along left-hand axis. Four plots for each sensor: <ol style="list-style-type: none"> 1. Average by Vehicle Type, Track 1 2. Average by Vehicle Type, Track 2 3. Highest Individual Train by Vehicle Type, Track 1 4. Highest Individual Train by Vehicle Type, Track |
| Passby Ground-borne Noise Spectra and A-weighted Levels | 1/3 octave band noise plot with A-weighted (AW) level along right-hand axis. Four plots for each sensor: <ol style="list-style-type: none"> 1. Average by Vehicle Type, Track 1 2. Average by Vehicle Type, Track 2 3. Highest Individual Train by Vehicle Type, Track 1 4. Highest Individual Train by Vehicle Type, Track 2 |

Outdoor Only Sites (4, 5, 8, 11, 14, 16)

| Item (in order of presentation) | Description |
|--|---|
| Tunnel Notes | Site location, track type, observations |
| Distance Table | List of sensor positions and distances to tunnels |
| Aerial map | Shows track centerlines and exterior sensor position points on aerial map |
| Overall Level vs Distance Plot | Average overall vibration levels for all sensor positions as a function of horizontal plan distance from track centerline. The data are sorted by 7000 Series and Non-7000 series vehicles on each track. |

B.1 Site 1 – 1300 block of Park Road NW (Residence)

B.1.1 Building and Tunnel Notes

| | |
|---------------------|--|
| Location: | Inbound track 2 side at 143+75 |
| Building Notes: | Residential townhouse, 4 floors comprised of partial underground basement plus 3 upper floors, exterior wall of brick construction |
| Tunnel Structure: | Earth Tunnel |
| Track Type: | transition from stiff DF to Egg Fasteners |
| T/R Depth: | 73 to 74 feet (track 2) / 45 feet (track 1) |
| Train Speed: | 34 to 42 mph |
| Measurement Period: | Monday, 5 June 2017, 16:43 to 20:45 |
| Field Observations: | Homeowners present during the measurements, children playing inside the home on the first and second floors. |

B.1.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|----------------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| Triaxial Geo. | Basement Bedroom | 31 | 74 | 80 | 38 | 45 | 59 |
| V1 | | | | | | | |
| N1 | | | | | | | |
| N2 | | | | | | | |
| V2 | 1 st Floor Livingroom | 25 | 74 | 78 | 32 | 45 | 55 |
| V3 | 2 nd Floor Playroom | | | | | | |
| V4 | Outside House | 28 | 73 | 78 | 21 | 45 | 50 |
| V5 | Across Street | 26 | 74 | 78 | 19 | 45 | 49 |
| V6 | Across Street | | | | | | |

Notes:

- Triaxial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth




Figure 1: Aerial Map of 1300 block of Park Road Residence and Exterior Measurement Locations




Figure 2: Cross-section Sketch (not to scale) of 1300 block of Park Road Indoor and Exterior Measurement Locations

B.1.3 GBNV Assessment Summary

| SITE 1 | 1300 block of PARK ROAD NW – ATTENDED PASSBY MEASUREMENT GBNV ASSEMENT | | |
|--------|--|--------------------|--------------|
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy with 4000 Series (Single Passby) | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 6000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 3000 Series - Individual Train with Highest Overall Vibration | NO | |
| | Mixed Legacy - Individual Train with Highest Overall Vibration | NO | |
| | | | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series (Average of Multiple Passbys) | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 3000 Series - Individual Train with Highest A-weighting | NO | |
| | Mixed Legacy - Individual Train with Highest A-weighting | NO | |
| | | | |

B.1.4 PPV Results

| SITE 1 | 1300 block of PARK ROAD NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|------------------------------------|--|--------------------|--------|--------|------------------|------------|------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0012 | 0.0008 | 0.0005 | 0 - 0.0236 | 0 - 0.0062 | 0 - 0.0801 |
| Basement | | | | | | | |
| 5-Jun-17, 4:58:00 PM to 9:10:50 PM | | | | | | | |

B.1.5 Passby Vibration Spectra and Overall Levels




Figure 3: *Site 1 at Location V1 Basement Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 4: *Site 1 at Location V1 Basement Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 5: *Site 1 at Location V1 Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 6: *Site 1 at Location V1 Basement Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 7: *Site 1 at Location V2 1st Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 8: *Site 1 at Location V2 1st Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 9: *Site 1 at Location V2 1st Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 10: *Site 1 at Location V2 1st Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 11: *Site 1 at Location V3 2nd Floor Playroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 12: *Site 1 at Location V3 2nd Floor Playroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 13: *Site 1 at Location V3 2nd Floor Playroom
 Outbound Trains on Track 1
 Individual Train with Highest Overall Vibration*




Figure 14: *Site 1 at Location V3 2nd Floor Playroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 15: *Site 1 at Location V4 Outside House
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 16: *Site 1 at Location V4 Outside House
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 17: *Site 1 at Location V4 Outside House
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 18: *Site 1 at Location V4 Outside House
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 19: *Site 1 at Location V5 Across Street
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 20: *Site 1 at Location V5 Across Street
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 21: *Site 1 at Location V5 Across Street
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 22: *Site 1 at Location V5 Across Street
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 23: *Site 1 at Location V6 Across Street
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 24: *Site 1 at Location V6 Across Street
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 25: *Site 1 at Location V6 Across Street
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 26: *Site 1 at Location V6 Across Street
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration*

B.1.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 27: *Site 1 at Microphone N1 in Basement Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 28: *Site 1 at Microphone N1 in Basement Bedroom
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 29: *Site 1 at Microphone N1 in Basement Bedroom
 Outbound Trains on Track 1
 Individual Train with Highest A-weighted Level*




Figure 30: *Site 1 at Microphone N1 in Basement Bedroom
 Inbound Trains on Track 2
 Individual Train with Highest A-weighted Level*




Figure 31: *Site 1 at Microphone N2 in Basement Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 32: *Site 1 at Microphone N2 in Basement Bedroom
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 33: *Site 1 at Microphone N2 in Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 34: *Site 1 at Microphone N2 in Basement Bedroom
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*

B.2 Site 2 – 3600 block of New Hampshire Avenue NW (Residence)

B.2.1 Building and Tunnel Notes

| | |
|---------------------|--|
| Location: | Inbound track 2 side at 163+90 |
| Building Notes: | Single-family residential townhouse, attached rowhouse, 3 floors comprised of partial underground basement plus 2 upper floors, exterior wall of brick construction, wood-joint floor, renovated |
| Tunnel Structure: | Tunnel |
| Track Type: | Egg Fasteners |
| T/R Depth: | 43 to 45 feet |
| Train Speed: | 24 to 40 mph |
| Measurement Period: | Wednesday, 16 August 2017, 9:05 to 12:56 |

B.2.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|--|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| V1 | Outside House | 26 | 45 | 52 | 63 | 43 | 76 |
| Triaxial Geo. | Basement Family Room | 43 | 45 | 62 | 79 | 43 | 90 |
| V2 | | | | | | | |
| N1 | | | | | | | |
| Triaxial Geo. | Basement Laundry Room (Position 1 on bare concrete) | 43 | 45 | 62 | 79 | 43 | 90 |
| V3a | | | | | | | |
| V3b | Basement Laundry Room (Position 2 on finished flooring) | 43 | 45 | 62 | 79 | 43 | 90 |
| V4 | First Floor Living Room | | | | | | |
| V5 | First Floor Dining Room | | | | | | |
| N2 | | | | | | | |

Notes:

- Triaxial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth



Figure 35: Aerial Map of 3600 block of New Hampshire Residence and Exterior Measurement Location




Figure 36: Cross-section Sketch (not to scale) of 3600 block of New Hampshire Avenue NW Indoor and Exterior Measurement Locations

B.2.3 GBNV Assessment Summary

| SITE 2 3600 block of NEW HAMPSHIRE NW - ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|--|---------------|---------------------------------------|
| | >70 | |
| Ground-borne Vibration (GBV) | VdB? | Notes |
| 7000 Series - Average of Multiple Passbys | NO | |
| 6000 Series - Average of Multiple Passbys | NO | |
| 5000 Series - Average of Multiple Passbys | NO | |
| 3000 Series - Average of Multiple Passbys | NO | |
| 2000 Series - Average of Multiple Passbys | NO | |
| Mixed Legacy 3000/2000 Series - Average of Multiple Passbys | NO | |
| 7000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V5 |
| 6000 Series - Individual Train with Highest Overall Vibration | NO | |
| 5000 Series - Individual Train with Highest Overall Vibration | NO | |
| 3000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V5 |
| 2000 Series - Individual Train with Highest Overall Vibration | NO | |
| Mixed Legacy 3000/2000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V4 (1st floor living room) & V5 |
| | >40 | |
| Ground-borne Noise (GBN) | dBA? | Notes |
| 7000 Series - Average of Multiple Passbys | NO | |
| 6000 Series - Average of Multiple Passbys | NO | |
| 5000 Series - Average of Multiple Passbys | NO | |
| 3000 Series - Average of Multiple Passbys | NO | |
| 2000 Series - Average of Multiple Passbys | NO | |
| Mixed Legacy 3000/2000 Series - Average of Multiple Passbys | NO | |
| 7000 Series - Individual Train with Highest A-weighting | NO | |
| 6000 Series - Individual Train with Highest A-weighting | NO | |
| 5000 Series - Individual Train with Highest A-weighting | NO | |
| 3000 Series - Individual Train with Highest A-weighting | NO | |
| 2000 Series - Individual Train with Highest A-weighting | NO | |
| Mixed Legacy 3000/2000 Series - Individual Train with Highest A-weighting | NO | |

B.2.4 PPV Results

| SITE 2a | 3600 block of NEW HAMPSHIRE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|---|---|--------------------|--------|--------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0036 | 0.0034 | 0.0020 | 0.003 - 0.008 | 0.002 - 0.013 | 0.002 - 0.004 |
| Basement Laundry Room at V3a 16-Aug-17 9:02:50 AM to 11:11:10 AM | | | | | | | |

| SITE 2b | 3600 block of NEW HAMPSHIRE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|--|---|--------------------|--------|--------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0033 | 0.0034 | 0.0021 | 0.003 - 0.034 | 0.003 - 0.025 | 0.002 - 0.012 |
| Basement Family Room at V2 16-Aug-17 11:12:45 AM to 12:53:51 PM | | | | | | | |

B.2.5 Passby Vibration Spectra and Overall Levels




Figure 37: *Site 2 at Location V1 Outside
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 38: *Site 2 at Location V1 Outside
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 39: *Site 2 at Location V1 Outside
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 40: *Site 2 at Location V1 Outside
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 41: *Site 2 at Location V2 Basement Family Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*





Figure 42: *Site 2 at Location V2 Basement Family Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*



- 7000 Series Train 512
- 6000 Series Train 308
- 5000 Series Train 306
- 3000 Series Train 304
- 2000 Series Train 302
- Mixed Legacy 2000/3000 Series Train 301
- - - Ambient Background

Figure 43: *Site 2 at Location V2 Basement Family Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 44: *Site 2 at Location V2 Basement Family Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 45: *Site 2 at Location V3a Basement Laundry Room (bare concrete)
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 46: *Site 2 at Location V3a Basement Laundry Room (bare concrete)
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 47: *Site 2 at Location V3a Basement Laundry Room (bare concrete)
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 48: *Site 2 at Location V3a Basement Laundry Room (bare concrete)
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 49: *Site 2 at Location V3b Basement Laundry Room (finished flooring)
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 50: *Site 2 at Location V3b Basement Laundry Room (finished flooring)
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 51: *Site 2 at Location V3b Basement Laundry Room (finished flooring)
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 52: *Site 2 at Location V3b Basement Laundry Room (finished flooring)
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 53: *Site 2 at Location V4 First Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 54: *Site 2 at Location V4 First Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 55: *Site 2 at Location V4 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 56: *Site 2 at Location V4 First Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 57: *Site 2 at Location V5 First Floor Dining Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*






Figure 58: *Site 2 at Location V5 First Floor Dining Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*



- 7000 Series Train 512
- 6000 Series Train 506
- 5000 Series Train 305
- 3000 Series Train 304
- 2000 Series Train 302
- Mixed Legacy 2000/000 Series Train 301
- - - Ambient Background


Figure 59: *Site 2 at Location V5 First Floor Dining Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*



- 7000 Series Train 512
- 6000 Series Train 505
- 5000 Series Train 306
- 3000 Series Train 304
- 2000 Series Train 302
- Mixed Legacy 2000/3000 Series Train 301
- - - Ambient Background

Figure 60: *Site 2 at Location V5 First Floor Dining Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.2.6 Passby Ground-borne Noise Spectra and A-weighted Levels



**Figure 61: Site 2 at Location N1 Basement Family Room
 Outbound Trains on Track 1
 Average Noise Levels by Vehicle Type**




Figure 62: *Site 2 at Location N1 Basement Family Room
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 63: *Site 2 at Location N1 Basement Family Room
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 64: *Site 2 at Location N1 Basement Family Room
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*




Figure 65: *Site 2 at Location N2 First Floor Dining Room
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 66: *Site 2 at Location N2 First Floor Dining Room
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 67: *Site 2 at Location N2 First Floor Dining Room
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 68: *Site 2 at Location N2 First Floor Dining Room
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*

B.3 Site 3 – 700 block of Princeton Place (Residence)

B.3.1 Building and Tunnel Notes

Location: Outbound track 1 side at 169+00
 Building Notes: Single-family residential, attached rowhouse
 Tunnel Structure: Cut and Cover
 Track Type: Floating Slab Track
 T/R Depth: 50 to 52 feet
 Train Speed: 14 to 30 mph
 Measurement Period: Tuesday, 6 June 2017, 15:50 to 19:15

B.3.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|-----------------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| V1 | Basement Laundry Room | 326 | 52 | 330 | 289 | 51 | 293 |
| N1 | Basement Family Room | | | | | | |
| Triaxial Geo. | | | | | | | |
| V2 | | | | | | | |
| V3 | 1 st Floor Living Room | | | | | | |
| N2 | | | | | | | |
| V4 | 1st Floor Dining Room | | | | | | |
| V5 | Outside House | 330 | 52 | 334 | 293 | 51 | 297 |
| V6 | Back Alley | 297 | 51 | 301 | 259 | 50 | 264 |
| V7 | Back Alley | 268 | 52 | 273 | 230 | 51 | 236 |

Notes:

- Triaxial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth



Figure 69: Aerial Map of 700 block of Princeton Place NW Residence and Exterior Measurement Location




Figure 70: Cross-section Sketch (not to scale) of 700 block of Princeton Place Indoor and Exterior Measurement Locations

B.3.3 GBNV Assessment Summary

| | |
|---------------|--|
| SITE 3 | 700 block of PRINCETON PLACE – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT |
| | <i>Train vibration detectable in 63Hz band but overall vibration levels dominated by non-train ambient sources. Train ground-borne noise not audible</i> |
| | |

B.3.4 PPV Results

| | | | | | | | |
|--|--|--------------------|--------|--------|--------------------|---------------|-------------|
| SITE 3 | 700 block of PRINCETON PLACE – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0012 | 0.0005 | 0.0004 | 0.0003 - 0.0016 | 0 - 0.0071 | 0 - 0.00155 |
| Basement 6-Jun-17, 4:44:59 PM to 6:54:55 PM | | | | | | | |

B.3.5 Statistical Vibration Spectra




Figure 71: Site 3 at Location V1 Basement Laundry Room Hourly Percentile Vibration Levels






Figure 72: Site 3 at Location V1 Basement Laundry Room
Hourly Percentile Vibration Levels



**Figure 73: Site 3 at Location V1 Basement Laundry Room
 Hourly Percentile Vibration Levels**



**Figure 74: Site 3 at Location V1 Basement Laundry Room
 Hourly Percentile Vibration Levels**




Figure 75: Site 3 at Location V1 Basement Laundry Room
Hourly Percentile Vibration Levels




Figure 76: Site 3 at Location V1 Basement Laundry Room
Hourly Percentile Vibration Levels







Figure 77: Site 3 at Location V2 Basement Family Room
Hourly Percentile Vibration Levels



**Figure 78: Site 3 at Location V2 Basement Family Room
 Hourly Percentile Vibration Levels**



**Figure 79: Site 3 at Location V2 Basement Family Room
 Hourly Percentile Vibration Levels**



**Figure 80: Site 3 at Location V2 Basement Family Room
 Hourly Percentile Vibration Levels**




Figure 81: Site 3 at Location V2 Basement Family Room
Hourly Percentile Vibration Levels




Figure 82: Site 3 at Location V2 Basement Family Room
Hourly Percentile Vibration Levels




Figure 83: Site 3 at Location V3 First Floor Living Room
Hourly Percentile Vibration Levels





Figure 84: *Site 3 at Location V3 First Floor Living Room
 Hourly Percentile Vibration Levels*



**Figure 85: Site 3 at Location V3 First Floor Living Room
 Hourly Percentile Vibration Levels**







Figure 86: Site 3 at Location V3 First Floor Living Room
Hourly Percentile Vibration Levels




**Figure 87: Site 3 at Location V3 First Floor Living Room
Hourly Percentile Vibration Levels**



**Figure 88: Site 3 at Location V3 First Floor Living Room
 Hourly Percentile Vibration Levels**



**Figure 89: Site 3 at Location V4 First Floor Dining Room
Hourly Percentile Vibration Levels**



**Figure 90: Site 3 at Location V4 First Floor Dining Room
 Hourly Percentile Vibration Levels**





Figure 91: Site 3 at Location V4 First Floor Dining Room
Hourly Percentile Vibration Levels



**Figure 92: Site 3 at Location V4 First Floor Dining Room
 Hourly Percentile Vibration Levels**





Figure 93: Site 3 at Location V4 First Floor Dining Room
Hourly Percentile Vibration Levels



**Figure 94: Site 3 at Location V4 First Floor Dining Room
 Hourly Percentile Vibration Levels**




Figure 95: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels




Figure 96: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels




Figure 97: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels




Figure 98: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels




Figure 99: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels




Figure 100: Site 3 at Location V5 Outside House
Hourly Percentile Vibration Levels

B.4 Site 4 – Rock Creek Church Road NW & 9th Street NW (Outdoor Only)

B.4.1 Tunnel Notes

Tunnel Structure: Cut and Cover
Track Type: Floating Slab Track, Crossover
T/R Depth: 50 to 52 feet
Measurement Period: Friday, 2 June 2017, 12:22 to 15:23

Field Observations: Busy intersection just south of Georgia Ave station. Most foot traffic of all outdoor locations. Metro buses along New Hampshire Ave NW. Trains are audible through vent shaft grates. Accelerometers mounted to curbs.

B.4.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 170+00 | 34 | 52 | 62 | 71 | 52 | 88 |
| A2 | 170+00 | 41 | 52 | 66 | 78 | 52 | 94 |
| A3 | 169+50 | 72 | 52 | 89 | 109 | 52 | 121 |
| A4 | 169+00 | 101 | 52 | 114 | 138 | 52 | 147 |
| B1 | 168+50 | 178 | 50 | 185 | 215 | 50 | 221 |
| B2 | 169+00 | 206 | 52 | 212 | 243 | 52 | 249 |
| B3 | 169+50 | 235 | 52 | 241 | 272 | 52 | 277 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth




Figure 101: Aerial Map of Site 4 Measurement Positions

B.4.3 Overall Level vs Distance Plot




Figure 102: Site 4 Average Overall Level vs Distance

B.5 Site 5 – New Hampshire Avenue & Randolph Street NW (Outdoor Only)

B.5.1 Tunnel Notes

Tunnel Structure: Tunnel (just north of transition from cut and cover)

Track Type: Direct Fixation (DF)

T/R Depth: 76 to 86 feet

Measurement Period: Friday, 2 June 2017, 8:37 to 11:00

Field Observations: Just north of Georgia Ave station. Vehicles and Metro buses along New Hampshire Ave NW. A1-A3 accelerometers mounted to curb, all other accelerometers mounted to sidewalk.

B.5.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 181+50 | 83 | 85 | 119 | 46 | 85 | 97 |
| A2 | 181+50 | 131 | 85 | 156 | 94 | 85 | 127 |
| A3 | 182+00 | 183 | 83 | 201 | 147 | 83 | 169 |
| A4 | 182+00 | 237 | 83 | 251 | 200 | 83 | 217 |
| B1 | 183+00 | 323 | 81 | 333 | 286 | 81 | 297 |
| B2 | 183+00 | 365 | 81 | 374 | 328 | 81 | 338 |
| B3 | 183+50 | 463 | 79 | 470 | 426 | 79 | 433 |
| B4 | 184+00 | 537 | 76 | 542 | 500 | 76 | 506 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth



Figure 103: Aerial Map of Site 5 Measurement Positions

B.5.3 Overall Level vs Distance Plot




Figure 104: Site 5 Average Overall Level vs Distance

B.6 Site 6 – 4100 block of New Hampshire Avenue NW (Residence)

B.6.1 Building and Tunnel Notes

Location: Inbound track 2 side at 191+75

Building Notes: Residential attached rowhouse with 3 floors consisting of partial underground basement and 2 upper floors. Exterior walls of brick construction, foundation is below-grade slab. The residence is renovated and divided into 3 separate tenant condominiums. Bottom unit is the basement unit. Bottom unit renovated with Pergo flooring throughout.

Tunnel Structure: Tunnel

Track Type: Egg Fasteners

T/R Depth: 65 feet

Train Speed: 30 to 55 mph

Measurement Period: Tuesday, 15 August 2017, 9:01 to 13:02

Field Observations: Homeowners vacant during measurements, only Wilson Ihrig staff present. It was raining during the measurements, so the outdoor locations are affected to some degree.

B.6.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|--------------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| V1 | Outdoor at Sidewalk | 34 | 65 | 73 | 71 | 65 | 96 |
| V2 | Outdoor at [REDACTED] entrance | 41 | 65 | 77 | 78 | 65 | 102 |
| V3 | Near Bedroom | 72 | 65 | 97 | 109 | 65 | 127 |
| N1 | | 101 | 65 | 120 | 138 | 65 | 153 |
| V4 | Closet (on bare concrete) | 178 | 65 | 189 | 215 | 65 | 225 |
| Triaxial Geophone | | | | | | | |
| V5 | Far Bedroom | 206 | 65 | 216 | 243 | 65 | 252 |
| N2 | | 235 | 65 | 244 | 272 | 65 | 280 |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction

- c) N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- d) Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- e) T/R depth = top-of-rail depth
- f) Total slant distance to T/R = total distance from building to track, accounting for tunnel depth




Figure 105: Aerial Map of 4100 block of New Hampshire Ave NW Residence and Exterior Measurement Locations




Figure 106: Cross-section Sketch (not to scale) of 4100 block of New Hampshire Ave NW Residence Measurement Locations


B.6.3 GBNV Assessment Summary

| SITE 6 4100 block of NEW HAMPSHIRE NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | | |
|--|--|--------------------|--------------|
| Ground-borne Vibration (GBV) | | >70 VdB? | Notes |
| 7000 Series - Average of Multiple Passbys | | NO | |
| 6000 Series - Average of Multiple Passbys | | NO | |
| 5000 Series - Average of Multiple Passbys | | NO | |
| 3000 Series - Average of Multiple Passbys | | NO | |
| 2000 Series - Average of Multiple Passbys | | NO | |
| Mixed Legacy without 4000 Series - Average of Multiple Passbys | | NO | |
| 7000 Series - Individual Train with Highest Overall Vibration | | NO | |
| 6000 Series - Individual Train with Highest Overall Vibration | | NO | |
| 5000 Series - Individual Train with Highest Overall Vibration | | NO | |
| 3000 Series - Individual Train with Highest Overall Vibration | | NO | |
| 2000 Series - Individual Train with Highest Overall Vibration | | NO | |
| Mixed Legacy without 4000 Series - Individual Train with Highest Overall Vibration | | NO | |
| Ground-borne Noise (GBN) | | >40 dBA? | Notes |
| 7000 Series - Average of Multiple Passbys | | NO | |
| 6000 Series - Average of Multiple Passbys | | NO | |
| 5000 Series - Average of Multiple Passbys | | NO | |
| 3000 Series - Average of Multiple Passbys | | NO | |
| 2000 Series - Average of Multiple Passbys | | NO | |
| Mixed Legacy without 4000 Series - Average of Multiple Passbys | | NO | |
| 7000 Series - Individual Train with Highest A-weighting | | NO | |
| 6000 Series - Individual Train with Highest A-weighting | | NO | |
| 5000 Series - Individual Train with Highest A-weighting | | NO | |
| 3000 Series - Individual Train with Highest A-weighting | | NO | |
| 2000 Series - Individual Train with Highest A-weighting | | NO | |
| Mixed Legacy without 4000 Series - Individual Train with Highest A-weighting | | NO | |

B.6.4 PPV Results

| SITE 6 | 4100 block of NEW HAMPSHIRE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|---|--|--------------------|--------|--------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0031 | 0.0032 | 0.0021 | 0.003 - 0.005 | 0.002 - 0.013 | 0.002 - 0.007 |
| Basement 15-Aug-17, 9:08:51 AM to 1:04:40 PM | | | | | | | |

B.6.5 Passby Vibration Spectra and Overall Levels



**Figure 107: Site 6 at Location V1 Outdoor Sidewalk
 Outbound Trains on Track 1
 Average Vibration Levels by Vehicle Type**




Figure 108: *Site 6 at Location V1 Outdoor Sidewalk
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 109: Site 6 at Location V1 Outdoor Sidewalk
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 110: Site 6 at Location V1 Outdoor Sidewalk
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration





Figure 111: *Site 6 at Location V2 Outdoor at Entrance
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*



**Figure 112: Site 6 at Location V2 Outdoor at Entrance
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type**




Figure 113: *Site 6 at Location V2 Outdoor at Entrance
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 114: *Site 6 at Location V2 Outdoor at Entrance
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*





Figure 115: *Site 6 at Location V3 Near Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*



**Figure 116: Site 6 at Location V3 Near Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type**




Figure 117: *Site 6 at Location V3 Near Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 118: *Site 6 at Location V3 Near Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 119: *Site 6 at Location V5 Far Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 120: *Site 6 at Location V5 Far Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 121: Site 6 at Location V5 Far Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 122: *Site 6 at Location V5 Far Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.6.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 123: *Site 6 at Location N1 Near Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 124: *Site 6 at Location N1 Near Bedroom
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 125: *Site 6 at Location N1 Near Bedroom
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 126: *Site 6 at Location N1 Near Bedroom
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*




Figure 127: *Site 6 at Location N2 Far Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 128: *Site 6 at Location N2 Far Bedroom
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 129: *Site 6 at Location N2 Far Bedroom
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 130: *Site 6 at Location N2 Far Bedroom*
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level

B.7 Site 7 – 4300 block New Hampshire Avenue NW (Residence)

B.7.1 Building and Tunnel Notes

Location: Outbound Track 1 side at 203+50

Building Notes: multi-family residential townhouse, 3 floors comprised of partially-underground basement plus 2 upper floors, exterior wall of brick construction, wood frame construction?

Tunnel Structure: Earth Tunnel

Track Type: Egg Fasteners

T/R Depth: 65 feet

Train Speed: 29 to 61 mph

Measurement Period: Wednesday, 7 June 2017, 8:30 to 12:40

Field Observations: construction outside on street during measurements, which made some of the measured data unusable for train passby analysis

B.7.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|-----------------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| Triaxial Geophone | Basement Bedroom No 1 | 79 | 65 | 102 | 42 | 65 | 77 |
| V1 | | | | | | | |
| N1 | | | | | | | |
| V2 | Basement Bedroom No 2 | 79 | 65 | 102 | 42 | 65 | 77 |
| N2 | | | | | | | |
| V3 | 1 st Floor Living Room | 55 | 65 | 85 | 19 | 65 | 68 |
| V4 | Outside House | | | | | | |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth




Figure 131: Aerial Map of 4300 block of New Hampshire Residence and Exterior Measurement Location at Site 7 (nearby Sites 8, 9, and 10 also shown for reference)




Figure 132: Cross-section Sketch (not to scale) of 4300 block of New Hampshire Indoor and Exterior Measurement Locations

B.7.3 GBNV Assessment Summary

| SITE 7 | 4300 block of NEW HAMPSHIRE NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|---------------|---|--------------------|--------------|
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy with 4000 Series - Single Passby | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 6000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 3000 Series - Individual Train with Highest Overall Vibration | NO | |
| | Mixed Legacy - Individual Train with Highest Overall Vibration | NO | |
| | | | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series (Average of Multiple Passbys) | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 3000 Series - Individual Train with Highest A-weighting | NO | |
| | Mixed Legacy - Individual Train with Highest A-weighting | NO | |
| | | | |

B.7.4 PPV Results

| SITE 7 | 4300 block of NEW HAMPSHIRE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|-------------------------------------|--|--------------------|--------|--------|------------------|------------|------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0006 | 0.0005 | 0.0003 | 0 - 0.0012 | 0 - 0.0118 | 0 - 0.0016 |
| Basement | | | | | | | |
| 7-Jun-17, 8:38:58 AM to 12:41:10 PM | | | | | | | |

B.7.5 Passby Vibration Spectra and Overall Levels




Figure 133: *Site 7 at Location V1 Basement Bedroom #1
Outbound Trains on Track 1 (near track)
Average Vibration Levels by Vehicle Type*




Figure 134: *Site 7 at Location V1 Basement Bedroom #1
Inbound Trains on Track 2 (far track)
Average Vibration Levels by Vehicle Type*




Figure 135: *Site 7 at Location V1 Basement Bedroom #1
Outbound Trains on Track 1 (near track)
Individual Train with Highest Overall Vibration*




Figure 136: *Site 7 at Location V1 Basement Bedroom #1
 Inbound Trains on Track 2 (far track)
 Average Vibration Levels by Vehicle Type*




Figure 137: *Site 7 at Location V2 Basement Bedroom #2
Outbound Trains on Track 1 (near track)
Average Vibration Levels by Vehicle Type*




Figure 138: *Site 7 at Location V2 Basement Bedroom #2
Inbound Trains on Track 2 (far track)
Average Vibration Levels by Vehicle Type*




Figure 139: *Site 7 at Location V2 Basement Bedroom #2
Outbound Trains on Track 1 (near track)
Individual Train with Highest Overall Vibration*




Figure 140: *Site 7 at Location V2 Basement Bedroom #2
 Inbound Trains on Track 2 (far track)
 Individual Train with Highest Overall Vibration*




Figure 141: *Site 7 at Location V3 First Floor Living Room
Outbound Trains on Track 1 (near track)
Average Vibration Levels by Vehicle Type*




Figure 142: *Site 7 at Location V3 First Floor Living Room
Inbound Trains on Track 2 (far track)
Average Vibration Levels by Vehicle Type*




Figure 143: *Site 7 at Location V3 First Floor Living Room
Outbound Trains on Track 1 (near track)
Individual Train with Highest Overall Vibration*




Figure 144: *Site 7 at Location V3 First Floor Living Room
Inbound Trains on Track 2 (far track)
Individual Train with Highest Overall Vibration*




Figure 145: *Site 7 at Location V4 Outside House
Outbound Trains on Track 1 (near track)
Average Vibration Levels by Vehicle Type*




Figure 146: *Site 7 at Location V4 Outside House
Inbound Trains on Track 2 (far track)
Average Vibration Levels by Vehicle Type*




Figure 147: *Site 7 at Location V4 Outside House
Outbound Trains on Track 1 (near track)
Individual Train with Highest Overall Vibration*




Figure 148: *Site 7 at Location V4 Outside House
 Inbound Trains on Track 2 (far track)
 Individual Train with Highest Overall Vibration*

B.7.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 149: *Site 7 at Location N1 Basement Bedroom #1
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 150: *Site 7 at Location N1 Basement Bedroom #1
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 151: Site 7 at Location N1 Basement Bedroom #1
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level




Figure 152: Site 7 at Location N1 Basement Bedroom #1
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level




Figure 153: *Site 7 at Location N2 Basement Bedroom #2
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 154: *Site 7 at Location N2 Basement Bedroom #2
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 155: *Site 7 at Location N2 Basement Bedroom #2
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 156: Site 7 at Location N2 Basement Bedroom #2
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level

B.8 Site 8 – New Hampshire Avenue NW & Webster Street NW (Outdoor Only)

B.8.1 Tunnel Notes

Tunnel Structure: Earth Tunnel

Track Type: Egg Fasteners

T/R Depth: 65 to 70 feet

Measurement Period: Thursday, 1 June 2017, 9:12 to 11:40

B.8.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 205+00 | 80 | 67 | 104 | 43 | 67 | 80 |
| A2 | 205+00 | 130 | 67 | 146 | 94 | 67 | 115 |
| A3 | 205+50 | 189 | 69 | 201 | 153 | 69 | 168 |
| A4 | 206+00 | 244 | 70 | 254 | 208 | 70 | 219 |
| B1 | 204+00 | 45 | 65 | 79 | 81 | 65 | 104 |
| B2 | 203+50 | 96 | 66 | 116 | 133 | 66 | 148 |
| B3 | 203+50 | 124 | 66 | 140 | 161 | 66 | 174 |
| B4 | 203+50 | 156 | 66 | 169 | 192 | 66 | 203 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth



Figure 157: Aerial Map of Site 8 Measurement Positions (nearby Sites 7, 9, and 10 also shown for reference)

B.8.3 Overall Level vs Distance Plot




Figure 158: Site 8 Average Overall Level vs Distance

B.9 Site 9 – 4400 block of 5th Street NW (Residence)

B.9.1 Building and Tunnel Notes

Location: Inbound track 2 side at 204+50

Building Notes: single-family residential attached rowhouse, 3 floors comprised of partial underground basement plus 2 upper floors, foundation is below grade slab with exterior walls of brick construction, renovated

Tunnel Structure: Tunnel

Track Type: Egg Fasteners

T/R Depth: 73 to 74 feet (track 2) / 45 feet (track 1)

Train Speed: 23 to 73 mph

Measurement Period: Wednesday, 9 August 2017, 10:07 to 14:00

Field Observations:

B.9.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|---------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| V1 | Outside (far) on Driveway | 174 | 73 | 189 | 211 | 45 | 216 |
| V2 | Outside (near) on Steps | 197 | 73 | 210 | 234 | 45 | 238 |
| Tri-axial geophone | Basement Laundry Room | 195 | 73 | 208 | 232 | 45 | 236 |
| V3 | | | | | | | |
| N1 | | | | | | | |
| V4 | Basement Bedroom | | | | | | |
| N2 | | | | | | | |
| V5 | First Floor Kitchen | | | | | | |
| V6 | First Floor Dining Room | | | | | | |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth




Figure 159: Aerial Map of 4400 block of 5th Street NW Residence and Exterior Measurement Locations at Site 9 (nearby Sites 8 and 10 shown for reference)




Figure 160: Cross-section Sketch (not to scale) of 4400 block of 5th Street NW Residence and Exterior Measurement Locations

B.9.3 GBNV Assessment Summary

| SITE 9 | 4400 block of 5th STREET NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|---------------|--|--------------------|--------------|
| | | | |
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Single Passby | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 5000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 6000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 5000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 3000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 2000 Series - Individual Train with Highest Overall Vibration | NO | |
| | Mixed Legacy without 4000 Series - Individual Train with Highest Overall Vibration | NO | |
| | | | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Single Passby | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 5000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 5000 Series - Individual Train with Highest A-weighting | NO | |
| | 3000 Series - Individual Train with Highest A-weighting | NO | |
| | 2000 Series - Individual Train with Highest A-weighting | NO | |
| | Mixed Legacy without 4000 Series - Individual Train with Highest A-weighting | NO | |
| | | | |

B.9.4 PPV Results

| SITE 9 | 4400 block of 5th STREET NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|---|---|--------------------|--------|-------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0029 | 0.0029 | 0.002 | 0.002 - 0.003 | 0.002 - 0.007 | 0.002 - 0.004 |
| Basement 9-Aug-17, 10:18:15 AM to 2:10:14 PM | | | | | | | |

B.9.5 Passby Vibration Spectra and Overall Levels




Figure 161: *Site 9 at Location V1 Outside Far
 Outbound Trains on Track 1
 Average Vibration Levels by Vehicle Type*




Figure 162: *Site 9 at Location V1 Outside Far
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 163: *Site 9 at Location V1 Outside Far
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 164: *Site 9 at Location V1 Outside Far
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 165: *Site 9 at Location V2 Outside Near
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 166: *Site 9 at Location V2 Outside Near
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 167: *Site 9 at Location V2 Outside Near
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 168: *Site 9 at Location V2 Outside Near
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 169: *Site 9 at Location V3 Basement Laundry Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 170: *Site 9 at Location V3 Basement Laundry Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*





Figure 171: Site 9 at Location V3 Basement Laundry Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration



**Figure 172: Site 9 at Location V3 Basement Laundry Room
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration**




Figure 173: *Site 9 at Location V4 Basement Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 174: *Site 9 at Location V4 Basement Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*





Figure 175: *Site 9 at Location V4 Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*



**Figure 176: Site 9 at Location V4 Basement Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration**




Figure 177: *Site 9 at Location V5 First Floor Kitchen
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 178: *Site 9 at Location V5 First Floor Kitchen
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 179: *Site 9 at Location V5 First Floor Kitchen*
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 180: *Site 9 at Location V5 First Floor Kitchen
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 181: *Site 9 at Location V6 First Floor Dining Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 182: *Site 9 at Location V6 First Floor Dining Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 183: *Site 9 at Location V6 First Floor Dining Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 184: *Site 9 at Location V6 First Floor Dining Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.9.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 185: *Site 9 at Location N1 Basement Laundry Room
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 186: *Site 9 at Location N1 Basement Laundry Room
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 187: *Site 9 at Location N1 Basement Laundry Room
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 188: *Site 9 at Location N1 Basement Laundry Room
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*




Figure 189: *Site 9 at Location N2 Basement Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 190: *Site 9 at Location N2 Basement Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 191: *Site 9 at Location N2 Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*




Figure 192: *Site 9 at Location N2 Basement Bedroom
 Inbound Trains on Track 2
 Individual Train with Highest A-weighted Level*

B.10 Site 10 – 4400 block of New Hampshire Avenue NW (Residence)

B.10.1 Building and Tunnel Notes

Location: Outbound Track 1 side at 206+75

Building Notes: Residential attached rowhouse with 3 floors consisting of partial underground basement and 2 upper floors. Exterior walls of brick construction, foundation is below-grade slab. One family/tenant for whole house.

Tunnel Structure: Tunnel

Track Type: Egg Fasteners

T/R Depth: 75 feet

Train Speed: 33 to 63 mph

Measurement Period: Tuesday, 8 August 2017, 10:03 to 13:59

B.10.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|---------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| Triaxial Geophone | Basement | 79 | 75 | 109 | 42 | 75 | 86 |
| V1 | | | | | | | |
| N1 | Basement 1/3 from walls | | | | | | |
| N2 | Basement corner | | | | | | |
| V2 | First Floor Living Room | | | | | | |
| V3 | First Floor Dining Room | | | | | | |
| V4 | Outside | 54 | 75 | 92 | 17 | 75 | 77 |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth



Figure 193: Aerial Map of 4400 block of New Hampshire Residence and Exterior Measurement Location (nearby Site 8 also shown for reference)




Figure 194: Cross-section Sketch (not to scale) of 4400 block of New Hampshire NW Residence Measurement Locations


B.10.3 GBNV Assessment Summary

| SITE 10 | 4400 block of NEW HAMPSHIRE AVENUE NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|----------------|--|--------------------|-----------------|
| | | | |
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys | YES* | *pos. V2 and V3 |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | YES* | *pos. V2 and V3 |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V2 and V3 |
| | 6000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V2 |
| | 3000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V2 and V3 |
| | 2000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V2 and V3 |
| | Mixed Legacy without 4000 Series - Individual Train with Highest Overall Vibration | YES* | *pos. V2 and V3 |
| | | | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 3000 Series - Individual Train with Highest A-weighting | NO | |
| | 2000 Series - Individual Train with Highest A-weighting | NO | |
| | Mixed Legacy without 4000 Series - Individual Train with Highest A-weighting | NO | |
| | | | |

B.10.4 PPV Results

| SITE 10 | 4400 block of NEW HAMPSHIRE AVENUE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|---|---|--------------------|--------|--------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0031 | 0.0032 | 0.0027 | 0.003 - 0.011 | 0.002 - 0.023 | 0.002 - 0.017 |
| Basement 8-Aug-17, 10:09:29 AM to 2:03:43 PM | | | | | | | |

B.10.5 Passby Vibration Spectra and Overall Levels



**Figure 195: Site 10 at Location V1 Basement
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type**




Figure 196: *Site 10 at Location V1 Basement
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 197: *Site 10 at Location V1 Basement
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*






Figure 198: *Site 10 at Location V1 Basement
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*



**Figure 199: Site 10 at Location V2 First Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type**



**Figure 200: Site 10 at Location V2 First Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type**




Figure 201: Site 10 at Location V2 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration





Figure 202: *Site 10 at Location V2 First Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*



**Figure 203: Site 10 at Location V3 First Floor Dining Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type**




Figure 204: *Site 10 at Location V3 First Floor Dining Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 205: *Site 10 at Location V3 First Floor Dining Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 206: *Site 10 at Location V3 First Floor Dining Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 207: *Site 10 at Location V4 Outside
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 208: *Site 10 at Location V4 Outside
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 209: *Site 10 at Location V4 Outside
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 210: *Site 10 at Location V4 Outside
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.10.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 211: *Site 10 at Location N1 Basement
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 212: *Site 10 at Location N1 Basement
Inbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 213: Site 10 at Location N1 Basement
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level




Figure 214: *Site 10 at Location N1 Basement
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*

B.11 Site 11 – New Hampshire Avenue NW & Buchanan Street NW (Outdoor Only)

B.11.1 Tunnel Notes

Tunnel Structure: Earth Tunnel

Track Type: Standard DF

T/R Depth: 90 to 95 feet

Measurement Period: Thursday, 1 June 2017, 13:10 to 15:21

Field Observations: Minimal road traffic on Buchanan, some Metro buses along New Hampshire. Trains are audible through vent shaft grate. Accelerometers mounted to curbs. Construction activity across 4th street on Buchanan.

B.11.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 214+00 | 68 | 92 | 114 | 31 | 92 | 97 |
| A2 | 214+00 | 88 | 92 | 127 | 51 | 92 | 105 |
| A3 | 214+50 | 108 | 93 | 143 | 71 | 93 | 117 |
| A4 | 215+00 | 163 | 95 | 189 | 127 | 95 | 159 |
| B1 | 213+00 | 54 | 90 | 105 | 90 | 90 | 127 |
| B2 | 213+00 | 74 | 90 | 117 | 111 | 90 | 143 |
| B3 | 213+00 | 94 | 90 | 130 | 131 | 90 | 159 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth



Figure 215: Aerial Map of 4600 block of New Hampshire Residence and Exterior Measurement Location at Site 11 (with nearby Sites 12 and 13 shown for reference)

B.11.3 Overall Level vs Distance Plot




Figure 216: Site 11 Average Overall Level vs Distance

B.12 Site 12 – 4600 block of 4th Street NW (Residence)

B.12.1 Building and Tunnel Notes

Location: Inbound Track 2 side at 214+75

Building Notes: Residential attached rowhouse with 3 floors consisting of partial underground basement and 2 upper floors. Exterior walls of brick construction, foundation is below-grade slab. House is at end of row.

Tunnel Structure: Tunnel

Track Type: DF

T/R Depth: 95 feet

Train Speed: 39 to 69 mph

Measurement Period: Monday, 14 August 2017, 14:35 to 18:36

B.12.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | | |
|-------------------------|---------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|-------------------------|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | |
| V1 | Outside Far | 176 | 85 | 200 | 212 | 95 | 232 | |
| V2 | Outside Near | 183 | 95 | 206 | 220 | 95 | 240 | |
| Triaxial Geophone | Basement Bedroom | 185 | 95 | 208 | 222 | 95 | 241 | |
| V3 | | | | | | | | |
| N1 | | | | | | | | |
| V4 | | | | | | | | First Floor Dining Room |
| V5 | | | | | | | | First Floor Living Room |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches feet above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth



Figure 217: Aerial Map of 4600 block of 4th Street NW Residence and Exterior Measurement Location (with nearby Sites 11 and 13 shown for reference)




Figure 218: Cross-section Sketch (not to scale) of 4600 block of 4th Street NW Residence Measurement Locations

B.12.3 GBNV Assessment Summary

| SITE 12 | 4600 block of 4TH STREET NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|---------|---|--------------------|--------------|
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | 7000 Series - Individual Train with Highest Overall Vibration | NO | |
| | 6000 Series - Individual Train with Highest Overall Vibration | YES | V4 |
| | 2000 Series - Individual Train with Highest Overall Vibration | NO | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 2000 Series - Average of Multiple Passbys | NO | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 2000 Series - Individual Train with Highest A-weighting | NO | |

B.12.4 PPV Results

| SITE 12 | 4600 block of 4TH STREET NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|---|---|--------------------|-------|--------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0032 | 0.003 | 0.0021 | 0.003 - 0.018 | 0.002 - 0.008 | 0.002 - 0.027 |
| Basement 14-Aug-17, 2:36:21 PM to 6:34:08 PM | | | | | | | |

B.12.5 Passby Vibration Spectra and Overall Levels




Figure 219: *Site 12 at Location V1 Outside Far
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 220: *Site 12 at Location V1 Outside Far
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 221: *Site 12 at Location V1 Outside Far
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 222: Site 12 at Location V1 Outside Far
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration




Figure 223: *Site 12 at Location V2 Outside Near Outbound Trains on Track 1 Average Vibration Levels by Vehicle Type*




Figure 224: *Site 12 at Location V2 Outside Near Inbound Trains on Track 2 Average Vibration Levels by Vehicle Type*





Figure 225: Site 12 at Location V2 Outside Near Outbound Trains on Track 1
Individual Train with Highest Overall Vibration



**Figure 226: Site 12 at Location V2 Outside Near
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration**




Figure 227: *Site 12 at Location V3 Basement Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 228: *Site 12 at Location V3 Basement Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 229: Site 12 at Location V3 Basement Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 230: Site 12 at Location V3 Basement Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration




Figure 231: *Site 12 at Location V4 First Floor Dining Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 232: *Site 12 at Location V4 First Floor Dining Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 233: *Site 12 at Location V4 First Floor Dining Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 234: *Site 12 at Location V4 First Floor Dining Room
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration*




Figure 235: *Site 12 at Location V5 First Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 236: *Site 12 at Location V5 First Floor Living Room
 Inbound Trains on Track 2
 Average Vibration Levels by Vehicle Type*




Figure 237: Site 12 at Location V5 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 238: *Site 12 at Location V5 First Floor Living Room
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration*

B.12.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 239: *Site 12 at Location N1 Basement Bedroom
 Outbound Trains on Track 1
 Average Noise Levels by Vehicle Type*




Figure 240: *Site 12 at Location N1 Basement Bedroom
 Inbound Trains on Track 2
 Average Noise Levels by Vehicle Type*




Figure 241: *Site 12 at Location N1 Basement Bedroom*
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level




Figure 242: *Site 12 at Location N1 Basement Bedroom
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*

B.13 Site 13 – 4600 block of New Hampshire Avenue NW (Residence)

B.13.1 Building and Tunnel Notes

Location: Inbound track 2 side at 216+10

Building Notes: single-family residential townhouse, attached rowhouse, 3 floors comprised of partial underground basement plus 2 upper floors, exterior wall of brick and interior wood frame construction

Tunnel Structure: Earth Tunnel

Track Type: Direct Fixation

T/R Depth: 97 to 98 feet

Train Speed: 43 to 74 mph

Measurement Period: Thursday, 8 June 2017, 14:58 to 19:26

Field Observations: 2nd floor noise mostly due to street traffic coming through windows

B.13.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|---------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| Tri-axial geophone | Basement Family Room | 87 | 98 | 131 | 124 | 97 | 157 |
| V1 | | | | | | | |
| N1 | | | | | | | |
| V2 | First Floor Living Room | 87 | 98 | 131 | 124 | 97 | 157 |
| N2 | Second Floor Bedroom | | | | | | |
| V3 | | | | | | | |
| V4 | Outside House | 59 | 98 | 114 | 95 | 97 | 136 |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth




Figure 243: Aerial Map of 4600 block of New Hampshire Residence and Exterior Measurement Location at Site 13 (with nearby Sites 11 and 12 shown for reference)




Figure 244: Cross-section Sketch (not to scale) of 4600 block of New Hampshire Avenue NW Indoor and Exterior Measurement Locations

B.13.3 GBNV Assessment Summary

| SITE 13 | 4600 block of NEW HAMPSHIRE AVENUE NW – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|----------------|--|--------------------|--------------|
| | | | |
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 4000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest Overall Vibration | YES | |
| | 6000 Series - Individual Train with Highest Overall Vibration | YES | V3 |
| | 4000 Series - Individual Train with Highest Overall Vibration | YES | V3 |
| | 3000 Series - Individual Train with Highest Overall Vibration | NO | |
| | Mixed Legacy without 4000 Series - Individual Train with Highest Overall Vibration | YES | V2 and V3 |
| | | | |
| | Ground-borne Noise (GBN) | >40 dBA? | Notes |
| | 7000 Series - Average of Multiple Passbys | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 4000 Series - Average of Multiple Passbys | NO | |
| | 3000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | | | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | 4000 Series - Individual Train with Highest A-weighting | NO | |
| | 3000 Series - Individual Train with Highest A-weighting | NO | |
| | Mixed Legacy without 4000 Series - Individual Train with Highest A-weighting | NO | |

B.13.4 PPV Results

| SITE 13 | 4600 block of NEW HAMPSHIRE AVENUE NW – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|--|---|--------------------|--------|--------|------------------|------------|------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.0005 | 0.0006 | 0.0003 | 0 - 0.0022 | 0 - 0.0115 | 0 - 0.0102 |
| Basement 8-Jun-17, 3:04:16 PM to 7:00:48 PM | | | | | | | |

B.13.5 Passby Vibration Spectra and Overall Levels




Figure 245: *Site 13 at Location V1 Basement Family Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 246: *Site 13 at Location V1 Basement Family Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 247: *Site 13 at Location V1 Basement Family Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 248: *Site 13 at Location V1 Basement Family Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 249: *Site 13 at Location V2 First Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*





Figure 250: *Site 13 at Location V2 First Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*



**Figure 251: Site 13 at Location V2 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration**




Figure 252: *Site 13 at Location V2 First Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 253: *Site 13 at Location V3 Second Floor Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 254: *Site 13 at Location V3 Second Floor Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 255: *Site 13 at Location V3 Second Floor Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 256: *Site 13 at Location V3 Second Floor Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*




Figure 257: *Site 13 at Location V4 Outside
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*





Figure 258: *Site 13 at Location V4 Outside
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*



- 7000 Series Train
- 6000 Series Train
- 4000 Series Train
- 3000 Series Train
- Mixed Legacy 6000/3000 Series Train
- - - Ambient Background

Figure 259: *Site 13 at Location V4 Outside
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 260: *Site 13 at Location V4 Outside
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.13.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 261: *Site 13 at Location N1 Basement Family Room
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 262: *Site 13 at Location N1 Basement Family Room
Outbound Trains on Track 2
Average Noise Levels by Vehicle Type*




Figure 263: *Site 13 at Location N1 Basement Family Room
 Outbound Trains on Track 1
 Individual Train with Highest A-weighted Level*




Figure 264: *Site 13 at Location N1 Basement Family Room
 Outbound Trains on Track 2
 Individual Train with Highest A-weighted Level*




Figure 265: *Site 13 at Location N2 Second Floor Bedroom
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*




Figure 266: *Site 13 at Location N2 Second Floor Bedroom
 Outbound Trains on Track 2
 Average Noise Levels by Vehicle Type*




Figure 267: *Site 13 at Location N2 Second Floor Bedroom
 Outbound Trains on Track 1
 Individual Train with Highest A-weighted Level*




Figure 268: *Site 13 at Location N2 Second Floor Bedroom
 Outbound Trains on Track 2
 Individual Train with Highest A-weighted Level*

B.14 Site 14 – Gallatin Street NE & 8th Street NE (Outdoor Only)

B.14.1 Tunnel Notes

Tunnel Structure: Cut and Cover

Track Type: Standard DF, Crossover

T/R Depth: 33 to 46 feet

Measurement Period: Thursday, 1 June 2017, 16:45 to 19:55

Field Observations: Quieter street with less road traffic, some Metro buses along Gallatin. Perceptible vibration on the ground. Trains are audible through vent shaft grates across the street. Accelerometers mounted to sidewalk. Street plate in intersection caused high vibration when buses and trucks rolled over plate.

B.14.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| A1 | 284+50 | 114 | 34 | 119 | 93 | 34 | 99 |
| A2 | 285+50 | 102 | 33 | 107 | 79 | 33 | 86 |
| A3 | 286+00 | 96 | 34 | 102 | 71 | 34 | 79 |
| A4 | 286+50 | 97 | 36 | 103 | 70 | 36 | 79 |
| B1 | 287+50 | 123 | 46 | 131 | 94 | 46 | 105 |
| B2 | 287+50 | 152 | 46 | 159 | 123 | 46 | 131 |
| B3 | 287+50 | 197 | 46 | 202 | 168 | 46 | 174 |
| B4 | 287+50 | 231 | 46 | 236 | 203 | 46 | 208 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth



Figure 269: Aerial Map of Site 14 Measurement Positions (nearby Site 15 exterior positions also shown)

B.14.3 Overall Level vs Distance Plot




Figure 270: Site 14 Average Overall Level vs Distance

B.15 Site 15 – 800 block of Gallatin Street NE (Residence)

B.15.1 Building and Tunnel Notes

Location: Outbound Track 1 side at 288+00

Building Notes: Single-family residential, detached duplex building, brick wood frame, renovated

Tunnel Structure: Tunnel

Track Type: Direct Fixation Fasteners

T/R Depth: 42 feet

Train Speed: 31 to 59 mph

Measurement Period: Wednesday, 16 August 2017, 17:00 to 20:15

Field Observations: street plate at intersection of Gallatin and 8th, central air conditioning and other interior mechanical sources interfere at times

B.15.2 Measurement Positions

| Sensor ^{a,b,c} | Location / Room Occupancy | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|-------------------------|---------------------------|--|----------------------------------|--|-------------------------------|----------------------------------|--|
| | | Horizontal Distance ^d (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) | Horizontal Distance (feet) | T/R Depth ^e (feet) | Total Slant Distance to T/R ^f (feet) |
| V1 | Outside House | 127 | 42 | 134 | 97 | 42 | 106 |
| Triaxial Geophone | Basement | 126 | 42 | 133 | 97 | 42 | 106 |
| V2 | | | | | | | |
| N1 | | | | | | | |
| V3 | First Floor Living Room | 126 | 42 | 133 | 97 | 42 | 106 |
| N2 | | | | | | | |
| V4 | Second Floor Bedroom | 126 | 42 | 133 | 97 | 42 | 106 |
| N3 | | | | | | | |

Notes:

- Tri-axial geophone mounted on floor, logging peak particle velocity
- V# vibration locations with accelerometer mounted on floor in vertical direction
- N# noise locations with microphone/sound level meter mounted on tripod 48 inches above floor
- Horizontal distance from track to building façade for indoor locations, not accounting for tunnel depth.
- T/R depth = top-of-rail depth
- Total slant distance to T/R = total distance from building to track, accounting for tunnel depth



Figure 271: Aerial Map of 800 block of Gallatin Street NE Residence and Exterior Measurement Location V1 at Site 15 (nearby Site 14 exterior positions also shown)




Figure 272: Cross-section Sketch (not to scale) of 800 block of Gallatin Street NE Residence Measurement Locations


B.15.3 GBNV Assessment Summary

| SITE 15 | 800 block of GALLATIN STREET NE – ATTENDED PASSBY MEASUREMENT GBNV ASSESSMENT | | |
|---------|---|--------------------|--------------|
| | Ground-borne Vibration (GBV) | >70 VdB? | Notes |
| | 7000 Series - Average of Multiple Passbys* | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | 5000* Series - Single Passby | NO | Track 2 only |
| | Mixed Legacy without 4000 Series - Average of Multiple Passbys | NO | |
| | Ground-borne Noise (GBN) | >35 dBA? | Notes |
| | 7000 Series - Single Passby | NO | |
| | 6000 Series - Average of Multiple Passbys | NO | |
| | Mixed Legacy without 4000 Series | NO | |
| | 7000 Series - Individual Train with Highest A-weighting | NO | |
| | 6000 Series - Individual Train with Highest A-weighting | NO | |
| | | | |
| | | | |

B.15.4 PPV Results

| SITE 15 | 800 block of GALLATIN STREET NE – POTENTIAL FOR BUILDING VIBRATION DAMAGE ASSESSMENT | | | | | | |
|------------------------------------|--|--------------------|--------|-------|------------------|---------------|---------------|
| | >0.2 in/sec PPV in any direction? | Average PPV (in/s) | | | PPV Range (in/s) | | |
| | | Tran | Vert | Long | Tran | Vert | Long |
| | NO | 0.003 | 0.0029 | 0.002 | 0.002 - 0.008 | 0.002 - 0.014 | 0.002 - 0.007 |
| Basement | | | | | | | |
| 8-Jun-17, 5:19:12 PM to 8:33:06 PM | | | | | | | |

B.15.5 Passby Vibration Spectra and Overall Levels



**Figure 273: Site 15 at Location V1 Outside
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type**




Figure 274: *Site 15 at Location V1 Outside
 Inbound Trains on Track 2
 Average Vibration Levels by Vehicle Type*




Figure 275: *Site 15 at Location V1 Outside
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 276: *Site 15 at Location V1 Outside
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*





Figure 277: *Site 15 at Location V2 Basement
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*



- 7000 Series (L Avg. 3 passbys)
- 6000 Series (L Avg. 9 passbys)
- 5000 Series Train 504 (single passby)
- Mixed Legacy w/out 4000 Series (L Avg. 2 passbys)
- - - Ambient Background

Figure 278: *Site 15 at Location V2 Basement
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 279: Site 15 at Location V2 Basement
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration




Figure 280: *Site 15 at Location V2 Basement
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration*




Figure 281: *Site 15 at Location V3 First Floor Living Room
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*




Figure 282: *Site 15 at Location V3 First Floor Living Room
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 283: *Site 15 at Location V3 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*






Figure 284: *Site 15 at Location V3 First Floor Living Room
 Inbound Trains on Track 2
 Individual Train with Highest Overall Vibration*



- 7000 Series (L Avg. 2 passbys) Ceiling Fan on during 1 of 2 passbys
- 6000 Series (L Avg. 8 passbys) Ceiling Fan on during 4 of 8 passbys
- Mixed Legacy 3000/2000 Series Train 309 (single passby) Ceiling Fan off
- Ambient Background, Ceiling Fan on
- Ambient Background, Ceiling Fan off

Figure 285: *Site 15 at Location V4 Second Floor Bedroom
Outbound Trains on Track 1
Average Vibration Levels by Vehicle Type*



- 7000 Series (L Avg. 3 passbys) Ceiling Fan on during 2 of 3 passbys
- 6000 Series (L Avg. 7 passbys) Ceiling Fan on during 6 of 7 passbys
- - - Mixed Legacy 3000/2000 Series Train 301 (single passby) Ceiling Fan off
- - - Ambient Background, Ceiling Fan on
- - - Ambient Background, Ceiling Fan off

Figure 286: *Site 15 at Location V4 Second Floor Bedroom
Inbound Trains on Track 2
Average Vibration Levels by Vehicle Type*




Figure 287: *Site 15 at Location V4 Second Floor Bedroom
Outbound Trains on Track 1
Individual Train with Highest Overall Vibration*




Figure 288: *Site 15 at Location V4 Second Floor Bedroom
Inbound Trains on Track 2
Individual Train with Highest Overall Vibration*

B.15.6 Passby Ground-borne Noise Spectra and A-weighted Levels




Figure 289: *Site 15 at Location N1 Basement
 Outbound Trains on Track 1
 Average Noise Levels by Vehicle Type*




Figure 290: *Site 15 at Location N1 Basement
 Inbound Trains on Track 2
 Average Noise Levels by Vehicle Type*




Figure 291: *Site 15 at Location N1 Basement*
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level





Figure 292: *Site 15 at Location N1 Basement
 Inbound Trains on Track 2
 Individual Train with Highest A-weighted Level*



- 7000 Series Train (single passby) Ceiling Fan on
- 6000 Series (L Avg. 5 passbys) Ceiling Fan on during 4 of 5 passbys
- Mixed Legacy 3000/2000 Series Train (single passby) Ceiling Fan off
- Ambient Background, Ceiling Fan on
- Ambient Background, Ceiling Fan off

Figure 293: *Site 15 at Location N2 First Floor Living Room
Outbound Trains on Track 1
Average Noise Levels by Vehicle Type*





Figure 294: *Site 15 at Location N2 First Floor Living Room
 Inbound Trains on Track 2
 Average Noise Levels by Vehicle Type*



- 7000 Series Train, Ceiling Fan on
- 6000 Series Train, Ceiling Fan off
- Mixed Legacy 3000/2000 Series Train, Ceiling Fan off
- - - Ambient Background, Ceiling Fan on
- - - Ambient Background, Ceiling Fan off

Figure 295: *Site 15 at Location N2 First Floor Living Room
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level*





Figure 296: *Site 15 at Location N2 First Floor Living Room
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*



- 7000 Series Train
- 6000 Series Train
- - - Mixed Legacy 3000/2000 Series Train
- - - Ambient Background, with lawn mower across street
- - - Ambient Background

Figure 297: *Site 15 at Location N3 Second Floor Bedroom*
Outbound Trains on Track 1
Individual Train with Highest A-weighted Level




Figure 298: *Site 15 at Location N3 Second Floor Bedroom
Inbound Trains on Track 2
Individual Train with Highest A-weighted Level*

B.16 Site 16 – Gallatin Street NE (Outdoor Only)

B.16.1 Tunnel Notes

Tunnel Structure: Tunnel

Track Type: Direct Fixation

T/R Depth: 55 to 60 feet

Measurement Period: Wednesday, 16 August 2017, 17:45 to 19:45

B.16.2 Measurement Positions

| Recorder Channel | Chainage (50 ft) | INBOUND TRACK 2 | | | OUTBOUND TRACK 1 | | |
|------------------|------------------|-----------------------|------------------|-----------------------------|-----------------------|------------------|-----------------------------|
| | | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) | Perp. distance (feet) | T/R Depth (feet) | Total slant distance (feet) |
| V1 | 304+25 | 106 | 56 | 120 | 69 | 56 | 89 |
| V2 | 303+35 | 95 | 60 | 112 | 59 | 60 | 84 |

Perp. distance = perpendicular distance to track, not accounting for tunnel depth

T/R depth = top-of-rail depth

Total slant distance = total distance to track, accounting for tunnel depth




Figure 299: Aerial Map of Site 16 Measurement Positions

B.16.3 Overall Level vs Distance Plot




Figure 300: Site 16 Average Overall Level vs Distance